MODEL ARPLANE NEWS

GRUMMAN PANTHER

IN THIS BIG ISSUE! • Chockful of PLANS for: Unusual Tailless Rubber Model..Free Flight Gas.. Class C Towline • ALSO — Latest Radio Control & License Data.. Helpful Hints on Glow Plug..How to Check Engine Hcrsepower..Wylam Masterplans..C. H. Grant ..Bill Winter's Scrap Box..W.W.I..Club News..West Coast Tips..Big Plane News..Etc.

APRIL 1948

25 CENTS

Digital Edition Magazines.

This issue magazine after the initial original scanning, has been digitally processing for better results and lower capacity Pdf file from me.

The plans and the articles that exist within, you can find published at full dimensions to build a model at the following websites.

All Plans and Articles can be found here:

HIsat Blog Free Plans and Articles.

http://www.rcgroups.com/forums/member.php?u=107085

AeroFred Gallery Free Plans.

http://aerofred.com/index.php

Hip Pocket Aeronautics Gallery Free Plans.

http://www.hippocketaeronautics.com/hpa_plans/index.php

Diligence Work by Hlsat.



TESIORS) Enters the Free-Flight

and U-Control Field with 2 Great Flying Model Kits



(FREE-FLIGHT GAS MODEL KIT No. 1) CLASS A OR B

SPECIFICATIONS

| Overall Length |
|--------------------------------|
| Wing Span |
| Projected Wing Area353 sq. in. |

A superbly-engineered kit with 36 pages of illustrated instructions that provide a new approach to legible, easy-to-follow plans.



LICENSED UNDER JIM WALKER U-CONTROL, UNITED STATES PATENT No. 2,292,416

SPECIFICATIONS

| For | Engines | .23 | to | .36 | cubic | inches | displacement |
|-----|-----------|-----|----|-----|-------|--------|--------------|
| Win | ig Span | | | | | | |
| 0. | wall Long | h | | | | | 30" |

Top Maneuverability with Class B Engines

TESTOR CHEMICAL COMPANY

ROCKFORD, ILLINOIS

MATCH-MATES FOR

CRIMER

Engine only-\$12.50

LESS GLOW PLUG

The PERFECT COMBINATION for FAST STARTS and HIGHEST SPEEDS

What a team they make!

The sensational, new "O.K." Hot-Head engine has already set new performance standards for Glow Plug operation. Now, even greater records are in the making with the introduction of "O.K." Hot-Head Miniature Engine Fuel, expressly formulated to bring out the best in the new Hot-Head engine.

"O. K." HOT-HEAD

Developed in the "O. K." laboratories, the new fuel is the result of more than two hundred individual performance tests. The finished formula was found to produce substantially more power than any other fuel intended for Glow Plug operation. So, if you want the best in performance — insist on these great power partners.

Not a conversion model but a completely new design, the "O.K." Hot-Head engine is built to take the unusual stresses peculiar to Glow Plug operation. It features an extra heavy crankshaft .406" in diameter, a drop forged, heat-treated connecting rod and a bronze main bearing, 1%8" long. Don't take a chance of ruining your present conventional ignition type engine by conversion as the average engine of this type will not perform satisfactorily nor is it built strong enough for Glow Plug.

TOP PERFORMANCE

The "O. K." Hot-Head is so simple to operate that all you have to do is connect a $1\frac{1}{2}$ volt battery to the Glow Plug until the engine starts. The battery is then disconnected immediately and the engine will continue to run on pre-ignition firing.

The Glow Plug itself can be purchased at your favorite hobby shop for 85c.

ENGINE SPECIFICATIONS

 DISPLACEMENT ---- .299, B CLASS
 BORE ---- .760

 R. P. M. --- (WITH HOT-HEAD FUEL ONLY)
 TO 11.000

 STROKE ---- .660
 WEIGHT --- 7 OUNCES

HERREICHER ER Tool and Model Works, Inc., Herkimer, N.Y. CANADA: Herkimer "OK" Engine Co., 511 Hermant Bldg., Toronto EXPORT: 120 Wall St., New York 5 (All Cables) Concordia, N.Y.



Serving Aviation 19 Years VOL. XXXVIII No. 4 APRIL 1948 CONTENTS

Cover Design by Joe Kotula

| FREE FLIGHT RUBBER Williwaw | . 9 |
|--|---|
| FREE FLIGHT GAS Skipper | . 16 |
| GLIDER A Class C Towliner | . 25 |
| WYLAM MASTERPLAN Clerget Rotary Engine | . 22 |
| PLANE ON THE COVER Grumman Panther | . 15 |
| SCIENCE Checking Horsepower The Ancient Glow-Plug Design Forum Meet the Rudevator Inertia Starter Tester for Model Sparkplugs | 12 19 24 28 32 33 |
| WORLD WAR I Breguet Biplane | . 23 |
| 3 VIEWS Grumman Panther French Farman Biplane 1914 German Halberstadt CL-2 of 1917 | . 14 . 36 . 38 |
| NEWS Flash The Scrap Box Modeling in Flying Schools Airways. West Coast Tips. Latest on Radio Control Licenses News of Modelers Club News. | 20 20 30 34 36 43 44 |
| HOWARD G. MCENTEE EC JOSEPH M. MANN Managing EC WILLIAM A. WYLAM Associate EC WITTICH HOLLOWAY Art Dire JAY P. CLEVELAND Adv. Man A. M. HOFFMAN Asst. Adv. Man Advertising Representative. WEST COAST: Justin Han 5429 Crenshaw Blvd., Los Angeles 43, Calif. | litor litor litor ager ager |

Published monthly by Air Age, Inc., Mount Morris, Illinois. Editorial and Advertising offices: 551 Fifth Ave., New York 17, Jay P. Cleveland, President and Treasurer 2. M. Hoffman, See'y. Entered as second class matter Dec. 6, 1934 at the post office at Mount Morris, III., under the act of March 3, 1870. Addi-tional entry at New York, N. Y. Price 25c per copy. Subscriptions \$2.50 per year in the United States and possessions; also Canada, Cuba, Mexico, Panama and South America. All other countries \$3.00.

Copyright 1948 by Air Age, Inc.



COMPLETION OF studies by the Presi-dent's Air Policy Commission promises a genuine "shot in the arm" for U.S. avia-tion. The Commission was made up of pri-vate citizens, presumably without special knowledge or interests in aviation, to insure an unbiased study and a citizen's view of the situation. Their findings, generally, are that the U.S. taxpayer must begin paying considerably more for aviation, and most of this money must go into military avia-tion to provide this nation with a vastly improved defense. First of all, the Air Forces and Naval Aviation must buy more airplanes each year, at least 30 million pounds of airframe this year and 40 million next year. (Present rate is about 20 million pounds a year.) This increased production will accomplish two things: (1) it will give the Air Force its 70-group program (only 55 are presently activated, many of them only skeleton forces) and the Navy its pro-gram for existing carrier air groups; and (2) it will provide the aircraft industry with gram for existing carrier air groups; and (2) it will provide the aircraft industry with the essential minimum level of production necessary as a base for a rapid expansion in the event of an emergency.

THE COMMISSION'S strongest recommendation is for legislation permitting the obligation of funds for a minimum of five years (instead of the present annual appro-priation of funds for each fiscal year) which would permit planning of long range proj-ects. It would also facilitate long range basic research projects and the development

of complex weapons now only in the design stage

REMAINING TO BE heard from how-

REMAINING TO BE heard from how-ever is the Congressional Air Policy Board, made up of Congressmen and Senators, who have it within their power to appropriate and legislate their findings into law. Their report is expected to confirm many of the findings of the President's group but to go further in the way of requitements for strengthening the nation's defenses. FOLLOWING UP these recommendations is Pres. Truman's 1949 Budget which asks for: a 35% increase over last year in Air Force funds, 42% increase for Naval Avia-tion, 30% increase for CAA, 10% increase for NACA, and a five-fold increase for air-ways communication equipment by the Army Signal Corps. Of the total armed services budget, 54% is for aviation, the remainder for combined ground and sea forces of the nation. NEW ORDERS have rolled into the in-

NEW ORDERS have rolled into the in-NEW ORDERS have rolled into the in-dustry from the military so quietly as to be almost a secret. Chief of these are addi-tional quantities of existing procurement types including: Boeing B-50, Douglas AD-1 Skyraider, Grumman F8F-1 Bearcat Lock-heed P2V Neptune. Vought F4U-5 Corsair, Martin PBM-5A. Piasecki. Bell and Sikor-sky helicopters. New orders include 225 North American P-86 swept-wing fighters, 10 Douglas DC-6 and 20 Republic F-12 Rain-bow photographic planes. (Continued on page 62)



(Above) New British jet flying wing, the Armstrong-Whitworth AW52, as it made its first public appearance near Rugby, England. (Below) A real flying freight car—this Convair XC-99 military transport and cargo ship can carry 400 fully equipped troops or 100,000 lbs. of cargo



MODEL AIRPLANE NEWS April, 1948



Make Your Ship "TALK"



Here's What Red Wing

Engine Speed Control

Can Do · · ·

FOR THE BEGINNER

Helps you learn to fly sooner by making possible several landings and take-offs per flight instead of the usual one.

Lets you break in your new engine while flying by changing occasionally to slow speed, which cools the engine.

Makes test hops possible — land for adjustment whenever necessary.

Permits landing at will. Safeguards your ship from crackups due to dizziness.

REOUIRES * No Battery * No Relay * No Third String * No Double Points

Price Only Patent Pending Patent will be protected to fuliest extent of law

FOR THE EXPERT

Ø

Permits you to fly two ships at once without catastrophe.

Helps get those extra points at contests by such maneuvers as:

Smooth, tail-high landings

Pick up gliders, mail, etc.

Unassisted take-offs Power-on landings Power stalls

Lets you study your ship at slow-speed flying. Allows stopping engine of racing ship after clocking — eliminates unnecessary wear and risk.

Red Wing Engine Speed Control is a Complete Unit ready to install. No Accessories to Buy

DEALERS: Demand is growing --- Order from your jobber now!

ATLANTIC AIRCRAFT INC.

213 Washington St., West Warwick, Rhode Island



SUPER Syclong NEIMES



THE ORIGINAL ROTARY VALVE **MINIATURE AIRCRAFT ENGINE**

IMPROVED over 14 years of continuous production. Proven an outstanding engine for contest or pleasure flying. Thousands of thrill-packed hours built into each "Cyclone".

ONE PRICE for this superior miniature engine. Your rotary valve "Cyke" is complete when you buy it. No extras to purchase to bring this engine up to maximum power. Buy "Cyclone" and be sure.

Manufactured by

SUPER-CYCLONE, INC. **GRAND CENTRAL AIR TERMINAL** 1117 AIRWAY **GLENDALE 1, CALIF.**

AT YOUR FAVORITE DENIERS SUPER - CYCLONE **BIGGEST NAME IN LITTLE ENGINES**



TRAIN FOR AN SUNNY SOUTHERN CALIFORNIA RONAUTICA GIN 3 3

STER AVIATIO ECHA

(NO FLYING INVOLVED)

NEW STUDENTS MAY ENTER IMMEDIATELY-BOARD AND ROOM NOW AVAILABLE MAXIMUM TRAINING IN MINIMUM TIME

Using modern training equipment, including jets, the courses are intensive, highly concentrated, complete and has over 7,000 successful C. A. A. approved, with all non-essentials eliminated. Leadership training is stressed ... Upon graduation you will be an aviation expert and fully qualified to hold a re-, pilots and 7,500 aviation munerative and responsible position in the aircraft industry,

forge ahead steadily and add more dollars to your pay check... Established in 1929 "Cal-Aero" is one of the oldest, largest and most distinguished aeronautical schools in the world. It is located on its own famous airport ..., Grand Central Air Terminal, in the Los Angeles-Hollywood Metropolitan area, in Glendalethe heart of Southern California's giant

aircraft industry, "Cal-Aero" civilian graduates in addition to more than 26,000 mechanics trained for U.S. Army and Navy Air Forces.

WE HAVE THE EXPERIENCE -THERE IS NO SUBSTITUTE FOR IT Cal-Aero has solved the housing problem! Board, room and transportation is now available right here on Grand Central Air Terminal.

APPROVED FOR VETERANS

TRAIN IN SUNNY SOUTHERN CALIFORNIA



CAL-AERO TECHNICAL INSTITUTE N-4 GRAND CENTRAL AIR TERMINAL, GLENDALE 1, CALIFORNIA Send full information and catalog, free and without obligation, on courses checked below: CAREER COURSES AERONAUTICAL ENGINEERING D MASTER AVIATION MECHANICS HOME STUDY COURSES C HOME STUDY -- AERONAUTICAL DRAFTING HOME STUDY - AIRCRAFT BLUEPRINT READING HOME STUDY-STRESS ANALYSIS AND DESIGN

Birth date

O Non-Veteran

Check one: D Veteran

| BE WISE PROTECT YOU | R FUTURE |
|---|-----------------------|
| EST. (1929 | Send |
| CAL- AGRO TECHNICAL , , INSTITUTE | |
| GRAND CENTRAL AIR TERMINAL | C C Name |
| GLENDALE 1, (Los Angeles County) CALIFORNIA | Addre Ciŋ Sexte |





Read Free Offer on opposite page

ENGINES

| ٠ | Arden .099 | CI, A | \$12.50 |
|---|-----------------------|----------------|---------|
| 1 | Marvin | CI. A | 15.50 |
| ٠ | Bullet | CI. B | 12.75 |
| ٠ | Cannon 300 | CI, B | 19,75 |
| ٠ | DeLong 30 | CI. 8 | 19.50 |
| | Forster 29 | Ci. B | 14.85 |
| 1 | Porsier Jus | CI B | 14.85 |
| | Melcrait | CI B | 18.50 |
| ٠ | Rogers 29 | CI. B | 15.75 |
| ٠ | Torgedo | CI. B | 18,50 |
| | Suger Cyclone Dual | CI. C | 23.00 |
| 1 | Super Cyclone | CI C | 21.00 |
| | Obleson 60 | CI C | 11.95 |
| • | OK Super 60 | CI, C | 18.00 |
| ٠ | Rocket | CI. C | 22.50 |
| | Vivell 35 | CI. C | 18.00 |
| 1 | VIVEIL I WIR | CI 8 | 19.50 |
| - | K & R 74 | CIB | 16.50 |
| ٠ | Mohawk Chief | CI. B | 8,95 |
| ٠ | Pacemaker | CI. C | 24,95 |
| ٠ | OK Super 29 | CI. 8 | 16.50 |
| 1 | OK Twin | CI.C | 49.00 |
| 1 | Super Champion | CI A | 15 60 |
| | Arden .099BB | CI. A | 15.50 |
| ٠ | Arden .199 | :CI. A | 18,50 |
| ٠ | Vivell 49 | CI. Ci. | 20.00 |
| • | Contestor | CI. C | 18,50 |
| 1 | Nell McCox 68 | CI CI | 35 00 |
| | Hornel 60 | CI. CI | 22.75 |
| ٠ | Wensen. | C1, 8 ; | 20.00 |
| ٠ | Hurteman | CI. C | 20.00 |
| | Madeweil | GI, GI | 12.50 |
| 1 | G. H. Q. Juden Kit | CI B | 8 95 |
| | McCov 49 | CI. C | 25.00 |
| ٠ | McCoy 29 | CI. 8 | 19.50 |
| ٠ | Air-O Mighty Midget_ | CI. CI. | 25.50 |
| 1 | U.K. Bantam | CI R | 13.95 |
| - | Pierce 4.1" | CI. B | 9.95 |
| ٠ | Hassad Sky Devil | CI, C | 37.50 |
| ٠ | OK 60 Race | CI. C | 23.00 |
| • | Forster 99 | CI. C | 24.75 |
| 1 | Genie 29 | CL B. | 9 95 |
| • | New Thor | CI. B | 9.95 |
| • | New Thor Kit | Ci. B | 6.95 |
| ٠ | Ohlsson 19 | CI. A | 9.95 |
| • | Unisson 23 | GI, B | 3.33 |
| | 10 L 3 L | CI B | 516 60 |
| 1 | Aero Diesei | CLA | 21 50 |
| | Orone Diesel | CI. B | 21.50 |
| ٠ | Mite Diesel | CI. A | 18.95 |
| ٠ | CIE Diesel | CI. A | 16.50 |
| • | Deezil | CI. A | 12.35 |
| 1 | LICEZII BAU BEQ. | CI B | 14.95 |
| | O K Hot-Head | CI, B | 12.50 |
| | AIR ENG | INES | |
| • | CO | | \$ 4.95 |
| | GLO PLUG | ENGINES | |
| ٠ | Mighty Midget GP | C1. C | \$14.75 |
| ٠ | Sportsman Jr | C1. C | 14.95 |
| ٠ | Sportsman Sr. | ULU UL | 10.95 |
| • | Dyna-Jei | a a c a' Ba Ma | \$24.50 |
| ÷ | Oyna jet Redhead | | 35.00 |



GENERATION OF FAIR DEALING GUARANTEES YOUR SATISFACTION

Dept. MC-48 Suite 230-742 Market St., San Francisco 2, California

New York 11, New York

Dept. MC-48 55 E. Washington St. Chicago 2, Illinois

We have two for onsts you 10c (st of items, Special trouble shoot og,

Dept. MC-48

MODEL AIRPLANS NEWS . April, 1948

h etc

156 West 22nd St.

THERE'S A MAND SHORT TO THIS NEW ARDEN FIRST

neur

THE ARDEN GLOW PLUG - an engineering achievement that has clicked with modelers throughout the nation—is now available with both long and short threaded sections.

> a GLOW PLUG ADAPTER which permits their use with Class C engines having the larger conventional 3/8" diameter plug opening.

No increase in **ARDEN ENGINE PRICES**

| Catalog N | o. | |
|-----------|--|---------|
| 1-P-099 | .099 engine with plain bearing crankshaft | \$12.50 |
| 1-B-099 | .099 engine with ball bearing crankshaft | \$15.50 |
| 1-B-199 | .199 engine with ball bearing crankshaft | \$18.50 |

PDEN GLOW PLUG PRICES

| For Arden and other engines with same diameter plug o | penna |
|--|----------------------|
| and same thickness of field | 857 ett. |
| No. E-8001 S (short), ³⁴ X S2 that 5/32" Length of threaded section 5/32" | thicker |
| For engines with same diameter plog operation | |
| head than Arden- | 0.5 - 40 |
| No. 8020 L (long), ¹ / ₄ × 32 Ti in Length of threaded section 7/32" | P.I. plug |
| Glow Plug Adapter, for Class C englines that Plugs. opening, permitting use of long Arden Glow Plugs. No. 8015, fabricated of aluminum with copper-asbesto | os gasket 25c ea. |
| | |

Ask your supply dealer or write us for information





BY BILL WINTER

THIS BUSINESS of the timer turning his back on free flight hops of more than 10 min. under the new rules reminds us of the days when you could chase and time the model just as long as you could keep it in sight. Remember? At one of those Detroit Nationals, '36 we think it was, Benny "Sure-Shot" Shereshaw--who after-wards designed the Bantam-got off a corker of a flight. After a hot, dusty, safari, Benny, timer, and crew returned to the field with some quite remarkable flight

wards designed the Bantam—got off a corker of a flight. After a hot, dusty, safari, Benny, timer, and crew returned to the field with some quite remarkable flight time. Unfortunately the ship had been sit-ing by the judge's stand all the time; it had landed at the end of the field while the boys chased another model or a bird. Bill Berry of Philadelphia once watched those Brooklyn boys—and do we remember them —who could talk a man into timing the spots before his eyes, work out on a timer. So many of them still saw this model that the timer had no difficulty in seeing it too. Just then some kid walked up with the ship and said, "Hey. Joe, here's your model." Maybe we should start a "Can You Top This?" contest. We'll try to talk the editor into wasting a free subscription on the best tall story teller of the month. In this screw-ball hobby of ours the best tall stories are the true ones. For instance, do you remem-ber the time the papers carried the tale of the lost gassie that hit the mast of a ship 4 miles at sea? Mysterious, eh! That fellow had a good eye—or radar. Walt Schroder once flew some dawn patrol practice before a Sunday contest and his ship glided beau-tifully through an open bedroom window. Just as Walt huffed and puffed onto the scene. an irate gent reached out the window and crowned Walt with the pieces. An-other day, at Creedmore, we saw two free flighters get so excited when their motor finally started that one of them hand-launched the big job, boosters and all. And it flew! Sorta . . . Say this could go on and on. So, if you want to get into the act, and win that grand prize of 12 issues of M. A. N. free for nothing, put your pet story on paper. glue it to the top of an expensive kit (contents intact) or any good motor and mail it to the man whose name you see at the top of this column. We're motor and mail it to the man whose name you see at the top of this column. We're serious—about the story, that is!

Speaking of the hard-to-believe, the only fellow who resented our crack (two issues ago) about the Boston builder who put down his indoor models long enough to set a mark of 144 mph was Phil Pauley of South Plainfield, somewhere in Jersey. Phil likes the column but says that the "wild likes the column but says that the "wild rumor" about the Bostonian wasn't fair. "Please give Kramer credit for the official record he made with his Dooling—with ignition!"

ignition!" Digging through our file on records we find that a mark of 143.82 mph in Class VI Open had been made by William Viets, Springfield, Mass. The ship was of original design (name: Snowflake), Dooling 61. The fuselage was made of sugar pine, the wing built up with balso sheet covering. Weight was 36 oz. Used Champion VR-2 sparkplug. Modelectric lightweight coil. four Burgess pencells, Aero Spark "racer" condenser. Fuel-gather 'round boys-was 2.5: 1 methanol-castor oil mixture, with no (Turn to page 59) (Turn to page 59)



THE WILLIWAW—so christened because it was built on Attu —is an experimental tailless model and is one of a series of similar designs built by the author during the past several

years. The model was designed to permit a maximum variety of setups to be used. Nose and tail plugs are interchangeable so that the ship may be flown as a tractor or pusher (or combination of both), while movable elevators permit easy trimming for changed C.G. position, incidence setting, etc. Swept forward wing designs have a number of advantages over the better known swept back type, especially for modelwork, most important of them being: control surfaces have greater moment arms than wings with an equal degree of sweepback; greater C.G. range (adjustments less critical); and the problem of tip stall is eliminated. Another big advantage is the fewer number of structural parts which permits the units used to be built much more ruggedly than conventional models.

The Williwaw is a stable model with an exceptionally flat glide, although the climb admittedly is nowhere near as spectacular as that of the purely contest type rubber job. The design is unusual, the construction strong and simple, and flight characteristics good.

FUSELAGE—The plans are half size and may easily be enlarged. The fuselage is constructed by means of the keel method. Simply pin the upper and lower keels down and build half the fuselage right on the plan. Note that the formers are not notched; instead the stringers are cemented to their perimeters. This permits a much smoother covering job, at the same time speeding construction. Also note that the grain is alternated at each station to give maximum strength. The wing mount is



WILLIWAW

by BRUCE WENNERSTROM

1/16 x 1/4 balsa.

Cement the wing mount dowel securely in place. Before covering, sand the entire frame lightly to remove any flaws or roughness which might mar the smoothness of the covering job. Silkspan is the covering material. Use the heavy gas model grade for the fuselage in order to resist tears and punctures. Double cover the bottom. Cover as large an area as possible without getting wrinkles. Don't worry about pulling the tissue tight, just make sure it's wrinkle free; dope will tighten it. Five coats of clear dope are brushed on.

WING —The wing is built upside down. All ribs are 1/16'' sheet balsa. If hardwood is used, cut lightening holes. Ribs and other sheet members should be cut out before starting construction. Pin the spar down and cement the ribs to it. When the cement is dry, glue the leading and trailing edges in place, the balsa tips last.

Cover the section from the leading edge back to the spar, and the center section with 1/32 sheet balsa. All ribs are cap stripped with 1/32 x 1/4 balsa. Sheeting the leading edge is best done by cementing the edge of the balsa sheet to the leading edge of the wing first, then when the cement has dried each rib and the spar is coated with cement and the sheet curved back and pinned in place until the structure has dried. Study the details of the elevator construction carefully. Note

Study the details of the elevator construction carefully. Note that they are hinged in the same manner as the control surfaces on real planes, which considerably cuts drag and increases their effectiveness besides improving appearance.

effectiveness besides improving appearance. Sand the entire structure lightly preparatory to covering it. Wings are best covered by applying the Silkspan wet and (Continued on page 41)







MODEL AIRPLANE NEWS . April, 1948



.







Ready to try a motor-lock pin in place

Calibration bar fastened to rear section

Motor running and ready for a test

Checking Horsepower

Build this torque stand and KNOW what power your engine produces by FRED R. YOUNGREN

DRESENT day contest rules favor engines which develop the highest horsepower per cubic inch. A hot engine properly handled will naturally give a higher rate of climb and thus a better chance to Various ideas have already been win. used successfully to increase the power to displacement ratio.

Here's another way which has resulted in as much as a 50% increase in available horsepower. It is based on the fact that many model engines are not run at the speed at which they develop maximum horsepower. A Super-Cyclone which had been operated at 7200 rpm with an output of .4 hp before making the tests is now operated at 12,000 rpm with a power output of .6 hp (see Fig. 1). Similar results were had with other engines; some other to slower speeds. Even engines of the same model had different power ver-sus speed variations. This shows that no general conclusion may be reached, for each engine is unique. Only two devices are needed to run similar tests on your engines: a tachometer and a torque stand. The tachometer can be purchased for around \$2, and construction and operation of a torque stand is described below. A four view drawing of the stand is

shown in Fig. 2. The main frame is assembled from 3/4 in. lumber (we used plywood) and should be built rigidly to

resist vibration. If necessary, metal gussets can be nailed across the corners to increase rigidity. The torque scale is mounted on a piece of sheet metal formed as indicated in the drawing. Dope was found to be satisfactory for attaching the paper scale to the metal. The ignition coil is strapped to the frame with a rubberband and held between two small nails.

The next assembly to make is the swinging arm which consists of a wooden bearer with balance arm, pointer, and two tee sections attached to it. The two tee sections were obtained from an aircraft salvage yard; however a section of angle stock or even bent up 3/16 in. plate would serve just as well. The hardware is bolted to the swinging arm bearer and this whole unit is then screwed to the main frame. Be sure to make the attachment holes in the tee sections a little oversize, and allow enough clearance from the frame so that the arm can swing freely. Washers will further reduce the friction. A hole should be drilled through the top of the main frame, through the swinging arm bearer, and into the lock block to provide for insertion of the starting lock pin. This pin is used to block the swinging arm when starting an engine for a test run. The engines are bolted to wooden mounts which in turn are held to the swinging arm bearer by two bolts and wing nuts.

Now that the stand is built, it must be calibrated so the scale readings will be true readings. This is done by using the calibration bar (see Fig. 3). First, clamp the stand to a bench and check to see that the base rests level. Then with the starting lockpin removed, set the pointer to read zero. Mount your engine on the stand ready to run just as it would be during a test; then fasten the calibration bar to the rear tee section as shown in Fig. 3 and check to see that bar and arm swing freely. Rotate the swinging arm until the pointer reads 5 and hold it in this position. Place a string-suspended 1/2 lb. weight on the bar so that the horizontal distance from the weight string to the axis of the swinging arm is exactly 12 in. with the pointer set at the .5 reading. Add lead shot to the balance can until the pointer holds this reading when released. By tapping the swinging arm it is pos-sible to get more accurate settings. The sible to get more accurate settings. can should now be sealed to prevent loss of the shot; wide scotch tape works nicely but be sure to remove a few shot to allow for the weight of the tape. The calibration bar may now be removed and the stand is ready to operate.

To find output or brake hp of an engine, two things need to be known: the torque and the engine speed. Therefore you will need some type of tachometer. We found that the vibrating wire Vibra-Tac was well suited to our needs; a Strobotac would be perfect, but even a revolution counter and watch will do. The best systems of course are those which absorb no power from the engine such as the Strobo-tac or Vibratac. To make a run, block the swinging arm with the lock pin and start the engine.

When engine is warmed up, advance the spark and adjust needle valve until engine is running steadily at top speed. Now remove the lock pin and take a reading of both torque and rpm at as close to the same time as possible. By referring to the graph of hp plotted in terms of torque and rpm you can determine the hp developed on this run. After making several runs with different sizes of props (thus vary-(Turn to page 64)





Fig. 2 Details of torque stand. It should be built to size shown for use with full size scale below







1



GRUMMAN PANTHER

PLANE ON THE COVER STORY





MODEL AIRPLANE NEWS . April, 1948

by ROBERT McLARREN

THE Panther---stubby, powerful jet fighter---is proof that Grumman is still "king of the carriers" in the single-seat fighter department. Not since 1932, when Grumman turned out its first fighter, has the Navy's fighting branch been without a Grumman fighter model in production and aboard its aircraft carriers. And the new Panther will carry that unbroken tradition forward for another 3-5 years. How has Grumman maintained this "corner" on the mar-

How has Grumman maintained this "corner" on the market? By (1) designing superior carrier fighter planes; (2)proving the ability to produce them rapidly and in the desired quantities; and (3) doing the job more economically than the competition.

Jet propulsion posed a challenge to Grumman engineers, after a decade of leadership in propeller-driven fighter design. With an unmatched war production record 1971 F4F Wildcat fighters; 12,272 F6F Hellcat fighters; 556 F7F Tigercat fighters; and more than 1200 F8F Bearcat fighters (the latter currently in production) the firm achieved honors and awards and a string of titles ("world's largest output in a single month", "largest production of a single type in a single plant", etc.) all attesting to the productivity of the group. The only small question mark was: "Will Grumman clear the turbojet hurdle and continue its leadership?"

Months went by and still no word concerning a Grumman design project for a jet-propelled fighter. With F8F Bearcat fighters continuing to pour from the plant, the word grew that the firm was "sticking to" the propeller-driven fighter until it outgrew its usefulness (which will not be for several more years with Navy schedules calling for F8F production through 1949). Finally, early last December the mysterious Grumman jet-fighter was unveiled and engineers knew the reason for the long secret.

The firm was not content merely to produce another jet fighter (McDonnell, Vought and North American all had already gone out into the lead in the carrier jet fighter class). It wanted a superior jet fighter, not just faster or with longer range, but one that solved the Navy's basic problems: (1) short takeoff—and fast waveoff; (2) mass productibility; and (3) economy of production.

The company assembled its top design team for the project. At the head of the list was of course Leroy Grumman himself, an able designer, a former Navy pilot and engineer and an astute guiding hand in the integration of the project into the overall problem of the company. Next in line was William T. Schwendler, vice-president of engineering, in administrative charge. For the initial design job there was Dick Hutton, assistant chief design engineer and Robert Hall, assistant chief experimental engineer. Hall is most widely known for his fabulous "Hall Racer" of the early 'thirties with the "Buck Rogers" butterfly wing, neatly panted landing gear and sharp, sweeping tail. In immediate charge of the detail engineering of the project was Gordon Israel, project engineer. Israel shared National Air Race honors for the success of Ben O. Howard, whose "Pete", "Mike", "Ike" and "Mr. Mulligan" were products of Gordy Israel's technical skill. On the Navy side was Marine Corps Major Ross Mickey, F9F project engineer in the Bureau of Aeronautics, and Lt. Comdr. W. J. Patterson, who handled the engine project. This ton-rung technical team first attacked the hasic prob-

This top-rung technical team first attacked the basic problem of the jet fighter for carrier use; slow acceleration. The power of a turbojet engine is a function of the airspeed of the plane in which it is mounted. For example, at low forward speed the jet fighter develops low power because it is a "momentum" machine rather than a "power" machine as is (Turn to page 57)



MODEL AIRPLANE NEWS April, 1948





HERE'S a model that literally "flies off the workbench." About 12 hours of work is all that is needed to get Skipper airborne. Designed for any .099 engine, this 30" job will really go places due to its slick, simple design. Conforming with A.M.A. regulations, Skipper is a real threat in any contest if given half a chance. Tested with every conceivable type of adjustment, the plans show the happy medium arrived at after numerous flights with different sized wings and tail areas. The dieselized Arden engine used in the original model has behaved perfectly, considering the author's brief experience with ignition-less engines. With the dieselized Arden, or with a Mite, weight will have to be added to bring the model up to weight rule for contest work. More about that later. Interested in building Skipper? Well, grab a razor blade and ...

Cut out the necessary ribs from medium 1/16'' balsa sheet. This should be no trouble at all, considering the full sized outlines given on the plans. All four panels can be built simultaneously, then joined after the cement is dry through the addition of dihedral braces W-9 and W-10. While waiting for the cement to dry, get a piece of $1/4 \times 3/4$ hard balsa. Taper it to $3/16\times3/8$ at one end, round the corners off with sandpaper, and there you have the completed tail boom. The pod is simplicity itself, so we won't gab about it too much. If a battery, coil and condenser contraption is desired, you'll have to modify it to your needs, maybe enlarging it to hold all these old-fashioned items. The method of mounting the landing gear is optional. As shown on the plans, the struts are set at a rakish angle, but if you are in a hurry, simply cement the gear to the rear of the fire-wall or nose bulkhead.

Now you can tackle the pylon, Five outlines are needed—make it any way you want, but laminate the different layers crossgrained, obtaining a pylon 5/8" thick. (Never thought of *carving* it from solid 5/8" stock!). Oh well, once it has been sanded, cement it in place on the pod. The simple sheet balsa tail surfaces will take no time at all to make, but don't forget to make some provision for a trim tab on the rudder. Several coats of clear dope on the rudder, stabilizer, pod and boom, and you're ready to slap things together. Just be sure the pylon, landing gear and tail surfaces line up while cementing said parts together. A wing platform of 1/8" sheet goes on top of the pylon, set at the same dihedral angle as the wing center (use dihedral brace W-10 for this).

The bristol board fillets add quite a bit of strength and are aerodynamically clean. (I've been plugging these fillets for years 'n years but have never seen anyone else use 'em—honest fellas, they're simple!) Since these diesel engines spray oil all over the land-(Turn to page 66)



MODEL AIRPLANE NEWS . April, 1948

THE ANCIENT GLOW-PLUG

by NATHAN A. GORDON

The "glo" plug, as it is usually called nowadays, mystifies many users study this story on how and why it works



ART HASSELBACH'S CONVERTED SPARK PLUG, FEATURES REPLACE ABLE ELEMENT

FIG. I



F1G.2

DEL AIRPLANE NEWS . April, 1948

THE HISTORY of the glo-plug and its variations is as old as the internal combustion engine. Around 1680, in Holland, the first internal combustion engine had its birth. It consisted of a cylinder with a movable top (piston); a charge of gun powder was placed inside the cylinder and ignited, or fired, by a flame held to a hole in the cylinder. The result, naturally, was an explosion which forced the top to move. Thus, simply, was the first recorded attempt at internal combustion engines made.

Further development involved piston, cylinder and a more practical combustible. The combustible was ignited by the flame of an outside burner which made connection through a hole or port; the opening made accessible at the proper moment by the piston's travel. Other methods of applying outside heat to aid ignition were found. Heat was applied via a hot bulb and hot plate which in turn transferred the heat inside the cylinder where it was used to ignite the fuel charge.

The first attempt at using compression ignition alone is generally credited to Rudolph Diesel. He tried such an engine with coal dust as a fuel. As an ignition aid for starting, an explosive powder was ignited and the results sent Mr. Diesel to the hospital seriously injured. He recovered, and in 1897 demonstrated a practical oil burning engine which today is called "Diesel" in his honor.

Most unique of the methods tried to facilitate ignition was the one used by a Minneapolis blacksmith. 'Way back in 1870 he arranged two hardwood blocks in such a manner that the friction created by rubbing them together developed sufficient heat to cause ignition.

From these beginnings the glo-plug evolved. The glo-plug is a metal holder for a fine coiled wire filament; this filament heats up and liberates the heat right where needed—inside the cylinder. To fully appreciate the significance of such a development, it may be of interest to know that glo-plugs are still in use in many large modern commercial engines. Their purpose is to aid ignition.

By use of the glo-plug, the engine becomes a form of compression ignition engine, but one distinctive feature of the spark ignition engine remains undisturbed. This is a pre-determined or fixed point of ignition. By its very design and operation the glo-plug is just that: a fixed ignition point.

The importance of this is understood when basic engineering facts pertaining to the internal combustion engine are known. While this article is limited, it is desirable to air some of these facts. In a diesel engine, the fuel and air do not mix and are not in contact with one another prior to meeting in the combustion chamber. Ignition is effected by the very high temperature developed with high compression ratios. In a spark ignition engine, however, fuel and air are mixed by means of a carburetor. The fuel is (theoretically) atomized and dispersed throughout the firing chamber. Each droplet of fuel is surrounded by a supply of air sufficient to support com-bustion when ignition is effected. The fixed ignition point now becomes important because, with this thoroughly mixed charge, combustion of the whole mass is rapid and takes place within the limited time allowed for complete combustion. Remember that the time in which ignition and combustion take place is a matter of finely split seconds. A delay in combustion will result in poor operation and often cause "knock" to be severe and even destructive to the engine.

Now, by adding the necessary factors which together will give the best possible combustion, it is seen that the glo-plug, as the fixed ignition point, is the focal spot in the entire cycle. The pre-mixed fuel and air charge is delivered to the firing chamber and the glo-plug does its work. Discarding of the usual ignition system—with its contacts, coil, condenser, wires and the necessary connections with their many possible sources of failure and increased weight—gives an apparent large advantage to the glo-plug user. The advent (Turn to page 53)



J. Shumway of Sparton, right, shows flying saucer to students Flying schools not only tolerate modeling—they encourage it!



An ambitious experiment in radio control is underway at Parks

MODELING IN FLYING **SCHOOLS**



Embry-Riddle students Tyler, Palczewski and Stevens with control line models





L. Schroeder shows plane ready for hop to other Parks students Embry-Riddle instructor Betz, left, and group of fellow model builders O'Brien holds plane as Stephenson cranks starter at Northrop Group of student mechanics at Cal-Aero show planes to Stunt Champ Davey Slagle







Back stagger is evident in this view of Breguet 14A.2 with Renault engine

WORLD WAR I

by ROBERT C. HARE



A 14A.2 with Fiat engine; note unbalanced ailerons, long radiator, no exhaust stack



This model of 14A.2 had stack, balanced ailerons, short radiator, Renault 12Fcx motor

TOWARD the end of World War I, designers of all the warring nations had pretty well standardized on aircraft types in each category. Actually, by the end of 1917, the belligcrent aircraft manufacturers found they could design aircraft objectively, that is, with a definite purpose in mind—with a high degree of success. Aircraft design was immeasurably more predictable than it had been two years earlier, and the old method of designing by guess and by gosh had just about seen its last day. Standardization, of course, meant a great deal to the various air services. They were

Standardization, of course, meant a great deal to the various air services. They were able to order in quantities, not only of aircraft but of engines, fuel and oil, instruments, accessories and raw and finished materials. Mechanics were better trained and more efficient with fewer types to work on. And the root of it all was the manufacturer's ability to build time-saving tools to speed production, with accuracy which permitted modifications of type and interchangeability of parts in the field without need for a factory rebuilding operation.

One of the best examples of a standardized aircraft type was the Breguet 14 series which was put out in two production versions: the 14A.2 (army cooperation) and 14B.2 (day bomber). Two field modifications were eventually used in limited quantities: the 14C.2 (two place pursuit) and the 14E.2 (trainer).

Breguet's versatile model 14 entered the picture late in 1916 as the 14B.2 and was a success from the start. It was capable of carrying 300 kilos. of bombs slung from carriers attached to each lower wing. While the 14B.2 was a good bomber, the French tended to rely on other types such as the Farman, Voisin and Caudron for this duty. The 14B.2 never was entirely retired from the scene as a bomber, but it faded out of the picture as the primary French bomber. When American squadrons arrived overseas they were given the 14B.2 with which to do their bombing. The aircraft performed notably with several squadrons as a day bomber, filling in until the famed Liberty DH-4, in production in America, reached the Front.

The French by no means did away with the basic model 14, however. Rather, they maintained a few 14B.2 units but diverted the bulk of production to a modified model, the 14A.2. Duties of this type were centered on the observation and photographing of various strategic areas, artillery spotting, and liaison. The types differed only in wing area, due principally to the use of balanced and non-balanced ailerons, the type of engine, and in the use of an automatic wing flap. The 14B.2, in order to get off the ground more quickly fully loaded, was fitted with full span automatic flaps; the 14A.2 had a conventional stiff wing. Specific differences will be discussed later in this article.

Louis Breguet

In order to fully appreciate the Breguet 14 series it would be well to become somewhat acquainted with the man behind the design, Louis Breguet. Like few of the true pioneers of aviation, he is still alive at this writing and takes an active part in the engineering affairs of his French company.

The name of Breguet is synonymous with the early days of French aviation. Prior to 1910 he carried out a number of experiments at Douai. It was Breguet who developed the first successful (though not practical) helicopter, mention of which can be found in the French aviation magazine L'Aerophile for September 1907. This helicopter lifted a total weight of 1100 lbs.

Breguet also experimented with more conventional aircraft. In September 1910 he flew his biplane with 5 persons aboard, a 150 lb. payload. Like Fokker, Breguet was a great believer in metal construction and even his (Continued on page 52)



by CHARLES H. GRANT









JUST 14 years and 6 months have passed since the birth of that infernal infant, "Spiral Instability." He has been no ordinary youngster. From the very moment he ar-peared in the original K. G. (Kovel-Grant) gas model in 1933 he took particular delight in throwing gas models into all sorts of disastrous maneuvers. This young gremlin through the years has caused more arguments and headaches than anything else in gas model history, and all sorts of devices and tricks have been applied to neutralize his ill effects.

The first and most successful means of overcoming spiral instability was the theory concerning location of the center of lateral area. This was developed and offered in practical form by the author in 1933. Since that time many modelers, including the experts, have been trying to disprove it. They have resorted to all sorts of mental contortions and mathematical intricacies to show why the center of lateral area has little or nothing to do with spiral stability, but have

One leading modeler even attributes spiral instability to the use of lifting stabilizers. Evidently he has failed to notice that thousands of spirally stable models use lifting stabilizers, and in all cases they have little effect upon the model's good behavior. However, we will leave the discussion of cambered lifting stabilizers to a later article.

This discussion of spiral instability concerns the center of lateral area and is prompted by a letter from Harry C. Brown—the gremlin of spiral instability apparently has paid him a visit. He tells us that he has built and flown a plane called *The Pipe*, a side view of which is shown in Fig.

plane called *The Pipe*, a side view of which is shown in Fig. 1, and he comments as follows: "The first test flight was in October and it spiralled to the left, breaking only the prop. The second flight was to the right and again a crash, this time with no damage. After putting a 1/8" shim under the trailing edge of the stabilizer I let it go for a third time. This time *The Pipe* went straight out shoulder high for about 10 ft., then into a tight left spiral upward." Mr. Brown goes on to say that on every other flight the

Mr. Brown goes on to say that on every other flight the ship showed spiral tendencies, either to spiral dive or spiral climb, and he wishes to know the reason for this type of performance.

An adherent of the CLA theory need only look once at Mr. Brown's design to know definitely why it has spiral tendencies. In fact, it would be impossible for the ship to act in any other manner. First of all, it is not because to act in any other manner. First of all, it is not because of the cambered stabilizer used but because the CLA is far above the center of gravity (CG) as indicated in Fig. 1. In order to possibly clear up the result of a lot of mis-information concerning CLA effect, let us first consider that this plane is flying in a straight level path. Due to the torque effect of the propeller or to some other ex-ternal force, the plane banks slightly to the left, arrow B, Fig 2 and the tail swings slightly to the right B. The Fig. 2, and the tail swings slightly to the right, R. The plane does not immediately turn to the left with the bank plane does not immediately turn to the left with the bank because its mass or weight tends to keep on moving straight forward, arrow Ff. Consequently it crabs slightly side-ways to the right through the air, as shown in Fig. 2. However, as the plane is nosed to the left the propeller thrust Tl, lift forces and other forces tend finally to direct it to the left from the original straight path of flight, FY, while centrifugal pull Cc, is developed outward by the weight of the airplane. This pulling force acts at the CG as shown by arrow Cc. Under these conditions the airplane does not fly along a course exactly parallel to the longitudinal axis of the fuselage but crabs slightly to the right, along path Ff, under (Turn to page 67)

(Turn to page 67)



A CLASS C TOWLINER

The hollowed-out fuselage is easy to construct and affords strength and realism for this attractive design



by H. A. THOMAS

THE smallest established class for towline gliders is "C" in which models are grouped having wing area more than 100 but not exceeding 150 sq. in. Our model is a small C job, having a wing area only a bit more than 100 sq. in. To meet AMA requirements it must have at least 1.62 sq. in. of fuselage crossection and must weigh a shade over 4 oz. If built according to the accompanying plans it easily meets these requirements.

The numerous carving sets now available to model builders which include small curved gouges have led us to employ a perfectly streamlined, hollowed fuselage. It is not a difficult type to build, and for this style of model is superior to any type of built-up construction. To meet the weight rule, the fuselage is not hollowed for maximum lightness and the nose section is left nearly solid for strength and to help balance the model properly.

The wing is of fairly high aspect ratio with false ribs added to help retain good crossection. Sweepback is employed since it is held to contribute to directional stability (visualize a model with sweepback wings being displaced in a yaw, the opposite wing presenting more drag to the airstream and causing a righting effect)—and there is slight toe-in in both fins which aids further in directional stability.

Begin construction with the fuselage, selecting a uniform balsa block and sawing it into two lengthwise halves, vertically. Cement these together again lightly, saw the side profile and then the top outline. Carve away excess wood with a sharp penknife, taking care to retain full width at the widest point. Finish the external shaping including sanding, then separate the halves and hollow the inside as indicated with a sharp, curved gouge. Permanently cement the halves together, carve a recess for the 1/8" plywood skid and cement it securely in place. Dope and sand the fuselage, adding wood filler if you care to smooth it to this extent. Bend the wire towline hooks and cement them to the fuselage belly. Select uniform 1/16" sheet for the wing and sta-

Select uniform 1/16" sheet for the wing and stabilizer ribs. We suggest you make metal templates of these and trim around them with a sharp pointed model knife. The wing halves are next completely assembled, the trailing edges being tapered and the leading edges rounded a bit. Cut the dihedral joiner and taper it to fit the angle of sweepback. Notch the center ribs for it and cement it firmly in place, checking the dihedral at the same time. Trim out the two fins of 1/16" sheet and sand them to streamline section.

Covering material for wing and stabilizer should be light Silkspan or jap tissue. Using thick dope as an adhesive (add cement to thicken it), work from the center outward in covering the frames, doping down about two rib stations at a time. Pull out wrinkles as you go and trim the edges flush. It is best to cut separate, smaller pieces of the covering material for the wingtip sections to avoid wrinkles. "Water dope" the wing and stabilizer lightly after covering, using a cotton swab or atomizer, and permit them to dry thoroughly before applying two coats of thin dope. Cement the fins to the outer stabilizer ribs.

(Turn to page 63)







General view of Rudevator installation on test ship



Actuating mechanism is very compact and light



The author (left) and Dick Schumacher ready to fly Control receiver takes little space in the large cabin



Meet the RUDEVATOR

by H. H. Owbridge

AN article entitled "Simplified Radio Control" by William A. Rhodes in the July 1947 issue of M.A.N. ended my three and a half years of effort to "discover" a really simple control that would advance the art to the stage of mass acceptance. In this article the author stated: "I do not contend that this unit is in its highest state of development, but it has lots of possibilities and I hope that others will cond-ct further research to improve upon it, keeping in mind however not to let it grow into a nightmare of complication as have some units I've seen."

Well, we both got our wish. Bill Rhodes showed me the really simple control and at the same time he found someone to "conduct further research to improve upon it." Together we believe we can offer our fellow enthusiasts the most control for the least weight on record.

As readers of that article will recall, the control as Rhodes conceived it is really a rotary tab that combines the duties of rudder and elevator. Since it is probably here to stay, let's accept it into the family of model airplane tricks and give it the nickname "Rudevator". Now, with flying time as a measure, the rudevator is very young yet. Bill Rhodes has flown it a little and so have I. But so far as I know, that is all. Like the idea of control line models and the now famous Good Brothers escapement—both of which started out with limited useage—the rudevator will grow in ability with flying time. We feel that its present ability compared to its utter simplicity gives it a good start.

ing time the relate the present ability compared to its utter simplicity gives it a good start. To begin with, the rudevator is completely coordinated with the operator. There is no need for counting or remembering past control positions. Then, too, neutral is automatic when the signal is off. If you get excited, a flick of the switch puts you back in the free flight class where you can wait until your heart stops pounding. Besides rudder and elevator, the rudevator includes an ignition switch. Go off and fly yourself silly until you think you're going to be late for dinner. Then cut the ignition, bring the ship in, pack up and go home.

The rudevator will fit any free flight model that will lift a receiver. And receiver installations complete with batteries are getting down below 8 oz. these days. The rudevator answers to a normal carrier wave and a simple pulse at that—no audio tone or timed signal length is necessary. The rudevator is simple to install. You know that old free flight job that never could get high enough on a 10 second motor run to win anything? Well, don't burn it. Give it a new lease on life with radio control. You don't have to rework the tail to hinged surfaces or install control rods either, for the rudevator does all that. As for that old engine that's low on compression, quit trying to sell it for more than it's worth; it's ideal for radio control. Unless however you intend to use your radio controlled model to go off hunting thermals in a free flight contest.

First let's review the rotary tab itself. It too has improved a little. As seen in Fig. 1, it is made of 0.020 celluloid sheet and the control area is the large area between the two protruding tips. This area can be adjusted at any angle on the shaft from 10 to 50 degrees depending on how fast you wish the ship to respond. Even two airplanes the same size may need a slightly different angle or area because one may be more stable than the other. A general rule is: 1 sq. in. for each foot of wingspan, and set at 30° or 40° to the shaft as a start. It's not too important however since the control can be turned on and off quicker than a water faucet. Just pick a calm day and have an engine timer aboard for that first flight. The small tabs at the tips of the rudevator are set at an angle over a teakettle so they will propel the main surface around in the slipstream. Ours turns about 100 rpm which is plenty. Since the shaft is clamped to the center of the rotary tab, no balancing is required. Check it out in a car before you fly. If it starts rotating at 10 mph, it's all right. Our tab has a control area $1-1/2^{"} \times 4^{"}$ with the cor-

MODEL AIRPLANE NEWS . April, 1948



ners rounded off. The propelling tabs are 3/4'' long by 3/8'' wide. For a 7 ft. span model this area is a little on the small side, but then we are beginners, too.

Let us assume we all understand that when the rudevator is turning free it is in neutral. And for those who think the model will show the effects of any aerodynamic vibration, let them try it sometime. The mass of the model and the stabilizing effect of the fixed tail surfaces just won't let the ship respond while the rudevator is rotating. Now, to produce rudder or elevator control, all that is necessary is to stop this rotary tab in any one of four positions. Let's forget about the other four intermediate positions since this is a step control rather than a proportional control, and the amount of turn or dive you get depends upon how long you hold the control on. Let's not worry about climbing turns either, since with only two engine speeds (go and no go) the model would only stall anyway and we can do that with the elevator. Diving turns yes; any model with a single control will dive if the rudder is held long enough, especially if the turn is with the engine.

Fig. 2 shows the brain behind the control. To assure coordination with the ground operator, the rudevator uses a form of escapement. It is really a stop that is positioned by an escapement. The fact that the stop has two directions of motion (rotary and transilatory) does the trick. Four spokes (#5) protrude from the short escapement shaft. The shaft is connected to the armature of the double coil electromagnet by means of a bearing (#10) which will allow rotation of the shaft. Torque to rotate the escapement shaft is provided by the loop of $1/32^{"}$ square rubberband (#15). Tension in the rubber motor is isolated from the escapement shaft by a small music wire crank (#17). Now, motion of the armature (when energized by the receiver sensitive relay) will step the four spoke wheel around one-quarter turn at a time through the labyrinth escapement stops (#24, 25). However, one spoke has a stop protruding from it (#4).

(Turn to page 64)

MODEL AIRPLANE NEWS . April, 1948





No. 1 Frank Hernandez' completely equipped model Convair 240



No. 3 Ancient reglistic Bleriot Monoplane built by Joe F. Park



No. 2 Brian Fairey, Brian Eccles & Martin Ollis at Warsaw Aerodrome



John E. Burkam perfected this gas powered model helicopter



News of Model Airplane Experimenters All Over The World



Detailed solid scale Republic Seabec, built by Robert C. Mikesh

MORE HELP FOR MODELERS. The Veterans of Foreign Wars, national veterans organization, will undertake a vigorously expanding program for model aviation, in cooperation with Air Defense Command, National Guard, and the Civil Air Patrol. The V.F.W. pioneered in model plane activity through the work of Carl Hopkins of Clarksburg, W. Va. who established one of the country's oldest model clubs in 1927.

The V.F.W.'s 10,000 posts will engage in the new program through formation of local model clubs, or aid to clubs already in existence. A large scale organization was inaugurated in Kansas City recently under joint sponsorship of V.F.W. and

Gold Stars United of American War Dads. This unit will be named in honor of Lt. Robert Mooney, who was shot down while serving as fighter pilot over China in 1942. C. R. Mooney, Lt. Mooney's Gold Star Dad, hopes to establish similar "liv-ing youth memorials" throughout the nation.

Maj. Gen. Claire Chennault, famed leader of the "Flying Tigers" is a staunch supporter of the new program, and has offered to contact 1.000,000 Chinese boys who are interested in model aviation. Strong indorsement is also given by J. Edgar Hoover, James H. Doolittle, Eddie Rickenbacker and many others. RESULTS OF THE ELECTION

of

A.M.A. officers for 1948 have been announced. New president will be C. O. Wright, of Topeka, Kansas who, through his long experience with association work in the central states, is expected to lend great impetus to the national model aviation movement. Russell W. Nichols of Washington, D.C. will continue as Secy.-Treas. and the following District Vice Presidents and Contest Board Members were elected:

District I-VP David Hunt, West Hartford Conn.; CBM's Bernard Collins, Providence R.I. and Carl Hermes, Bridgeport Conn. District II---VP John Schneider Scotia N.Y.; CBM's Harold G. Bradish, Schenectady N.Y. and William Fletcher,



John M. Olson hopes to add radio control to this model Cub Coupe



Siemens Schuckert D4, a WWI job constructed by Dan Weinberg



W. Van Rensburg built this Whippersnapper



Jet powered U-control made by Lawrence Gostomski



Thomas Gabriel's modified Jabberwack



Korda Wakefield winner has afforded fine results to Alfred Walsky



From Holland, G. van der Linden sends picture of his sailplane

Elmhurst N.Y. District III-VP John W. Hillegas, Cleveland Ohio; CBM's Carl Hopkins, Clarksburg W. Va. and Chester Hopkins, Clarksburg W. Va. and Chester Lanzo, Cleveland Ohio. District IV—VP Frank Parmenter, Hampton Va.; CBM's Dr. Walter A. Good, Silver Spring Md. and John Worth, Hampton Va. District V —VP H.R. Hudson, Atlanta Ga.; CBM's C. C. Caviness, Atlanta Ga. and C. H. Thompton Laghcaptille Ela District V Thornton, Jacksonville Fla. District VI-VP Frank Nekimken, Indianapolis Ind.; CBM's Carl Goldberg, Chicago Ill. and Al Yount, St. Louis Mo. District VII-VP R. F. Watson, Des Moines Iowa; CBM's Frank Sposite, Detroit Mich. and Curtis Janke, Sheboygan Wis. District VIII—VP Rogers Barton, College Station Tex.;

MODEL AIRPLANE NEWS . April, 1948

CBM's John Clemens, Dallas Tex. and Rogers Barton, College Station Tex. Dis-trict IX—VP Leo Rutledge, Wichita Kans.; CBM's C. L. Bristol, Cheyenne Wyo. and James McClelland, Wichita Kans. District X—VP Ray Acord, L.A. Calif.; CBM's Jack Douglas, Salt Lake City Utah and Harvey Robbers Sr., Oak-land Calif. District XI—VP Jim Walker, Portland Ore.; CBM's Elmer Roth, Salem Ore. and E. R. Nichol, Portland Ore.

WE HEAR FROM AN old correspondent, Joe Bligh of Atlantic City Sky Blazers, that activity in that vacation spot is high despite a tough winter. Indoor flying is practiced in the world's largest audi-torium (seats 41,000 according to Joe)

where high time for the city is 12:47.0, made by John Ginnetti. Joe passes on an interesting tip which should be useful to anyone living near the sea. The Sky Blazers have had the usual winter trouble in that their baseball diamond control line field is either a quagmire from alter-nate freezing and thawing, or is covered with a treacherous blanket of snow. They have the problem licked now, however, as they simply do their flying on the ocean beach at low tide. Every high tide sweeps the sand smooth, packs it down, and clears away snow if any has fallen. They have had no trouble with noseovers or sand in engines, and have been able to

(Turn to page 42)



INERTIA STARTER







This starter uses no battery or wires—a strong arm is all you need by DALE SPRINGSTED

ERE'S a starter anyone can make and operate. No batteries, no motor, no carrying case needed—just a hand grinder and a small flywheel from your neighborhood junk shop. This starter is constructed as follows:

Any grinder can be used; this particular starter utilizes one having a 10 to 1 gear ratio, but there is no reason why a higher or lower ratio would not work out well. The flywheel is a piece of turned steel 4" in diam. 1" thick, about 3-1/2 lbs. in weight. A hole the size of the shaft on the grinder is drilled in the center of this wheel. A piece of common 3" channel iron 1-1/2" wide was drilled in the center with the same size hole as in the flywheel. Next a piece of round cold rolled stock also of the same diameter was inserted through the flywheel, the channel iron placed in position on it and welded to the flywheel. Then the channel was welded to the cold rolled bar, and the excess bar cut off inside the channel. Caution was used in this operation to make certain that all parts lined up since it is important that there be no wobble in the outer shaft.

Common automobile heater and radiator hose was pressed on the outer shaft and clamped in place with a standard hose clamp. This assembly is used on the grinder in place of the stone, but the latter may be replaced at any time.

The bench is very simple to construct. The main crossmember is 2" by 4", while the legs and gussets are 1" stock. To operate the starter—hook up your

To operate the starter—hook up your booster batteries in the usual manner. Place prop spinner in the cone formed by the rubber hose, and have your mechanic crank at a moderate speed. We found it advisable to prime the motor, retard the spark, and have the needle valve setting about 1/2 turn richer than the regular operating mixture of the motor. A word of caution though—don't try to use a plastic spinner since the hose cuts into it and leaves unsightly ridges where it was in contact.

MODEL AIRPLANE NEWS . April, 1948

Tester for Model Sparkplugs

By Ray Rusher

A HANDY miniature tester suitable for model sparkplugs can be readily made by the model engine user from the types of neon tubes or bulbs shown in drawing 1. Such a tester will enable you to determine whether the plug is sparking or not, with-out having to remove it from the engine. A neon tube is preferable because it produces a brighter glow or flash during tests. If you are unable to purchase these, buy a sparkplug tester (drawing 2) at any auto supply store. They are 4" or 5" long, provided with a clip so they can be carried in the pocket, and usually cost 25c. If unavailable, a line tester for electrical and radio work (drawing 3) or a night light (drawing 4) can be purchased for 25c to 50c. Line testers and night lights will be found to contain the bulb type of neon light. light.

To remove the neon tube from a pocket sparkplug tester, cut through the transparent plastic barrel at a with a hack-saw, or saw off the metal cap at b if the tube the metal cap at 6 if the tube is of glass, being careful not to damage the neon tubes inside. These testers are usually pro-vided with two neon tubes, so you will have two model spark-

you will have two model spark-plug testers. To remove the neon bulb from a line tester, saw the sleeve at c and pull the assembly of bulb, resistor and leads (drawing 5) out of the transparent plastic protective housing, being care-ful not to break either of the fine wires extending from the bulb. To remove the neon bulb from a night light, remove the fibre cover at the base, and the wires leading from the terminal prongs to the resistor and bulb will be exposed. Drawing 8 gives details and shows the relation of parts. Carefully break the wires loose from the prongs and the resistor and bulb can be pulled out. out. Your

Your miniature sparkplug tester can be made from one of tester can be made from one of the neon tubes by cementing a piece of black paper around two-thirds of the tube as in drawing 6 to serve as a back-ground for the glow or flash in the tube and as a light shield so that the glow can be more readily seen, especially in broad daylight. The intensity of the glow can then also be more accurately judged. This shield can usually be omit-ted for testing on the workbench. Draw-ing 7 shows a crossection through the tubes

ing 7 shows a crossection through the tubes and shield of drawing 6. The shield also serves as a protector for the glass tube of the tester when the tester is kept loose among other small parts, bolts, etc., in your tool or kit box.

tool or kit box. To use the tester, merely touch one of the metal end caps to the top of the spark-plug while the engine is running slowly, or while turning the prop over by hand. Hold the other metal end cap in your hand and the glow or flash will be brighter than if you held the glass. You will not receive a shock unless you are touching ground (the engine) also. Even then the shock will only be slight due to the birth resistance of only be slight due to the high resistance of the neon gas in the tube. A bright glow or flash indicates a properly firing plug. See the following chart for a full outline of provide the following chart for a full outline of possible tests.

TEST CHART

Engine turning over by hand Indicates no flash.....dead sparkplug or high tension current too weak to cause spark dim flashsparkplug fouled or current too weak to cause satisfactory spark

medium flash...satisfactory spark bright flash.....excellent spark

Engine running slowly

Indicates dim glow.....sparkplug fouled but suffi-cient spark to run engine medium glow....satisfactory spark bright glow....excellent spark

If the sparkplug is fould with carbon and/or oil so that there is secondary cur-rent leakage, the spark across the gap of the sparkplug will be lean and weak. This is indicated by a dim glow or flash in the

tester. The high tension lead can also be tested by touching the sparkplug tester to the insulation while rotating the engine by hand. A bright flash indicates possible leak-age, and a dim flash or none indicates a grounded lead. No flash may also indicate a



broken wire inside the insulation and there-

fore an open circuit. By starting at the sparkplug and moving the tester along the lead, a change from no flashes to flashes will indicate the point of break.

of break. Drawing 9 shows how a neon bulb from a line tester or a night light can be adapted as a model sparkplug tester. Two strips of tin or brass 1-16" wide serve as contact strips. The wires from the base of the bulb are soldered to the strips after passing through small holes drilled in them. Omit the resistors of drawings 5 and 8 as they will cut down the current through the tester. Wrappings of thread hold the strips in place. The wires are then soldered to in place. The wires are then soldered to the strips, using the soldering iron spar-

Then cement the threads to the strips and bulb.

and bulb. It is suggested that a rheostat be cut into an ignition circuit and the sparkplug re-moved from the engines so that the spark can be observed, or a similar test setup made. By then adjusting the rheostat for successively weaker sparks and noting the effect on the flash in the tester you can familiarize yourself with its use. Make some tests in broad daylight and some un-der restricted lighting conditions to see the difference between the appearance of the flashes. flashes.

Model Hobby and **Handicraft Dealers**

STROMBECKER INTRODUCES ANOTHER GREAT SALES-GETTER

Newest in a series of solid wood model assembly sets. All parts ready-shaped.



CONVAIR FLAGSHIP

Twin-engine Consolidated-Vultee Transport, solid model assembly set. Scale 7/64 to 1 ft. Dimensions when assembled: wingspan 10", length 8¼". All wood parts Western Pinc (not balsa). Complete with decal trim and insignia, metal props, tricycle landing gear, illustrated instruc-tions, wood filler, glue, sandpaper. No. C-38. To retail at 69c.

Other sure-fire items for rapid turn-over:



Piper Cub Super Cruiser. No. C-34. 50c Piper Cub Super Seascout. No. C-37. 50c

DC-6 Flagship. No. C-36, \$1.00 DC-3 Flagship, No. C-35, 59c P-80 "Shooting Star". No. C-32, 59c P-61c "Black Widow". No. C-33. \$1.00 B-24 Liberator, No. C-76, \$1.69 B-29 Superfortress. No. 250. \$2.50 Consolidated Flying Boat. No. C-8. 45c



DeWitt Clinton Train. No. 1831-GT. \$1.00 DeWitt Clinton.

No. 1831-c. 50c Wm. Galloway Train. No. 1837-BT. \$1.00 Wm. Galloway. No. 1837-C. 50c Rock Island Rocket. No. 1937. \$1.50

> Battleship California. No. C-16. 45c Cruiser Indianapolis. No. C-11. 45c

Aircraft Carrier Yorktown. No. C-13. 45c Destroyer Warrington. No. C-14. 45c Submarine Nautilus. No. C-15, 35c

DEALERS: CONTACT YOUR LOCAL JOBBERS!



Model Fans! See your favorite hobby dealer! For FREE catalog describing complete model line write to

STROMBECK-BECKER MEG. COMPANY Dept. MN-4, MOLINE, ILLINOIS

by JOHNNY DAVIS

THE Mohawk Chiet THIS AT A PRICE SO LOW



Compare THESE QUALITY FEATURES WITH ENGINES COSTING TWICE AS MUCH · · ·

One-piece steel cylinder for even heat flow . Deep cylinder fins for efficient cooling . Aluminum crankcase with strong mounting lugs . One-piece crankshaft, hardened and ground • Rotary valve for high performance • Impact fuel induction for high speed . One piece steel piston, hardened and precision fitted to the cylinder • Aluminum connecting rod, heat treated Adjustable timer, easily regulated
 Precision needle valve for fine adjustment • Bakelite gas tank permits use of "hot" fuels • Gasoline tank mounted on crankcase · Large volume exhaust stack for rapid scavenging . Champion spark plug . Hardened propeller flanges . Replaceable propeller bolt.



MOHAWK SPITFIRE COIL for top performance for any miniature motor. Produces intense spark, low battery drain. Complete with high tension lead ... only \$1.95.

See your local dealer or order direct from factory. Add 25c for handling. Or send only \$1.00 and we will ship C.O.D. for balance.

MOHAWK ENGINEERING CO. MOHAWK. NEW YORK

WEST COAST TIPS

CONTEST time is here! Already we have received word that this year's All West-ern Open, sponsored by the Aviation Com-mittee of Los Angeles Junior Chamber of Commerce, has set June 25, 26, 27 and 28 as the dates for this biggest of All Western Contests! Contests!

Tom Engelman, able chairman of last year's show, informed us he would be a contestant this year instead of an official, and that a well known eastern model buildcontestant this year histead of an onletan, and that a well known eastern model build-er and contest director who has taken up residence in Southern California will be selected to head up this year's committee. Since the new man has not been definitely promised as yet, his name is withheld; but if he is selected we feel sure you will really enjoy the meet—he has plenty of that old touch which makes things go right. Speaking of the Western Open always brings to mind that great champion Frank Cummings, two time winner of the Western Open's highest award, the Sweepstakes Championship. Frank is an all around ex-cellent model builder—you name it and he can build it; moreover, he can usually win with it, too!

with it, too!

At last year's Nationals we were the most At last year's Nationals we were the most surprised person in the world when Frank showed up at the control line circles with a sleck little Class III speed ship powered by a K & B Torp. He said, in answer to our query: "Oh. I just thought I might pick up a couple more points." Imagine that! Think of all the time the average fellow spends on a recing ight to get overwhing right and not a racing job to get everything right and not only that but learns how to fly besides. Does Frank do that? Heck, no! He just takes time out from building indoor jobs (which, inci-dentally, he much as well as hitter if dentally, he makes as well or better than anybody we've seen except Bill Atwood) and whips up a nicely designed speed job that immediately is a threat to all comers. Well, Frank didn't exactly set the world on fire at the Nats in control line, since he was pretty busy just winning the National Championship and a Piper Cub—but look out, fellers, he'll probably attend to that little chore next year. He really excels in rubber powered events and indoor flying. This is the field where perhaps his real talent exists. There is a certain indefinable "feel" necessary to get the mest out of indoor ibs that leaves the

the most out of indoor jobs that leaves the average model builder out in the cold. Maybe it isn't necessary to be born with the "touch", but if it is possible Frank must have been born with it.

All this flowery praise is just a build-up to tell you that we pick Frank Cummings to nose out a big field for top honors again this year. Any bets, gentlemen?

We find that the Snafu boys-Ed Lans-berg, Doug Morgan, Don Gulotta, Bobby Brown and others of the stunt flying con-trol line hot shots-have changed their trol line hot shots—have changed their spots. Not literally, just figuratively speak-ing, that is. It seems the other day some of the "control line" boys racked up some ter-riffic flying times with "towline gliders" no less. How about getting ready for the Sweepstakes awards in the senior class at the Western Open? You free flight and tow-line standbys had better keep an eye on Don Gulotta who turned in a 27 minute flight on a T.L. glider the other day. They are also building free flight jobs night and day and getting them tuned up. You know this year's Open might prove to be quite a contest. Which reminds us that we have an old free flight job hanging from

we have an old free flight job hanging from our chandelier, too, Oh, well, it probably wouldn't fly anyway-

Bob Palmer, one of the finest control line stunt flyers in the hobby, had the misfor-



"Mom and Pop" Robbers with some of their Oakland **Cloud Dusters at All Western Open presentations**

Frank Cummings receives trophy and \$300 check as Sweepstakes Open Winner at '47 Western Open. Tom Engelman, who is making the awards, was Director of this big event and is Chair-man of L. A. Junior Chamber of Commerce Aviation Com-mittee for 1948



West Coast Tips

(Continued from page 34)

tune of getting his hand caught in a die-stamping machine and lost four fingers from his right hand at the first joint. Bob is probably one of the best liked model builders on the Coast and we are sure that builders on the Coast and we are sure that his friends and competitors alike extend their sincere sympathy at this tough break. While in the hospital, he was visited by J. C. Yates, Don Gulotta, Ed Tefft and many others one night, and though in great pain, Bob was figuring out how he was going to fly again when he got out. We have known Bob Palmer to be tops not only as a stunt flyer but also as a reglar feller, and we pre-dict he will never miss a lick as soon as his hand heals—because he's got what it takes!

We just received our annual report of the We just received our annual report of the activities of the Oakland Cloud Dusters, that famed club of absolute experts who float around the clouds over San Francisco Eoy. Believe us, with the kind of record they made as a group for 1947 they have a right to "dust off some clouds." Among other highly rated doings, they managed to hang up 13 AMA records during the year; took 54 places in meets like the Western Open and the Nationals: and collected an awful lot of merchandise awards.

Western Open and the Nationals: and col-lected an awful lot of merchandise awards. When this group left for Oakland after the Western Open they needed nearly two cars and a truck just to pack away their prizes and merchandise (included was a motor scooter and some 40" trophies.) We have a list in front of us that gives the club's complete record, but with apolo-gies to "Mom" Robbers--"Mom, we just don't have enough space to print all of it" -we will give the names of the regular, associate, and candidate members:

REGULAR MEMBERS REGUI Manuel D. Andrade Robert E. Blau Stanley Burns Guy E. Dake Michael G. Demos David W. Gilbert Gordon F. Hansen Donald B. Lausten Sergius H. Milisich MEMBERS Lawrence E. Parsons Andrew G. Peterson Charles E. Pottol Carl G. Rambo Donald J. Robbers Harvey S. Robbers, Jr. Jarvey S. Robbers, Sr. James A. Robbers Jyrtle B. Robbers James F. Tangney Arthur R. Wells

ASSOCIATE MEMBERS nett Richard E. Schumacher Robert E. Moncrieff Stuart G. Bennett CANDIDATE MEMBERS George Matsumoto Larry Mongeon

We have word that the Burbank Club is planning a contest for April 25, with a few new wrinkles thrown in concerning scale speed races. (We will try to have more in-formation on this in our next issue.) The scale speed idea was first thought of nearly a year and a half ago, but so far this Bur-bank contest will be the first attempt to use it.

bank contest will be the first attempt to use it. Incidentally, we noticed an ad recently where an Atwood Champ held the Class VI-A Sleeve Bearing racing class speed this type of event; at the time it created quite a lot of favorable comment because it tended to cater to the younger modeler with the slimmer pocketbook. But few contest directors were courageous enough to attempt hold a contest, fearing there would be too few contestants.

attempt hold a contest, fearing there would be too few contestants. We believe it would be possible to have separate classes of sleeve and ballbearing engine powered models. This would tend to level off the competition and permit more attendance at small meets, especially those where the 12 year olds and up could com-pete. We would appreciate comment on this idea, and perhaps if enough response is found it will be possible to carry the pro-posal before the AMA contest rules commit-tee for a separate breakdown. What say you?

| | ΡΗΟΤΟ | CREDITS |
|-------|-------------|---------|
| e | | |
| Upper | British Cor | nbine |

Upper 2 Lower

Pag

- Consolidated Vultee Harold G. Martin Robert C. Hare All 15
- 23 All

Enjoy the Fun of Building These Popular SCIENTIFIC MODELS



"CIRCLE KING", Wingspan 30", length 27". Flies on 24-toot lines of cotton thread. The Circle King is a rubber powered control-line model that is easily built from the complete kit which contains a double set of plans for a CO or rubber powered airplane



"CYCLONE", Classes A-B-C, Wingspan 36". Here's a proven champion as is evidenced by the hundreds of letters received from satisfied Cyclone owners. The Cyclone control-line model is excellent for stunt and training purposes. Kit is complete, con-taining every last detail right down to the smallest bolt and nut.



"STUNT ACE", Classes B-C. 40" Wingspan, length 27". The Stunt Ace is capable of performing every stunt in the book-flies inverted 6" off ground-ver-tical eights-horizontal eights-spectacles-inverted inside and outside loops and overhead eights. Kit is complete including rubber \$3.50 27 \$3.50 wheels



"TRAIL BLAZER", Classes A, B, C. 24" SPAN 6 CHORD. For the thrill of your life fly the Trail Blazer. Kit is most complete, comparing with models selling for twice the price. Finished balsa wood fuselage carved inside and out, metal bell crank, wire, full size detailed plans and simplified step-by-step instructions.



MODEL AIRPLANE NEWS . April, 1948
The Scale Model Supreme! **BE SURE TO BUILD IT**



DOUGLAS DC-3 "Workhorse of the Air" Span 70¾" Super-detailed. Almost like \$14.50 building the big plane itself. MFM Kit...... 36" Model "IT" Dry Kit, \$1.00 0.5 303/4" Republic P-47 THUNDERBOLT \$4.00 MFM Kit..... 28" Republic SEA-BEE \$3.00 MEM Kit 1.50 Northrup P-61 BLACK \$1 4 50 WIDOW 491/4" MFM Kit. 1 7 36" T Kit 1.50 R. For the Really an r Serious Model 30" North American \$1.00 Builders 46" Deuglas HAVOC A-20 MFM Kit \$8.50 481/2" B-26 MARAUDER MFM Kit \$9.50 55" B-25 For CO-2 motors \$1.00 Dry Kit ANCER MITCHELL MFM Kit \$9.50 **Tether TOPPERS** Topper 1 (CO-2) \$1.00 Topper 11 (A & B) 2.23 Topper 111 (B & C) 3.00 32" Baby FLEETSTER Designed especially for CO-2, but may \$1.25 be flown rubber. 62 30" PIPER CUB 30" Piren 600 Big favorite among all model builders. \$1.00 LUSCOMBE \$3.00 SILVAIRE Gas... 1.00 Dry Kit. 30" IT Kit. 30" Beechcraft BONANZA Dry Kit..... CIT. \$1.00 STREAMLINER B or C. Builds either tractor either \$4.00 or pusher Send for FREE Jumbo De Luxe SHARPIE Greatly im-proved Kit. Folder

See your dealer first. If he is unable to supply you, accept na substitute, but order direct, en-closing 25c for packing and postage.

Cleveland Model & Supply Co. World's Largest Manufacturers of Quality Model Aircraft Lines-Since 1919 4514D1 Lorain Ave., Cleveland 2, Ohio, U.S.A.

Latest RADIO CONTROL Developments and Official LICENSE Data!

by ED LORENZ

RECENTLY there has been considerable excitement over the new Citizens Radio Service band (460-470 megacycles) as a means of operating radio controlled models without a license. There are those, sup-posedly "in the know", who have received information from the FCC (Federal Com-munications Commission) and given it their own interpretation, and those who know nothing more about it than the announce-ment of a free band. We will try to clarify

ment of a free band. We will try to clarify this matter and give you a complete picture of just what the situation is. At a recent AMA-FCC meeting in Wash-ington (attended by Dr. Walter Good, vari-ous manufacturers. members of the AMA and FCC, and the author) the frequencies and other rules and regulations were dis-cussed and set up. This article deals pri-marily with what took place there and has been approved by the FCC and AMA as being correct and authentic in every way. First of all, it must be remembered that the FCC and not the AMA is the governing body as far as radio transmissions are con-

body as far as radio transmissions are con-cerned, and it therefore makes all rules and regulations covering the use of a radio

transmitter. The AMA may and does act as intermediary between the FCC and the model builder in making the rules covering the flying of radio controlled models. At present the FCC requires that each and every person operating a radio transmitter must have the proper license to cover such operation. There are no exceptions to this operation. There are no exceptions to this rule. Then what can the model builder do to fly his radio controlled model? He can obtain a "ham" license (write to the A.R. R.L. in West Hartford, Conn. for informa-tion, or get in touch with a local ham), or he can wait until the so-called "license free" bands are opened for public use. We said so-called "license free" bands because there will be a simple license required, but probably nothing more than filling out a card and filing it with the FCC. No techni-cal knowledge or code will be required. It must be pointed out here that no indi-vidual will be allowed to construct his own

vidual will be allowed to construct his own transmitter for operation in the allotted bands of 27.230-27.280 megacycles and 462-468 megacycles. Manufacturers will be required to take out special licenses to experiment on these frequencies and will have to



of MORE OPPORTUNITY for you than ever before in Aeronautical Engineering

Right now there are more aeronautical engineering projects under way, and scheduled for the future, than ever before. Opportunities for the aeronautical engineer grow greater, grow broader, day by day. Spectacular progress in aviation is being ushered in by Flying Wing design, jet and rocket propulsion, gas-turbine engines, sonic and super-sonic speeds, atomic power, and many other still-secret developments.

All this means more opportunity than ever before for YOU. Creativeminded, or practical-minded, there is a place for you in Aeronautical Engineering, with its many types of duties...in design, research, development, and production. The door is wide open for making original contributions to the progress of Aviation...for reaching the heights of personal achievement...for gaining security and success.

Prepare yourself to grasp these enviable rewards...with training that fits you to meet the industry's needs. At Northrop Aeronautical Institute you are trained by a division of the organization that developed the Flying Wings and other famous aircraft...an organization that is itself a major employer of engineers and knows *bow* and *what* you must learn.

In only 2 years (in less time, with advanced standing), you can complete the Northrop Aeronautical Engineering course... a technical institute curriculum accredited by the Engineers' Council for Professional Development. Find out how this Northrop course gives you both a better start and an earlier start on your career. Send coupon for full details.

> N.A.I. also offers a 1-year Aircraft and Engine Mechanics course approved by the Civil Aeronautics Administration.



| COUP | ON FOR | CATALOG | ANDC | OMPLE | TE INF | ORMATI | |
|----------|--------------------------|---|----------------------------------|-----------|-----------|--------|--|
| ORT | HROP | AEROI | NAUTI | CAL | INST | ITUTE | |
| | 6 1 | | | | | | |
| arting d | ates of clas Aeronaut | sses. I am inte ical Engineer: Aircraft and . | erested in ing Aircraft Er | igine Mec | hanics (2 | 4 & E) | |
| arting d | ates of clas | sses. I am inte ical Engineer Aircraft and . | erested in ing Aircraft En | igine Mec | hanics (7 | 4 & E) | |
| arting d | ates of clas | ises. I am inte ical Engineer Aircraft and | erested in ing Aircraft Er | ngine Mec | hanics (2 | A & E) | |



GERMAN HALBERSTADT CL-2 OF 1917 THIS TWO SEATER WAS PRODUCED BY THE HALBERSTADTER FLUG-ZEUGWERKE AT 10.000 FEET IT MADE 97 M.P.H. POWER WAS FUR-NISHED BY A 180 H.P. MERCEDES



have the units approved by the FCC before they are put on the market. Please note that while these frequencies are near the present ham bands, no ham will be allowed to operate within the bands unless he has obtained the proper license. If you are a ham, or have a ham friend and desire to experiment on the amateur frequencies of 28.500-29.700 megacycles and 420-450 megacycles to perfect receiver design, it would be a simple matter to change to the radio control frequencies when transmitters are available. In any case, the individual will not be allowed to change the frequency of the purchased transmitter in any way. This means that the receiver must be built with a variable frequency control of some sort. The transmitters will probably be sealed at the factory and only battery changes will be permitted. It is thought, at present, that even the changing of a tube will not be left to the purchaser since this may be enough to put the transmitter off frequency.

This is especially true of the 462-468 mc band, where length of tube leads and other wires definitely affect the frequency of the unit. Repairs or tube changes on transmitters in the 27.230-27.280 mc band probably will be allowed by persons holding a 2nd or 1st class commercial radio license. Repairs and tube changes in the 462-468 mc band most likely will have to be made by the manufacturer of the unit. The individual may make his own receiver and control mechanism, but due to the close frequency tolerances on the low band and the difficutty in working with U. H. F. (300-3000 mc) the model builder probably will have to purchase the receiver and transmitter in one complete set. For those qualified to use the necessary amateur frequencies for experimenting, it is well to remember that the power requirements on transmitters for the radio control bands are 5 watts input to the final stage on the 27.255 mc (center frequency) band and 10 watts input to the final stage on the 465 mc (center frequency) band. This will eliminate the use of some of the 25 to 100 watt transmitters which are being used for radio control at the present time.

time. Although these two new bands have been approved by the FCC for experimental work, there are so far as is known no manufacturers ready to submit their equipment for approval. When such units do reach the market it is believed that they will be bulkier, heavier and more expensive than present commercial equipment, and the latter thus appears to be the only equipment that will be available for quite some time.

time, The receivers, since they must be carried by the plane, are our chief worry as far as size and weight is concerned, and will undoubtedly be 1 to 4 ounces heavier, per channel, and a bit larger. Power requirements should remain the same. The cost will be higher due to the extensive research and engineering needed, especially in the 465 mc range, but should drop almost immediately due to the expected high volume of sales,

Here are a few suggestions to go on when designing your own receiver. Due to the





narrow width of the low frequency band-50 kc compared to the present 6 meter band of 4 mc—a very selective circuit will have to be used to confine the selectivity of the to be used to confine the selectivity of the receiver to the transmitting frequency of about 27.255 mc. Present superegenerative receivers tune quite broadly and therefore would probably be of little use. An R. F. amplifier, crystal circuit or superhet circuit most likely will be used. For the high band, a superhet circuit appears to be the best bet. This is due to the fact that there are very few tubes available for this high fre-quency, which would be suitable for model use, and amplifiers or mixer circuits would

quency, which would be suitable for model use, and amplifiers or mixer circuits would have to be used. It should be pointed out here that present equipment cannot be changed over to the high band. It may, however, be converted to the low band without too much trouble. Control mechanisms will probably remain the same for quite some time. New versions will appear but complicated means of con-trol will still be a thing for the future. Jet propelled, multi-engined craft and models with everything operating by R.C. are nice to dream about, but it would be far better to wait until this new phase of model buildto wait until this new phase of model build-ing progresses a little more. Control line models didn't loop-the-loop or hit 140 mph a week, a month or even a year after they were introduced. The model builder would do well to concentrate on the design of a stable airplane and the mechanical means of actuating the controls, or we should say control. It has been proven time and time again, by experts, that rudder control will accomplish more than a plane load of radio equipment.

The Good brothers have won many con-The Good brothers have won many con-tests with rudder control alone. The excep-tion to a simple single control is Jim Walk-er's marvelous multi-channel proportional control plane. But all this will come in time and some day we may hold miniature Na-tional Air Races, with radio controlled models performing all the feats of the larger planes. In closing, remember this: keep your equipment as simple as possible; keep it neat and don't try to overpower your plane or expect too much from your first radio job.

(We expect soon to publish complete data on receivers suitable for the two new bands. Transmitters, however, will be covered briefly if at all since homemade transmitters will not be allowed in these bands, and further-more the bands are not yet "open".--EDITOR)

Modeling in Flying Schools

(Continued from page 21)

"We do consider model experiments, building, and flight most valuable in the development of air interest and air knowledge," continues Hammond. "However, there seems to be a failure to connect up the performance and understanding of the model with the aerodynamics, engineering, and understanding of full flight. Model work seems to consist of an element of interest limited to satisfaction at the observance of the phenomenon of flight; whereas, full scale work carries an interest based on understanding. Flight may be necessary as proof, but many an aerodynamicist or engineer has never flown or even been in the air.

"My thought is that a greater interest should be developed on the part of model workers to understand the why and the wherefore of what they are doing, to convert the results of performance into cause and effect."

While Mr. Hammond's comments are the exception, rather than the rule, and as such may sound arbitrary to many builders, it should be pointed out that his thoughts are constructive. There is some truth in what he says but, on the other-hand, a great many builders do already appreciate cause and effect.

Williwaw

(Continued from page 9)

doping it just to the wing outline—root and tip ribs and the leading and trailing edges. Then the paper can pull tight over the whole surface as it dries, giving an exceptionally smooth covering. Dope the wing thoroughly; a spray gun gives best results. Warp in 3° "wash in" in each tip. "Wash in," of course, means the tips have a higher angle of incidence than the wing root. This is absolutely necessary for fast recovery from critical flight altitudes.

RUDDER-The vertical fin, due to its large size, has a laminated leading edge for strength. Cut the formers from 1/4 soft balsa sheet and build up the leading edge as shown. The ribs are $1/16 \times 1/4$ stock sanded to a streamline section after they are cemented in place. Sand the cockpit fairing down as shown. The rudder is a rather touchy point of the design. Although the original ship was stable, some subsequent models were spirally unstable. If your model should show any tendencies to spin in during test flights this can be corrected by adding a 1/8 sheet balsa sub-rudder approximately 3 or more inches deep and with the same chord as the fin on top. The subrudder must be solid, though, to with-stand landings. The rudder is also cov-

ered with Silkspan similar to the wing. PROP—The prop is a single bladed folding assembly designed for fast climb and low drag in the glide. Lay out the prop blank on a block of medium balsa and cut out with a coping saw. Drill the shaft hele. shaft hole.

Start carving; the concave side is cut first. Finish off with fine sandpaper, removing all ridges. About 3/32" undercamber is sufficient. Then carve the top face of the prop so there's about 1/8 thickness at the point of maximum cam-ber. Attach your favorite folding mechan-ism (we used the "Best-by-Test" hinge) and bind well with thread covered with plenty of cement. A tissue covering, several coats of dope and a rubbed and polished finish completes the prop.

The shaft is 1/16'' diameter piano wire. Use a thrust tube in the nose block and a ball bearing washer for a smooth running unit and one in which a thrust adjustment will remain a thrust adjustment. Note that the nose and tail blocks are interchangeable so try the ship anyway you

terchangeable so try the ship anyway you want—pusher, tractor, or both. FLYING—The model should balance at the wing fastening dowel or about 1/8" ahead of No. 2 rib leading edge. The model should glide well with no other adjustment. If it dives, turn up the ele-vators; if it stalls, add weight to the nose. Do not adjust by turning the elevators Do not adjust by turning the elevators down as this counteracts the wash in. First powered flights should be made with about 100 turns. Downthrust will be

needed, the amount depending on the ship. For power we used 8 stranks of 3/16" brown rubber 60" long, prewound and doubled. In this way maximum power can be contained in the short fuselage. A wide spiral climb with a glide of slightly wider radius is good.

LOENING AMPHIBIAN

Control line scale modelers will find this project 'way off the beaten path. This fa-mous old "duck" was a biplane, and our plans in

May issue of MODEL AIRPLANE NEWS

will enable you to build an accurate and smooth-flying model. Don't miss this issue. On sale everywhere April 9th.



VOLUME 3, NO. 5

| GAS ENGINES | | GMCO | | U-C |
|--|--|--|---|----------------|
| *Arden .099 P. B\$12.50 | YOUP C | VIALITY | | Laire |
| *Arden 199 B. B 15.50 | TOOR | (UALIII . | JOFFLIER | Dron |
| *Atom .099 15.50 *Bantam .199 18.50 | Buy from GMCO- equipment in the | -the Model Supply H USA. Our 21 years | ouse with the finest of experience guar- | Spee |
| *Ohlsson 19 9.95 | antees you the u | tmost value for you | r money-quickest | Miss mi |
| *Ohlsson 23\$ 9.95 | Don't forget GMU | 'O's outstanding cat | alogues-for planes | Flyir Perk |
| *Sportsman Jr. 36., 14,95 *OK Hothead 12,50 | 25c each. | or snip models, one | for railroads. Only | Star |
| *McCoy 29 | SUPPL | IES AND ACCES | SORIES | The |
| Super 29. 16.50 | ALUM. TUBING | Paper Cond25 Austin Timor 1 50 | VECO | A. J Miss |
| "Bullet 100 12,75 Thor 30 | 1/16"10a | Arden Timer 1.85 | (With Turned | Beec |
| *Forster 29 | 3/32"10c 1/8" 12c | coil 2.50 | 34" dla,20c pr. | Junio |
| *K&B Torpedo 24 16.50 | 5/32" | Arden Coil., 2.50 Competitor., 1.95 | 1 %" dia | Fokk |
| Class C | 1 4″18e | New Wilco . 1.95 | 1%" dia. 50e pr. | Bear Cyclo |
| *Ohlsson 60 | Needle Valve | Aero Twin 4.00 | 2 %" uia. SUC pr. VFC0 | Supe |
| • Vivell 35 | Flexible Needle Valve \$1.00 | Smith Dual 4 50 | AIR WHEELS | Hipe |
| Dennymite 57 | Spinit Starter 5.00 | Fuel Shur Off Valve 1.00 | pr | Baby |
| *Wasp-Twin | U-Reely Con | PROPELLERS | 3½" dia., pr. 2.50 | P-51 |
| *McCoy 49 25.00 | Perrycraft | Flo Torque | 43/g" din., 9.75 | Gr'n |
| *Madewell 49 12.50 | Tank 2.50 Froom Tanks 1.00 | 8"to14" ea. \$.35 | Veco Bell- | Skys |
| "OK Twin 49.00 | Alum, Prop Spinners | III - B all | Toggle Switch 45c | Navi |
| *Super Cyclone S.I. 17/95 *Super Cyclone D.I. 18/95 | 13/16" 30c : 1 %" | (High Pitch) 9"to14" ca35 | Slide Switch | Strea |
| *Contestor RV 18.50 *Forster 99 24.75 | 2", 1.15; 214", | Testor's Props | Per Wee Clip 10c | Firel Custo |
| *Sportsman Jr. 36 14.95 | 1.25; 2 ¹ 4", 1.50; 2 ¹ 4", | Rite Pitch | clip, 2 | Orbin |
| Super Champion JH 17.50 | Hi-Tension Lead 15 | 12" to 14" .60 | Sulderless | Zing |
| *Spitfire 60 | Ignition Wire | Diesel Conver- sion Kit for | Plug | Cade |
| DIESELS | Arden Glow | Arden .099., 3.00 Arden .199 3.50 | 14" OF "" | Curti |
| Mite A | Plug ,85 | Reggie Pink | gasket, 2 | Whip Tyre |
| Air-O-Diesel | POWER PLUS | (Shipped Ex- | Hinges | Strat |
| IFT | WET CELLS | Two Speed Con- | Class A, pc15c | Voug |
| Dyna Jet Standard \$24,50 | Free-Fliter.\$2.25 Super-Fliter 2.95 | trol Line Sup- plies. Electra- | Swivels, Class B.C. | Gee |
| Dyna Jet Red Head 35,00 CO2 Engine 4.95 | Race Car Special 5.50 | line Wire, | pr | Stun |
| Campus A100 12.50 | Booster 3.50 | din., 150 ft 1.50 | BER WHEELS | Dem |
| F.F. GAS KITS | Aero lock lead | Ohlsson 2- | 2" dia | Supe |
| Buccaneer 36\$ 1.95 | B.B. Washers .10 Steel Music | Speed Points 1.75 Stranded Steel | 35% dia60c | Lil 3 |
| Super A Skyrocket. 1.95 | Wire, all sizes, | Control Line, 7 Strand flar, | COLORED DOPE | Bust |
| Brigadier 38 1.95 Piper Cub Coupe 1.95 | Spark Plugs | ible, non-kink- | ora: 1 oz., 150; | P |
| Mike 2.00 Easterner 2.50 | ea | dia, 70 ft. 1.00 | 2 oz., 20c: 4 oz., 30c: | Stins |
| Runt | Silkspan GM | .020" dia., 70 ft 1.15 | 1/2 pt., 55e | Cessi Culve |
| Miss Tiny | | PURE BROWN | (Wood filler same | Inter |
| Ardent Air 2.00 | TREXLER | NATURAL CON- TEST RUBBER | dope.) | Pipe |
| CLASS B | 2" dia 8 .50 | AT PRE - WAR | CEMENT. | Erco |
| Brigadier 58 | 2% " dia 100 | %" flat, | THINNER, BA- | Golly |
| Buccaneer Spec 3.95 Playboy Junior 3.25 | 3" dia 1.25 3%" dia 1.50 | per ft\$.01 3/16" flat. | NANA LIQUID | Jabb |
| Zipper 5.95 | 4%" dia 1.75 | per ft01 1/4 | oz., 20c; 4 oz., | Ther |
| Humdinger | Smith Cond35 | per ft | 1 pt | Folke |
| Roamer 2.95 | Minimum Wood | order #1 Include 25 | packing charge | Piper |
| Diamond Demon 2.00 | STRIPS | 5/16 x 3/86c | 1/16 x 311c | Gran |
| Brooklyn Dodger 3.95 Powerbouse 4.95 | 1/16 x 1/16 8 | 5/16 x 1/280 5/16 x 5/89c | 3/32 x 313e 1/8 x 315e | Sail |
| Coronet 1.50 | 1/16 x 1/8 6.5c | 5/16 x 1 | 3/16 x 3 17e | Prest |
| Interceptor | 1/16 x 1/41c | 3/8 x 1/2 10c | 3/8 x 3 27c | Cami Ouec |
| CLASS C New Buccapeer Strid 55 95 | 1/16 x 1/2 | 1/2 x 1/210c | BEVELED 36" | Liber Augu |
| Custom Cavalier 108 17.50 | 3/32 x 3/32 65c 3/32 x 3/161e | 1/2 x 3/415c 1/2 x 1 | EDGES | Const Sea V |
| Cruiser | 3/32 x 1/4 3 50 3/32 x 3/8 20 | 5/8 x 5/815c 5/8 x 118c | 3/32 x 3/830 | Sub 1 Fireb |
| Flamingo Amphibian 9.95 Playboy Senior 6.00 | 3/32x1/2 2 1/2c | BALSA 36" | 5/32 x 5/85c | Super |
| Westerner C 5.95 | 1/8 x 3/16 3.5c | PLANKS 1/2 x 2 24c | 5/32 x 7/87c | Subm |
| Mercury 5.50 | 1/8 x 1/4 2 | 3/4 x 2 | POWERED | MeCo |
| Buzzard Bombshell 9.95 | 1/8 x 1/2 .4c 1/8 x 3/4 .5c | 1/2 x 3 | BOATS | McCo |
| RADIO CONTROL | 1/8 x 1 | 2 x 3 | Chris Craft \$4.95 | New |
| Good Brothers, complete | 3/16 x 1/4 4c | 3 x 31.50 | 0-Gee Kit. 5,95 | Reuh |
| Aero-Trol, complete (less | 3/16 x 3/8 | SHEETS | Sea Elf 5.50 | NOTE |
| Datteries) | 3/16 x 3/48c 3/16 x 1 9c | 1/32 x 2 70 1/16 x 2 | Sea Bird 4.95 | |
| CONTROL | 1/4 x 1/4 | 3/32 x 2 | Hardware Kit. 2.95 | TERS |
| Packaged radio control | 1/4 x 1/2 | 3/16 x 211c | Sea Gull 7.50 | ASK |
| \$120.00. | 1/4 x 1 | 3/8 x 214c | Owens 4.95 | 0008 |
| · | MAIL THIS OF | UPON TODA | | |
| GMCO MODEL CRAFT NO | BRIES (MA-4) | USI OF TODA | (Tel. IAmales | 3-9140) |
| 1 166-21 Jamaica Ave., Jam | alca 3, N.Y. | 25o anah) 🗂 Bin | E Rasa Cara Ci Chia | Models |
| Railroads. Attached is | list of items 1 need. | Send them right aw | a nace cars [] Ship Ly. | m ou€i\$ |
| NAME | | | | |
| ADDRESS | | | | |
| Laumu | | | | |

| | GMCO | | |
|--|---|--|-------|
| YOUR G | QUALITY | SUPPLIER | |
| Buy from GMCO- quipment in the s atess you the u ervice-kits, moto ban't forces (AN) | the Model Supply H USA. Our 21 years tmost value for you ors and supplies yo | ouse with the finest of experience guar- ir money—quickest u can depend on. | |
| k race cars, one f | or ship models, one | for railroads. Only | |
| SUPPL | IES AND ACCES | SORIES | |
| Dia, per ft. | AustinTimer 1.50 | WHEELS | |
| /16"100 | Aero Lt. Wt. | Alum. Hubs) | |
| /8 120 /32"120 | Arden Coil. 2.50 Competitor. 1.95 | 11/a" dia20c pr. | |
| 4"isc niversal | New Wilco 1.95 Aero Qual. 3.00 | 1%" dia. 50c pr. 2%" dia. 60c pr. | |
| eedle Valve | Aero Twin 4.00 Firecracker 2.75 | VECO ALR WHEELS | |
| eedleValve\$1,00 pinit | Fuel Shur Off | 21/2" dia | |
| Larter 5.00 J-Reely Con- | PROPELLERS | 31/2" dia., pr | |
| errycraft | Flo Torque (Low Pitch) | 4½" dia., pr. 2.75 | |
| room Tanks 1.00 lum. Prop | 8"to14" ea. \$.35 16" & 18"75 | crank | |
| pinners. 3/16"30c:1%" | (High Pitch) | Slide Switch | |
| 50;1¼",1.00; ",1.15;2¼", | Testor's Props | Per Wee Clip 10c | |
| .25; 2 ¹ / ₂ ", 1.50; %" | Rite Pitch 8" to 11"50 | clip, 2 | |
| end | 12" to 14" | Solderless Plug | |
| er ft | sion Kit for Arden 1099 3.00 Arden 199 2.50 | Lugs, 1210c | |
| Plug ,85 | Reggie Pink Fuel of 1.25 | gasket, 2 | |
| POWER PLUS | (Shipped Ex- press Collect) | Hinges 20c Swivels, | |
| ree - Fliter. \$2.25 | Two Speed Con- trol Line Sup- | Class A, pc15c Swivels, | |
| ace Car | line Wire, | Class B, C, pr | |
| ooster 3.50 | din., 150 ft 1.50 Relay 2.00 | SPONGE RUB- BER WHEELS | |
| ad | Ohlsson 2- Speed Points 1.75 | 2" dia | |
| teel Muslo Vire, all sizes, | Stranded Steel Control Line, | COLORED DOPE | |
| ft. lengths. park Plugs | 7 Strand, flex- ible, non-kink- | 11 Ass'td. Col- ors: 1 oz., 150; | |
| ilkspan 00 | dia , 70 ft. 1.00 | 2 oz. 20c: 4 oz. 30c: | |
| for | 70 ft 1.15 | pt. \$1.00 | |
| | PURE BROWN NATURAL CON- | price as colored dope.) | 1 |
| dia | AT PRE - WAR | CEMENT, CLEAR DOPE | |
| dia 1.00 | %" fint, per ft\$.01 | THINNER, BA- NANA LIQUID | |
| %" dia 1.50 %" dia 1.75 | 3/16" flat. per ft0114 | 1 oz., 15c; 2 oz., 20c; 4 oz., | ļ |
| ero Cond35 mith Cond35 | ¾" flat, per ft | 30c; ² 4 pt.,50c; 1 pt 76e | 1 |
| Minimum Wood BALSA 36" | order #1 Include 256 5/16 x 5/165c | packing charge | 1 |
| STRIPS (16 x 1/16 | 5/16 x 3/86c 5/16 x 1/280 | 1/16 x 311c 3/32 x 313e | |
| 8 | 5/16 x 5/89c | 1/8 x 3 15c 3/16 x 3 17c | |
| 16 x 3/10 9 | 3/8 x 1/2 10c 3/8 x 3/4 12c | 3/8 x 3 27c | |
| 16 x 1/2 | 1/2 x 1/210c 1/2 x 3/415c | BEVELED 36" TRAILING | 1 |
| 32 x 3/161c 32 x 1/4 3 .5c | 1/2 x 1 | EDGES 3/32 x 3/830 | 10.01 |
| 32 x 3/8 | 5/8 x 1 | 1/6 x 1/24c 5/32 x 5/85c | 1 |
| $3 \times 1/8 = 430$ $8 \times 3/16 = 350$ $8 \times 1/4 = 50$ | PLANKS 1/2 x 2 | 5/32 x 7/87c | 3 |
| 8 x 3 8 3c 8 x 1/24c | 3/4 x 2 | POWERED | 1 |
| 8 x 3/4 5c 8 x 1 | 1/2 x 3 | Chris Craft \$4.95 | 1 |
| 16x3/164c | 3 x 31 50 | U-Uee 10.95 O-Gee Kit 5.95 Harvo 40 | 1 |
| 10 x 3/800 16 x 1/2 6c 16 x 3/4 8c | SHEETS 1/32 7 2 74 | Sea Elf 5.50 Sea Bird 4.95 | 1 |
| 16 x 1 9c 4 x 1/4 4c | 1/16 x 2 | Sea Bird Hardware | 1 |
| 4 x 3 85c 4 x 1/27c | 1/8 x 2 9c 3/16 x 2 11c | Kit. 2.95 Sea Gull 7.50 | |
| 4 x 3/4 10c 4 x 112c | 1/4 x 213c 3/8 x 214c | Jeeno 22_50 Owens 4.95 | |
| | | | |

STATE

| | 2 | - 21 |
|--|----------------------|------------------------------------|
| Ferky A | 2. | 0 |
| Stardust | 10. | 0 |
| The Bat | -2 | . 9 |
| The Bug | 1 | . 5 |
| A. J. Fireball | 1 | . 9 |
| Miss Behave | З. | 9 |
| Beechcraft | 9. | 9 |
| Super Zilch | 4. | . 9 |
| Junior Cruiser | 5. | 9 |
| Falcon Sporster | 3 | , H |
| Fokker D-7 | 7. | 5 |
| Bearcat | 6. | 9 |
| Cyclone | 4. | 9 |
| Super V Shark | 4. | 9 |
| Whirlwind | 7. | 9 |
| Bipe Trainer | 3 | 9 |
| Ercoupe | 7 | 5 |
| Baby Miss Behave | 2 | 9 |
| Answer | 2 | ñ |
| P-51 Controliner | 7 | ġ |
| Navion | 3 | ă |
| Griman Rearcat ESE | 2 | ä |
| Skystreak | ï | â |
| Skycycle | ÷ | ñ |
| Navion (Capitol) | 4 | ΞĘ. |
| Streenliner | ÷. | 5 |
| Sharrin Do luxo | 3 | 8 |
| Firshall | - A. | 0 |
| Custom Crailean 1 | ы. П | 2 |
| Onbis | 0. | 20 |
| Cranbound | · | 10 |
| Greynounu | 2 | . y |
| Zillig | 1 | . 2 |
| a peedster | 5 - | -24 |
| | | in. |
| Cadet | 3. | 9 |
| Trainee | 3. | 9.9 |
| Cadet Trainee Curtis-Hawk P6E | 3. | 9.9 |
| Fadet Trainee Curtis-Hawk P6E Whippet | 3.363. | 9.9.9 |
| Trainee Curtis-Hawk P6E Whippet | 3.3633 | 9999 |
| Cadet Trainee Curlis-Hawk P6E Whippet Tyro Strato Cat | 336335 | 999959 |
| Cadet Trainee Curtis-Hawk P6E Whippet Tyro Strato Cat Fireball Fighter | 3363358 | 999 99 99 90 |
| Trainee Curtis-Hawk P6E Whippet Tyro Strato Cat Fireball Fighter Yought Corsair | 33633586 | 999995909 |
| Cardet Trainee Curtis-Hawk P6E WhIppet Tyro Strato Cat Fireball Fighter Yought Corsair Gee Bee | 336335861 | 999959039 |
| Cadet Trainee Curis-Ilawk PGE Whippet Tyro Strato Cat Fireball Fighter Vought Corsair Gee Bee Circle King | 3.3.6.3.3.5.8.6.2.1. | 9999590390 |
| Cadet Trainee Curlis-Hawk P6E Whippet Strato Cat Fireball Fighter Vought Corsair Gee Bee Circle King Stunt Ace | 33633586213 | 99995905905 |
| Cadet Trainee Curlis-Hawk P6E Whippet Strato Cat Fireball Fighter Vought Corsair Gee Bee Circle King Stunt Ace Sky Buksy | 336335862135 | 999959059059 |
| Cadet Trainee Curtis-Hawk PfE Whippet Strato Cat Fireball Fighter. Yought Corsair Gee Bee Stunt Ace Sky Bugg Demico Special | 3363358621357 | 9999590590599 |
| Cadet Traince Curlis-Ilawk P6E | 33633586213512 | 99995905905999 |
| Cadet Trainee Curlis-Hawk PfE Whippet Tyro Strato Cat Firehall Fighter Youdut Corsair Gee Bee Circle King Skunt Ace Sky Buegy Demico Special Hahy V Shark Super Circh | 336335869135092 | 999995909905999999 |
| Cadet Trainee Curtis-Ilawk P6E | 3363358691357924 | 999959059059999999 |
| Cadet Trainee Curlis-Hawk PéE Whippet Tyro Strato Cat Firehall Fighter Voudut Corsair Gee Bee Circle King Stunt Ace Sky Busky Demico Special Hahy V Shark Super Circle Monocoupe Jai Zlich | 336335868135149449 | 99999590390599999999 |
| Cadet Traince Curlis-Ilawk P6E | 3363358611351494422 | 9999590590599999995 |
| Cadet Trainee Curlis-Ilawk PéE Whippet Tyro Strato Cat Firehall Fighter Vought Corsair Gee Bee Circle King Stunt Ace Sky Busgy Demycy Special Haby V Shark Super Cincl Monocoupe Lit Zitch Buster | 336335869135192422 | 9999590590599999995 |
| Cadet Trainee Curtis-Ilawk PéE | 336335868135682422 | 999959029059999995 |
| Cadet Carling Control of Carling Carli | 336335862135172422 | 9999590590599999995 |
| Cadet Trainee Curlis-Ilawk PéE Whippet Strato Cat Fireball Fighter Vonght Corsair Gee Bee Circle King Stunt Ace Sky Busky Demrco Special Haby V Shark Super Cinch Monocouye Lil Zilch Buster RUBBER POWERED KIT Stinson Voyaget 130 d | 336335862135722422 | 9999590590599999995 |
| Cadet Traince Curlis-Ilawk PéE Whippet Tyro Strato Cat Frieball Fighter Vought Corsair Gee Bee Circle King Stunt Are Skt Buger Demece Special Baby V Shark Super Cinch Buster RUBBER POWERED KIT Stinson Voyage 150 f Cesana 140 | 336335862135772422 | 9999590590599999995 |
| Cadet Traince Curtis-Ilawk PéE | 336335862135722422 | 9999590590599999995 |
| Cadet Trainee Cadet Trainee Verlage Ve | 336335862135772422 | 99995905905999999995 |
| Cadet Trainee Curtis-Ilawk PéE | | 99999590590599999995 55550 |
| Cadet Trainee Curlis-Ilawk PéE Whippet Tyro | 336335862135772422 | 9999959059059999999995 555506 |
| Cadet Traince Curtis-Ilawk PéE | 336335862135772422 | 99999590590599999995 5555065 |
| Cadet Trainee Curlis-Ilawk PéE Whippet Curlis-Ilawk PéE Whippet Tyro Cat Fireball Fighter Vonuch Corsair Gee Bee Circle King Stunt Ace Storight Corsair Gee Bee Circle King Stunt Ace Storight Corsair Start Ace Storight Corsair Curcle King Curles Carlos Corsair Curcle King Curcle Carlos Corsair Curcle Carlos Corsair Curcle Carlos Corsair Curcle Carlos Corsair Curcle Carlos Carlos Corsair Curcle Carlos | 336335862135772422 | 9999955905905999999995 55550650 |
| Cadet Traince Curtis-Ilawk P6E Whippet Tyro Strato Cat Fireball Fighter Vonulut Corsair Gee Bee Circle King Stunt Ace Stugy Demeco Special Buster RUBBER POWERED KIT Stinson Voyaget 150 t Cesana 140 Culver V Interstate Cadet Luscombe-Silvaire Tuper Cub Basecat Ercoupe Zenbyr | 33633586213572422 | 99999559059999999995 55506500 |

Gollywock Jabberwock Baby Fleetster Thermalier Stinson L-5..... Folkerts Bacer, Piper Cub...... 1.501.501.501.00SHIP MODELS Grand Banke Sail King Bluenose 3.50 Preston Campbell 4.00

~

| ~ ~ ~ ~ ~ | | | | | | |
|-----------|-------|-------|----|-----|---|-------|
| Que | en | Ma: | су | | | . 8.5 |
| Libe | rty | Shi | p | | | -1.5 |
| Ang | นจระ | ۰ | | | | 1.5 |
| Con | stltı | ittor | 1 | | | 34.0 |
| Sea | Wit | ch. | | | | 31.0 |
| Sub | Bui | ster | | | | 9.0 |
| Fire | boat | L | | | | 13.0 |
| Vari | 1ev | LST | Γ | | | 5.0 |
| Sup | er F | len | PT | -14 | 0 | 5.0 |
| Sub | niar | Ine | | | | 2.5 |
| | | | | | | |

RACE CARS Invader

50 50 50 00 Racer Railto Jr... himble Drone NOTE NEW GMCO DRESS! WHEN IN N.Y VISIT GMCO'S NEW A LARGER HOBBY QU TERS. AD-Y.C.

SEE THE LATEST MODELS. ASK QUESTIONS, ORDER FROM GMCO'S TREMEN-DOUS STOCKS.

TO ORDER Send full remit Send full remit-tance or send \$1.00 and we ship C.O.D. for bal-ance. We prepay postage and in-sure all orders over \$1.50. TWENTY-FOUR HOURSERV-ICE.

APRIL 1948 U-CONTROL GAS KITS

1.95

6.95 2,00

2,95 1,50 7,95 3,95 9,95 4,95 5,95 3,95 7,50

Flying Manlac..... Perky A Stardust

GOTHAM'S EX-G.I.'s GIVE YOU MORE FOR YOUR MONEY

★ FREE POSTAGE

- ★ FREE PACKING
- ★ IMMEDIATE SHIPMENT

★ MONEY BACK GUARANTEE

★ WE HANDLE EVERYTHING

REMEMBER

Gotham's cx-G.I.'s carry everything.

CHECK

this list of hard-to-get items:

| \star | Fox 59 | \$29.95 |
|---------|---------------------|---------|
| * | Wasp-Twin | 29.95 |
| \star | Forster 29red. to | 14.50 |
| \star | Forster 99 | 24.75 |
| \star | McCoy Sportsman Jr. | 14.95 |
| * | McCoy Sportsman Sr | 16.95 |
| * | Pacemaker C | 12.50 |
| * | Ohlsson 23red. to | 9.95 |



OHLSSON "23" \$9.95

| * | OK Twin | \$55.00 |
|---------|----------------|---------|
| \star | Madewell C | 12.50 |
| \star | Dyna Jet | 24.50 |
| \star | Drone Bred. to | 14.95 |
| 4 | DEEZIL "A" | 12.95 |



DEEZIL "A" \$12.95

| \star | McCoy Hot Rod Race Car\$ | \$42.50 |
|---------|--------------------------|---------|
| \star | Dooling Race Car | 45.00 |
| \star | Reuhl Race Car | 24.95 |
| * | Thimble Drone Racer | 3.95 |
| \star | Marlin Boat | 8.50 |
| \star | Reuhl Bakelite Hydro | 15.00 |
| \star | Formacraft | 12.50 |
| \star | Jr. Whirlwind | 2.95 |
| \star | Zing | 4.95 |
| \star | Modelcraft Bi-Line | 4.50 |
| \star | Cleveland Streamliner | 4.00 |

FREE A coil and condenser with each gas engine. A 176 page book on model engines with each order of \$5.00 or more.

HOW TO ORDER

It's simple—because you don't pay for packing, postage or any other "charges." Just write down what you want and the price and send a money order or check, or send only \$1.00 and we ship C.O.D. for balance. It's easy! It's quick! Minimum order...\$1.00. Write Dept. M.

GOTHAM HOBBY CO.

107 E. 126th Street New York 35, N. Y.

Airways

(Continued from page 31)

continue control line flying through the winter, whereas in previous years they practically went into hibernation when cold weather set in.

In addition to a regular job, Joe is Publicity Chairman for *The Sky Blazers*, and on the side writes a regular model plane column each Sunday in the Atlantic City Press. Although these columns are usually devoted to a discussion of various model types, a recent one was made up of excerpts from letters received from foreign modelers—Joe made contact with these new acquaintances through names published in the *News of Modelers* department of MODEL ATRPLANE NEWS.

LOST OR DAMAGED ENGINES are not a great worry to members of the Galesburg Model Airplane Club of Illinois. Secy. Kenneth Freese noted the suggestion on this subject in "Air Ways" of Jan. 1948 M.A.N. but feels his club has this difficulty well in hand. Voluntary contributions from members are put in a fund used solely to reimburse members for losses. Of course there are a few strings attached to this form of "insur-. Free flight ships must have reliable ance' dethermalizers, and witnesses must certify that the equipment worked if a ship is lost; if so certified the owner gets half the price of a new motor. Should a lost ship be returned, the money collected is returned to the fund, or the modeler can put his replacement motor up for auction and retain any amount of money greater than he received from the fund.

In the event of motor damage to a control line ship, a board of club officers checks on the amount of damage and the owner is awarded the sum they decide upon to half the value of the engine. Needless to say, only those members who contribute to the fund are eligible for any of these benefits.

This progressive club has a low cost insurance coverage giving full protection in case of injury, death or property damage. Because of stress on safe flying they have never had occasion to make a claim.

Freese and Ray Johansen have over 250 Kodachrome slides taken of club activities; the slides are very popular at banquets, parties and are loaned to other nearby clubs.

Aside from feverish activity readying ships for flying under the new rules, the chief ambition of the Galesburg group is to form an association of model clubs in Western Illinois and Eastern Iowa for the purpose of coordinating contest and other model activities. They hope to hear from other clubs south to Quincy and Decatur, Ill.; west to Ottumwa, Iowa; north to Rockford, Ill.; and east to Bloomington. They will be pleased to coordinate ideas from the 30 or so other model plane groups within this area.

Picture No. 1 is a model Convair 240 built by Frank P. Hernandez Jr. (2120 Burroghs St., San Diego, Calif.). The model has 50" wingspan, weighs 4 lbs. 14 oz. and is powered with two Madewell 49's. The interior is completely furnished with seats, rugs, hostess room, radio room, galley, lavatory and baggage compartment. There are lights in the cabin, wingtips, tail and nose. To complete this fully equipped plane, Mr. Hernandez has even included a shock absorbing landing gear and a retracting stairway for entrance and exit of passengers. It took 485 hrs. to build at a cost of \$75.

Brian Fairey (110 Widney Road, Bentley Heath, Knowle, N. Birmingham, England) contributed No. 2. The three men in this photo are shown at the first Midland Rally at Warsaw Aerodrome last June. Mr. Fairey is holding a *Trojan* powered *Cavir*; Brian Eccles and Martin Ollis with a *Lepricorn* sailplane of the latter's own design. All are members of the *Dorridge Model Aeroclub*.

Oldtime plane fans should be interested in No. 3 submitted by Joe F. Park (830 N. 3 Ave., Tucson, Ariz.). This well posed model of the ancient *Bleriot Monoplane* is not only extremely realistic but it is a reasonably good flier as well. Close examination will show a rubber hook at the rear end of the fuselage. Mr. Park has had many nice flights from this ancient looking ship.

John E. Burkam (820 Wayne Ave., Dayton, Ohio) contributed the gas powered model helicopter, No. 4. This model was constructed as the basis of Mr. Burkam's thesis for a master's degree at the University of Cincinnati. He is trying to solve the problem of inherent stability for the model in hopes that the solution can be applied to full scale helicopters. The model has a rotor diameter of 7 ft. and is powered by a pre-war Forster Super 99 with throttle. Gross weight is 7.8 lbs. and maximum lift of the main rotor is 12-1/2 lbs. Bolted on the engine crankshaft is a centrifugal blower which cools the engine, acts as a flywheel, and gives a convenient method of starting the engine by means of a leather thong. The drive shaft from nose to tail runs at half engine speed, as does the tail rotor. Main rotor revolves 1/4 as fast as the drive shaft. All shafts are carried in ball bearings. A ratchet in the main rotor hub provides for free wheeling and auto-rotation if the engine stops before the model reaches the ground. The main rotor hub consists essentially of two adjustable pins on which the blades are hinged with the axis of the pin at a 45° angle to the blade's longitudinal axis. When the blades rise, as they do if the engine is stopped in flight, the blade angle decreases, making auto-rotation possible.

Four flights have been made close to the ground under the restraint of strings. The throttle was linked to a small reversible electric motor and fine wires strung from helicopter to operator, who could thus open or close the throttle any amount by working a double-pole-double throw switch.

another by working a double-pole-double throw switch. No. 5 is a *Republic Seabee* built by Robert C. Mikesh (306 Oakwood Ave., Ottumwa, Iowa) from a 3 View drawing in MODEL AIRPLANE NEWS. The model is made from white pine to a scale of 3/4'' =1'. Being hollow it has a molded plexiglas enclosure which was formed in the oven; it also has a retractable landing gear. Ribbing along the wings and tail are made from string doped to the surfaces. A local dealer purchased Mr. Mikesh's *Seabee* for demonstration purposes.

John M. Olson $(302-1/2 \text{ W} \cdot 3 \text{ St.}, \text{ Hast$ $ings, Minn.})$ sent in No. 6 which is a *Cub Coupe*. He claims this is a sturdy little ship, having been cartwheeled across a quarter block of stubble field one windy day without receiving any damage. It is powered by a Dieselized *Arden* .099, weighs 10 oz. and is red with gray numerals. Mr. Olson's ambition is to eventually install Radio Control in the ship.

The Siemens-Schuckert D4 shown in No. 7 is another WW I job for enthusiasts of that aviation era. Dan Weinberg (2035 72d St., Brooklyn 4, N.Y.) carved the body from block balsa with built up wings. He incorporated regular ignition when the plane was first built, but re-cently has been using glo-plug ignition. Coloring of the ship is a green body with red and white checkerboard wings. Mr. Weinberg says she flies like a bird on 35 ft. lines and he has complete control of it from takeoff till landing; he now has made over 100 flights. W. Van Rensburg (P. O. Goedgegun,

W. Van Rensburg (P. O. Goedgegell, Swaziland, So. Africa) submitted No. 8 which was built from Dick Clarke's Whippersnapper published in Jan. 1945 M.A.N. Mr. Rensburg's daughter, Jacqueline, seems to be an enthusiastic observer. The plane is all balsa with a very high gloss finish.

The jet powered U controlled plane viewed in No. 9 was sent in by Lawrence Gostomski (Rte. 1, Thorp, Wisc.). The plane is all wood and was built to test Mr. Gostomski's cooling system which he developed—he found it worked quite

well. The plane is a very good performer. Thomas Gabriel (193-07 Linden Blvd. St. Albans 12, N.Y.C.) contributed No. 10, a modified version of the Jabberwock. Powered by 12 strands of T56 rubber it

has made several flights of long duration. No. 11 is a Korda Wakefield winner constructed by Alfred Walsky (Box 30, Morris Plains, N.J.). Span is 44" and weight 9 or weight 9 oz.

No. 12 was submitted by G. van der Linden (The Hague, Regentesselaan 73, Holland). The model is named Ria and has made many good flights in several contests. The span is 8' 4".

NEWS OF MODELERS

J. T. Polding (2 Samuel Sq., Gawker Rd, Barnsley, Yorks, Eng.) would like an American pen pal about 16 yrs. old who is interested in free flight gas jobs, rubber

models and gliders. D. W. Evans (1 Oxford St., Weston—S— Mare, Somerset, Eng.) is anxious to ex-change engines with an American modeler.

Jim Inkester (216 Wallasey Rd., Wallasey, Cheshire, Eng.) would like to correspond, exchange plans, etc., with any chap 19-20 yrs. old who is interested chiefly in free flight power jobs. He is chiefly in free flight power jobs. He is particularly eager to obtain plans of the Jersey Javelin which he is unable to get in his country. If successful he intends to power it with a 2cc Majesco Diesel, which is a fairly large Class A job with very good performance when turning over a 12" prop. Capt. H. M. Bourgeois (VMF-323, MAG-33, MCAS El Toro, Santa Ana, Calif.) is interested in contacting a model buildor in England He would like to ex-

builder in England. He would like to exchange letters, magazines and model equipment. Capt. Bourgeois, 27 yrs. old, has been building models of all types since 1929 but he is particularly interested in gas, control and free flight. His present occupation is fighter pilot in the U.S. Marines. He is also interested in model race cars.

William R. Sinclair (828 W. "E" St., Willmington, Calif.) would like to trade three view plans of World War I aircraft

with anyone interested in this subject. P. R. Darrington (14 Rowland Road, Barnsley, Yorks, Eng.) wishes to corre-spond with an American modeller about 17 yrs. old. He is primarily interested in free flight power, rubber, and glider— "anything but control line.

C. J. Burger (Borneostraat 13, Haarlem, Holland) is unable to buy a small model engine in his country and would like to contact an American who would be in-terested in helping him obtain one.

John W. Stafford (5a Goldsmith St., MODEL AIRPLANE NEWS . April, 1948

NOW MORE THAN EVER BARGAIN IN QUALITY **RSTER** "29"

HIGH PERFORMANCE



Write us for literature showing comparative power curves of actual power developed with spark plug and glow-plug ignition, using gasoline, alcohol and glow-plug fuel.

NEW LOW PRICE!

THE SAME BALL BEARING ENGINE! THE SAME HIGH OUALITY! THE SAME SPEED AND POWER! Everything is the same except the **NEW LOW PRICE!**

Here you get a quality "double-duty" engine complete with metal fuel tank and timer for spark ignition operation, which, however, operates equally well with the new glow-plug. Nothing but a change of plugs is necessary to give you top performance in both fields.

See it at your dealer's!

FORSTER BROTHERS ONLY \$1485 LESS C.&C. 3539 N. Kenton Ave., Chicago 41, 111. Look what 50c buys in beautiful Modelcraft kits RECORD WRECKER again available! again available! Consecutive flights of 54 and 49 min. A Mod-elcraft sensation that was destroyed in the fire which wrecked our plant in 1945 now brought out again by oppular demand. 26" wingspan. All wood full length—no splicing. Hand-select-ed balsa with new-type special covering pa-per, super-light, water shrinks drum tight. 50¢ LESS LIQUIDS. KAYDET Only 5 joints to glue, 25 to 30 min. assembly and you have this all-balsa die-cut stick model in the air. Slotted the air. cabane. Grooved 15¢ SENORITA Sweet as her name top. plus 5c postage

PACIFIC ACE

(The Master) .

glider in zu is a. Balsa, semi-finished. 15¢ IF DEALER CANNOT SUPPLY. ORDER DIRECT



GREMLIN

You can easily build this sweet little 15" glider in 20 to 30 min.

build

plus 5c postant

43

plus 15c



Mansfield, Nottinghamshire, Eng.) is interested in corresponding with an American boy. His interests are in all kinds of modelling, from solids to rubber models, gliders, control line and free flight power iobs.

CLUB NEWS

California

Fresno Gas Model Airplane Club held their monthly free flight contest Nov. 30

and reported the following winners: Class A = 1, Tommy Jenkins; 2, John Marshall; 3, Lt. R. Randolph. Class B = 1, Dutch Van Tassell; 2, John Lender-man; 3, Lt. R. Randolph. Class C = 1, Dean Hughes; 2, Jack Crose; 3, Fred Mosier

Mosier. Juniors -1, Fred Mosier; 2, Russ James; 3, Ron-ald Mosier. ak ak

The Oakland Cloud Dusters elected the following officers for 1948: Michael G. Demos, Pres.; Sergius Milisich, Vice Pres.; Myrtle Robbers, Secy-Treas.; Manuel Andrade, Sgt.-At-Arms.

California Association of Model Clubs elected the following officers for 1948: Vernon Oldershaw, Pres.; Ocie Randall, Vice Pres.; Roy Mayes, Secy-Treas.; Bill Sweet, Corr. Secy. Meetings will be held quarterly, a minimum of four a year. *

The Fresno Control Flyers is a new U-Control Club, organized July 1947, spon-sored by the Junior Chamber of Com-merce. The club consists of 33 active merce. The club consists of 33 active members, meets twice monthly, and clected the following officers for 1948: Roy Bitters, Pres.; Bob Frity, Vice-Pres.; Eldon Webster Sr., Treas.; Bill Price, Secy.; Paul Nieto, Contest Direc. An an-nual contest will be held June 13 unless it conflicts with some other meior context it conflicts with some other major contest.

Results of the Airmail contest between Oakland Cloud Dusters and Australian Eastern Suburban Model Airplane Club:

| Oakland Cloud Di | isters . | 6 Highest Flights |
|------------------|----------|---------------------|
| James Tangney | 14:52.0 | "C & "D" H.L. Cabin |
| Peter Demos | 8:30.5 | D' H.L. Fuselage |
| Manuel Andrade | 8:12.4 | "D" H.L. Fuselage |
| Myrtle Robbers | 8 07.2 | "D H.L. Stick |
| Larry Mongeon | 7:38.6 | "C" H.L. Stick |
| Michael Demos | 6:13.5 | "D" H.L. Stick |
| Eastern Suburban | Model | 3 Highest Flights |

Airplane Club J. M. Fullarton 10:11.2 A. Lim Joon 9:42.2 R. Ingleinger 4:43.2 Wakefield Type H.L. Stick "Atom Smasher" design

Here are results of the Cloud Dusters'

Indoor Helicopter Challenge Round Contest held Jan. 4, 1948:

Donald Robbers, 2:25.6: Michael Demos, 2:15.2: James Tangney, 1:05.7; Robert Blau, 0:38.3; Carl Rambo, 0:05.4.

Results of the Outdoor Hydro Challenge Round Contest, Jan. 11:

Class C-Row Stick-1, Donald Robbers; 2, Carl Class C—Rew Stick—1, Donaid Robbers Rambo, Class C—Rew Cabin-James Tangney, Class D—Rew Stick—Michael Demos, Class D—Rew Cabin—Manuel Andrade,

* *

On Dec. 5 the Thermal Thumbers Model Airplane Club celebrated their first anni-Airplane Club celebrated their first anni-versary. Clarence Searcy, Contest Direc-tor, held a party for 32 members, with wives and sweethearts to add to the glamour of the affair.

Colorado

R. J. Beckman, Secy. of Rocky Moun-tain Canaries of Boulder, recently wrote the following enthusiastic letter: "Since I last wrote you the RMC has been very active. In addition to taking a good twothirds of all prizes offered at the contests in the region, we held a meet of our own on 24 August 1947. We are justly proud of this contest as we didn't have one complaint the whole day and we had an ex-ceptional number of contestants. It went so smoothly that we were able to complete the judging and award the prizes with time to spare. We are already planning a bigger and better meet for next summer.

"As soon as the contest was over, the RMC organized and are conducting a class in model aeronautics designed primarily for younger boys and girls. At present the training program is in the form of a series of classes in which students are guided in the construction and flying of a control line model. For this purpose, the F and B Model Aircraft Co. supplied us with 6 of their Sky Box Trainer kits. The American Legion Post #10 of Boulder is supplying engines and accessories for the planes. (Post #10 is sponsoring the RMC and too much cannot be said for the help they have given us.) Until a short time ago the RMC has been primarily a control line club, but the past two months has seen a rising interest in free flight that has almost pushed control line out of The picture. We have scheduled our first club izee flight contest for Feb. 15 and are planning an open free flight contest next summer along with our control line meet. I for one am convinced that the *RMC* will outdo the rest of the region in free flight as well as in control line. As you can see, ours is the top club in the region and we intend to stay on top.

Your Club News reporter likes the spirit and determination of this outfit and feels they are going to give other clubs a "boulderful" of competition.

Florida

Gene Johnson, pres. of Clearwater Model Airplane Club reported that speed, crackups and stunts highlighted a windy session at the city parking lot on North Osceola Ave, where 100 spectators turned out to watch the contest. Everyone got a big thrill when a biplane owned by Dick Shewell won the stunt feature. Almost immediately after the ship took off it lost its top wing. In spite of the damage the little plane held the air, went through some outstanding maneuvers and finished with a perfect landing. Because of the high erratic wind, spectators were treated to 5 or 6 crackups out of the 30 entries handled by the local boys. Prizes for the event, consisting of sports items, were sponsored by Walker's Sporting Shop. Other winners were:

Speed Class A--Ned Anderson, Speed--Class B---Gene Johnson, Speed--Class C--Charlie Clark, Scale Prize---Lloyd Hicks,

Illinois

The Tri-City Modelers of LaSalle, Peru & Oglesby elected the following officers for 1948: Ray Broviak, Pres.; Joe Locasto, Vice-Pres.; Bob Davidson, Secy.-Treas. The club will hold its annual U-control meet in July, exact date to be announced later.

Chicago Flying Gremlins U-control gas model airplane club was recently reorganized. The new officers are: Bob Twining Jr., Pres.; George Chirigos Jr., Secy.; John Anderson, Treas. For the past few months the club has been flying at Winnemac Park, 2200 W. Winnemac Ave., on Sundays.

Indiana

Glenna Williamson, Secy. of Anderson Johnnies, sent us a comprehensive letter on the activities of this club. Unfortunately we do not have enough space to present everything the secy. wrote us but we feel that several things deserve mention here. At a dinner-meeting Dec. 12 the club instigated the organization of a State of Indiana Assoc. whose purpose would be:





.290 Disp. — 1/5 H.P.

Precision engineered for casy starting. Beyond question the greatest motor value in years! Hardened and ground steel piston, micro honed and hand lapped for high turbulance—high compression. Brings you expensive engine features at a popular price. Ask your dealer to show you this great new motor.

Less Coil and Condenser



Add \$1.50 if wanted with Coil and Condenser

Order from your dealer. If he cannot supply, write direct.

| PIERCI | EINDU | STRIES |
|--|---------------------|---|
| OHI W. ADAMS SI | | CHICAGO 7, HL. |
| PIERCE INDUSTRIES, CHICAGO 7, ILL. | 844 W. ADAMS | SET THIS HANDY COUPON ST., Bept. MN4 |
| Please add | 25c to cover postag | e and packing. |
| Model R @ \$6.95. Add \$1.50 for coil and condenser. | NAME | |
| Model J @ \$4.95. Add \$1.50 for coil and condenser. | CITY | STATE |



STUNT FLYING IS EASY

LEARN with the ADVANCED TRAINER. It has everything a good stunt ship should have and it's reasonably priced.





GREAT LAKES MODELS 1125 Brown Ave., Erie, Pa.

1. To establish an efficient model airplane contest calendar the year around. 2. Pooling of contest personnel and

equipment. 3. Aid clubs in building up their membership.

4. Encourage more youth participation. 5. Facilitate closer cooperation with organizations, such as, The American Le-gion, Civil Air Patrol, and Air Defense Command in their model airplane pro-grams. Mr. Frank Nekimken. American Legion National Headquarters, Indianapolis, who was present at this celebration, offered his services to the Association. Also at this banquet, the annual achievement awards were presented to: Harry Murphy Jr., winner of the Junior Division Award, and Harold Tremps, winner of the Senior Award. Competition was pretty close this year with 14 year old Luther Marr Hays running a close second in the Junior Division, trailing by only 15 points. Mr. Tremps was ahead of second place Luther Hays (father of the younger) by 92 points. These points are awarded for construction, attendance, placing in contests, and provision is made for extra points for any outstanding achievement. Officers of the Anderson Johnnies for 1948 are: Robert Johnson, Pres: William J. Campbell, Vice-Pres., John Hobbs, Treas., Glenna Williamson, Secv.

The Hoosier Capitoliners' third year of existence was officially opened by Wilbur T. Portteus Sr., last Jan. 7. Appointments of committees and boards took up the bigger part of the meeting, Geo. Clingman, Geo. Reed and Frank Nekimken are on the Advisory Board, Jim Mitchell on entertainment, Bill Pazder on Membership Board, and Geo. Reed and Frank Nekimken on the Education Board, Geo. Reed of Display Craft Studio has turned the shop over to the boys every Tuesday night for 25c per person. The shop is complete with power tools, spray booth, projector for enlarging plans, work tables, engine testing etc. The *Capitoliners* are setting their goal at 100 members this year. If you are interested and live near Indianaplis, contact B. A. Stellhorn by phone at Franklin 7942 or by mail c/o Hoosier Capitoliners, 710 S. New Jersey, Indianapolis.

The Purdue Aeromodellers, model club at Purdue University, has a large workshop in the basement of the Purdue Memorial Union Bldg. and at present are doing most of their winter flying at the Purdue Armory on Saturday afternoons. The club is negotiating with the Uni-





versity for a plot of ground for a permanent flying site and hopes to have it in operation by spring. AMA U-Control record trials will be held in April and May, and a U-Control contest the end of May. The club is mostly control line, with a few exclusively free flight, and some who build both.

lowa

One of the largest model airplane contests in the nation — The Tall Corn Model Airplane Meet, held annually at Marshalltown — will be sponsored this summer by the Iowa Civil Air Patrol. This announcement was made simultaneously by Wallace R. Blake of Marshalltown, originator and director of the Meet, and Lt. Col. W. O. Fuller, Deputy Commander of the Iowa Wing, CAP.

At the same time, Colonel Fuller revealed the Iowa CAP has made a bid for the regular District CAP Model Contest, which draws entries from all the

46



north central states. If accepted, the two contests would be combined into one of the largest exhibitions of model airplane activity ever held. Arrangements are being made with the Taylorcraft Corp. Alliance, Ohio for awarding a new 65 hp \$2300 Taylorcraft airplane as grand prize for the 10th Jubilee Tallcorn Model Meet. The Fort Des Moines Army Post is being considered as site of the Jubilee Meet which is scheduled for July 3-5.

Kansas

Some 50 model airplane enthusiasts representing 60 model clubs met at the Hotel Continental in Kansas City, Mo. on Jan. 3-4 for the 3rd Annual Meeting of the Mid States Model Aeronautical Assoc. High point of the meeting probably was the announcement that Mid-SMAA President C. O. Wright was elected A.M.A. President C. O. Wright was elected A.M.A. President Also many new proposals for the Precision Stunt, Novelty Stunt and Flying scale were recommended.

Maine

A gas model club called The Flying Maniacs was recently organized in Augusta. All 14 members belong to the A.M.A. The following are newly elected officers: Howard E. Smith, Pres.; Raymond Vigue, Secy.; Richard Main, Treas.; Louis Marden, Publicity man. Plans for a few contests under A.M.A. rules are already underway. Those interested in this new club should contact Secy. Raymond Vigue 143 Northern Ave., Augusta. In answer to a question that Mr. Smith sent in, we wish to inform everyone that all club news should be sent to the same address as MODEL AIRPLANE NEWS, namely: 551 5th Ave., N.Y., 17, N.Y., attention of Club News Dept. Maryland

Aero Craftsmen Gas Model Club of Baltimore elected the following officers for 1948: John Gunther, Pres.; Charles Peacock, Vice Pres.; Larry Simms, Senior Advisor; Pete Truman, Treas.; Yvonne Gunther, Secy.; Max Ripken, Bob Stevens and Bucky Verrier, Board of Directors; Leonard Watson, Publicity Direc. Bucky Verrier informs us that the club has quite a vigorous program planned for the coming year which includes bus trips, a design contest and some social affairs.

Massachusets

It is requested that all correspondence to the Lawrence Gas Model Club be mailed in care of Edmund Chulada, 164 Park St., Lawrence, and not to John O'Rourke, Bay State Bldg.

* *

Henry R. Jex, Pres. of a newly formed model airplane club at Massachusetts Institute of Technology, called The Tech Model Aircrafters, writes us that the club has been officially recognized as a regular Institute activity and were given a room in the electronic lab for their workshop and clubroom. An interesting feature of this club is its research program. Members work on a project of their own choosing, some of which are: Power effects of gas models; Rubber-turn chart; Vee-tails; Effect of Stabilizer Area; H-L Glider Construction; Channel-Wing design; and Compression-Ignition. Recently the club obtained use of a nearby armory for a Saturday afternoon and held an indoor contest. A U-control stunt contest was also planned. The club reports that some developments they have been working on are progressing well, such as Mite



POWER YOUR MODEL RACER

\$1.95

With any Class A engine the Challenger Differential and Fly Wheel U-Jaint Combination make a perfect power haokup for Thimbledrome Racing Cars. Also adaptable to other model racers.

Differential is precision machined from Dural with case hardened steel gears and naval bronze bearings. Housing is $1.1/2^{\pi}$ in diameter, axle 6 $1/8^{\pi}$ long, drive shaft 1 $3/4^{\pi}$ long.



At Your Hobby Shap or Sold Direct Plus Postage



LUCAS & SMITH MANUFACTURING CO. 2636 HUMBOLT ST. • LOS ANGELES 33

with glow-plugs and Atoms with Arden needle valve conversion. Mr. Jex states that cooperation among the members is wonderful and he predicts his group will be well known in a few years. Your club news reporter can only add that with this kind of a beginning — the sky's the limit!

Minnestota

Roger C. Sorensen, Corr. Secy. of Piston Pushers Club, is proud of the accomplishments of his club and believes some of these things are worthy of mention in this column. The Piston Pushers have managed to take the lion's share of honors at upper mid-west contests. Winnings for 1947 consisted of 17 trophies, plus 15 first, 14 second and 12 third places, along with many contest grand champions. Dan Philippbar, retiring Pres. of the club, deserves especial credit for the fine work he has done in office by putting the club back on its feet. Mr. Sorensen writes that the club especially likes M.A.N.'s "West Coast Tips" column and would appreciate hearing from fliers and clubs out there due to the fact that fliers in this area are usually behind the westcoast designs.

New Jersey

The former Passaic Rubber Heels group is now the Passaic Model Club. M. Bakels, Rec. Secy. reports that the change was voted Dec. 11. The club has outgrown its former title, and since it embraces model aircraft in all its phases, plus model boat and race car building, the members feel the new title is more truly descriptive. The club, now chartered by AMA, chose the following officers: A. Casano, Senior Advisor; H. Rublack, Pres.; B. Spille, Vice-Pres.; M. Bakels, Recording Secy., and W. Deetz, Treas. The club is negotiating for purchase of sufficient land for its own free flight and U-control requirements. The members would welcome correspondence with other clubs. Address all letters to: M. Bakels, 102 Main Ave., Passaic, N. J.

New York

The Queens Thermal Thumbers will hold their 3d Annual Model Airplane Contest, sanctioned by AMA, on July 11—rain date July 18—at Beth Page, L. I. Events will be: Classes A, B, C & D free flight gas, combined towline & combined rubber (fus. & stick). The contest starts at 8:30 a.m. and ends 5:30 p.m. Directions to the field are: take Route 24 east on Long Island until it crosses Wantugh Parkway; then continue 1 mile and the field is on the right hand side.

* *

14 model clubs comprise the parent organization known as North Eastern Model Airplane Conference which came into existence when several of the leading clubs decided to do something about combining the area to obtain a possible free flight field. Cooperation among these 14 clubs was so good they decided to organize. The following are the newly elected officers: Sidney November, New York Aeronuts — Chairman; Bernard Litchterman, Brooklyn Skyscrapers — Vice Chairman; Arnold Penenberg, Brooklyn Skyscraper, — Rec. Secy.; Salvatore Fruciano, New York Aeronuts — Corres. Secy.; William Fletcher, Prop-Spinners — Treas.

Last October the New York Aeronuts ended a highly successful contest season. The club gained most of its honors in free flight gas events, particularly in Class C. Flying McCoy and Hornet ships, Kenny Fisher and Sid November took





HERE IT IS!...

A Thrill For Model Builders

Converts Any Model Gas Engine Into A Jet Engine! Build It Yourself. Complete Set of Plans Only \$1.75 Postpaid. Order Today!

MODEL EXPERIMENTAL LAB. P. O. Box 186 West End Station Colorado Springs, Colo.



PITTSBURGH'S WHOLESALE DISTRIBUTOR... VAII leading lines MODEL AIRPLANES MODEL BOATS MODEL SUPPLIES FULL LINE OF MOTORS Dealer's Price List Available Upon Request WHOLESALE ONLY J. SPOKANE & CO., Inc. 1106 Fifth Avenue, Pittsburgh 19, Penna.

top honors. Pete Andrews won in indoor flying, annexing the Bloomingdale Trophy at the Nationals.

North Dakota

Frank McKenzie, 518 9th St. S., 18 yr. old Fargo High School student, won the grand prize - a jet motor - in the 2d model airplane display contest of the Fargo-Moorhead CAP squadron in Fes-tival hall, NDAC which drew a crowd of nearly 200 persons. McKenzie's model of a Grumman *Bearcat* fighter was judged the best of 29 entries; it also took first place in the gas engine model class for which his prize was a ride in the CAP's AT-6 army plane. Dr. M. L. Red-man and Lt. Karl Ording, CAP, were judges. William Dubnenke of Bismarck was awarded a plane ride for entering the largest model; Gary Kurowski, 1120 7th St. N. won a subscription to a model magazine for entering the smallest plane; and Ronald Rogers, 13, of 1637 9th Ave. S. won a motor for being the youngest S. won a motor for being the youngest contestant. Other contest winners were: Gas Models—1, William Dubnenke: 2, Jerry Spies. Rubber—1, Phil Benedict; 2, Dalton Brightbill;
3, Dale Larson. Solid—1, Gary Kurowski; 2, Barbara Loomis. Gilder—1, Gary Kurowski; 2, Gary Kurowski;
3, Barbara Loomis. Scale—1, Barbara Loomis; 2, Gary Kurowski;

Scale-1, Ba 3, Dale Larson.

Ohio

The Junior Aviator Indoor Air Meet, sponsored by The CLEVELAND Press and the Air Force Association was held at Central Armory in Cleveland Jan. 3. The armory is 72 ft. from floor to ceiling and the meet, largest ever held there, drew 150 contestants, each with three or more models. It was directed by Leo Dixon, chairman of the Council of Model Aeronautics, and assisted by: AFA members headed by Commander Erwin Cooper, Junior Chamber of Commerce Aviation Committee members headed by Dick Hanson, and representatives of Women's Chapter NAA, Arlene Davis Flying Club and Wing Scouts. Trophy winners received their awards during a WEWS television show Saturday night. Here are the prize winners:

Beginners

Glider Event-1, Sylvia Lanzo; 2, Robert Hart; 3, John Fox. Stick Event-1, Sylvia Lanzo; 2, John Fox; 3, Bob Gregorek

Event-1. Ray Vargo; 2, Spud Kohler; Glider

Glider Event-1, Ray Vargo; 2, Spud Kohler; 3, John Humphreys. Stick Event-1. Harvey Mace: 2, John Humph-reys: 3, John Ward. Fuselage Event-1. John Humphreys; 2 John Ward; 3, Spud Kohler. Glider Event-1. Gene Kemmerline; 2, Jerry Gregorek: 3, Paul White. Stick Event-1, Lawrence Weimer: 2. Gene Kem-merline; 3, William Steele. Fuselage Event-1. John Drobat; 2, Robert Mad-sen; 3, Franklin Schultz. *Open*

Open Glider Event—1, Richard Fox; 2, Richard Korda:

Ginder Lvent-1, Richard Fox; 2, Richard Korda;
3, Donald Springer.
Stick Event-1, Chester Lanzo; 2, Richard Fox;
3, John Russell.
Fuselage Event-1, Richard Fox; 2, George Vasenko; 3 Chester Lanzo.

Oregon

Corres. Secy. Roger D. Smith recently informed us of the formation of a new all control line club in Portland called the Fireballs. Jim Walker and the American Junior Aircraft Corp. offered their services as sponsors and also consented to let the club use their present name. The first meeting was held Jan. 5 and the following officers were elected: Binger Sefton, Pres.; Harvey Jensen, Vice-Pres.; Connie Stuhr, Secy.-Treas.; R. D. Smith, Corres. Secy.; Harry Fosbury, Contest Direc. Committees were named for contests, membership and publicity.

MODEL AIRPLANE NEWS . April, 1948



49



Gotham proudly presents the world's sweetest and hottest little diesel engine—the DEEZIL "A." We put a solid year of design and development into this engine to give you a diesel that has everything—and now, quantity production gives you in addition the lowest possible price. The DEEZIL is the perfect power plant for planes, boats and race cars. Its compact streamlined shape lends itself to easy installation and perfect cowling. Easy starting and steady running give you 100% flying time. Operation is simple and economical. The DEEZIL is light enough for the tiny jobs yet powerful enough for the tiny jobs yet powerful enough to pull a six foot free-flighter straight up. And it will run for years and years without attention because it is simple and rugged. Order a DEEZIL today for the thrill of a lifetime.

- ★ DEEZIL STARTS EASILY
- ★ DEEZIL IS RUGGED
- ★ DEEZIL RUNS STEADILY
- ★ DEEZIL IS POWERFUL
- ★ DEEZIL IS LOW PRICED
- ★ DEEZIL IS GUARANTEED

GET your DEEZIL from your favorite hobby shop, or if he is sold out, send only \$1.00 to GOTHAM and we'll ship C.O.D. for balance. We pay postage.

DEALERS AND JOBBERS WRITE

GOTHAM HOBBY CO. 107 East 126th St., Dept. M New York 35, N. Y.

١.

Meetings will be held once a month. The club has a solid foundation of experienced modelers and expects to really go places in the coming contest season.

Pennsylvania

With 32 members and 6 visitors in attendance, a meeting of the Doylestown *Kiwanis Aero Club* was held Dec. 29 when the following officers were elected: James Campbell, Pres.; Walter DeSousa, Vice-pres.; D. Warner, Secy.; W. Lownes, Treas.; J. Carlson, Sergeant-at-arms; Ralph Biddle and Walter DeSousa, Federation representatives; John Happ, Chairman; D. Rohde, G. Shaughnessy, J. L. Friling and Ralph Biddle, Directors. It was decided to hold a school of

It was decided to hold a school of aerodynamics to teach all younger members of the club how to build and fly control line as well as free flight models. The school will be conducted by Ralph Biddle of Neshaminy, who is a veteran model builder and official, aided by Frank Horn and John W. Brinser, Jr. Schooling is to be given every Thursday evening. William A. Lehman, sponsor of the club, announced that W. Harry Watson & son, local automobile dealers, contributed space in their South Main St. building to be used as a workshop.

16 County Seat business men are aiding this newly formed workshop by contributing tools, supplies, and other equipment. "I think what these businessmen have done is one of the finest gestures we have been shown since we organized," said President Campbell. "Any businessman is invited to attend and inspect the workshop at any time."

At their Jan. 28th meeting, the Kiwanis Aero Club's guest speaker, Comdr. Richardson, gave a very informative address on the development of military planes. He later visited the new workshop at Watson's Garage and was much impressed with the progress shown.

* *

The Pittsburgh Conference on Model Aeronautics is a new organization established to coordinate the activities and more thoroughly publicize contests in the Pittsburgh area. As a result of the mass meeting of all Pittsburgh modelers on Jan. 10, M. J. Thomas was reelected Conference Coordinator; Joe Mellot, publicity director and Buzz Bullock, Secy.-Treas.

Texas

The first annual West Texas Model Airplane Contest will be staged in Amarillo June 12—13 at a site yet to be chosen. It will be open to entries from the Panhandle, South Plains, Eastern New Mexico and Western Oklahoma. Richard M. Kidwell Jr., owner and manager of The Kidwell Model Shop, is staging the contest and reports it will include all classes in free flight, U-Control, speed races, stunts and exhibition flying. There will be high priced awards in all divisions.

divisions. The Veterans of Foreign Wars of Uvalde is sponsor of the control line Model Airplane Meet Feb. 22. The meet comprised the 3 events: speed, stunt and sportsman. The sportsman event was judged on a point system and the winner adjudged the best model filyer, not necesarily the best model builder. There were no age or engine displacement classifications in this event, the only prerequisite being a fixed gear on the model. Takcoff, landing, and flight stability were the main points judged. Prizes consisted of a magneto, several engines, several stopwatches, etc.

Virginia

Robert M. Bruce, Secy.-Treas. of the

→WEST COAST←

RETAIL

HOBBY SUPPLIERS

WE FEATURE

VIVELL DIESEL at \$12.50 ORWICK ``64'' at \$32.00

We Handle All National Advertised Engines, "U" Control Kits and Accessories, Free Flight and Sailplane Kits.

KIRKS HOBBY HANGAR "U" CONTROL SPECIALIST 2320 ENCINAL AVE., ALAMEDA, CALIFORNIA

A New Low for High

HEY, you, stop a while and visit. We aren't going to hi-pressure you. Modeling is our hobby too. If you don't believe it, you ought to see a copy of our dime catalog. In it you will read our frank opinion of the products we sell. We tell you exactly what you get in the kits and the actual specifications of the models. And to top all of this it also tells stories and incidents about modeling in an informal way. If you want to buy a model you have to look it up in the price index which is a new low for hi-pressure.

OLE RELIABLE MODELS Box 756 Cleveland 22, Ohio

NATIONAL BOYS' CLUB WEEK APRIL 5th TO 11th

The principle of Boys' Clubs is to build good citizens, but in doing so they have demonstrated their effectiveness in lessening delinquency. This is not a theory, but a fact!

26' SCALE MODELS \$4.95 Postpaid Weight of the second seco

50

When OTHER Prices go Down.. K&B Performance GOES UP!! TORPEDO

We will NOT sacrifice QUALITY to

lower our prices

*29"

1850 (less c & c)

Precision engineering, Highest quality material and skilled workmanship have made K&B engines the great champions they are. We will continue to produce quality—not quantity.

K & B MANUFACTURING COMPANY 6901 EASTERN AVENUE · BELL GARDENS, CALIFORNIA

newly organized Torque Twisters Model Airplane Club of Langley Field reports that full credit for organizing the club goes to its President, Sgt. Paul Shaffer, who recruited 20 members. This sounds like a good start for any new club.

к & В "24"

1650

(less cac)

Argentina

J. Cartoceti, Pres. of the Asociacion Aeromodelistas "Tuco Tuco," Buenos Aires, writes that they keep up with airplane publications of other countries and find them very useful from the point of view of reference and design.

England

F. C. Saunders is keeping us up to date with the Batteria Aeromods. The club is situated in the Battersea Men's Institute in S.W. London, and since the club is run in conjunction with the Institute it has a number of advantages over the usual club in that they have no rent or lighting to pay and have a dry canteen, a hall for indoor flying, and a playground for control line flying. All outdoor flying is done on Hounston Heath which is quite close to London Airport; there is a ban on power flying in the London area. The club records are as follows: 62 mph with a Mills Class A Diesel control line; 9 mins. 10 sec. O.O.S. with a 15 sec. motor run in the power class (this was also a diesel engine); 2 min. 10 sec. in the rubber duration class; and 1 min. 53.8 sec. in the indoor R.T.P. class.

The Society of Model Aeronautical Engineers held its annual General Meeting Nov. 30, 1947 at Londonerry House, Park Lane, London W. The following men are newly appointed officers: Lord Brabazon, Pres.; Sir Robert Bird Bt., Vice-Pres.



We are accepting import orders for the famous Schuco (made in Occupied Germany) autos—The Gear Shift "Examico"—The Remote Control "Telesteering"—The Horn blowing and steering "Akoustico"—The Self Starting and Reversing "Garaging" & The "Racer"—



NF?

2. Jerry James — 1st place — Class B

 Don Newberger — 1st place (120 mph) Class 3 Speed-Open — 10/18/47
 Lew Mahieu — 1st place (117.64 mph)

Senior Class 3 Speed-10/18/47

 Ray Acord — Official AMA Record — 32:02.6 mins. Free Flight-open

6. Paul Conrad—Official AMA Record— 98.97 mph—Class 3 Jr. U-Control Speed WATCH THIS GROW

Jr. F. F.- Nationals

Starting and Reversing "Garaging" & The "Racer"— Also the complete fully painted "Britain Line" of Farm figures, Zoo animals & Soldiers of the World—in all gauges—Astounding and revolutionary imports will be added during the year—Get your orders in Noto—These are all year round sellers.





(Continued from page 23)

early aircraft were framed in steel and aluminum.

His early aircraft were sensational in that they flew. His later products were sensational in that they flew better, all factors considered, than those of most of his competitors. The underlying theme of all Breguet designs was a simple beauty and grace coupled with common horse sense, which made his ships extremely useful. They were neither the biggest, fastest nor farthest flying, but they did well the job that was intended for them with a minimum of regrets from the purchaser.

Breguet Model 14

The biggest purchaser when the war started was, of course, the French government. Breguet's first official product was a version of the 1910 biplane adapted for whatever use the French army could find for it. But from his factory at Villacoublay came a pusher biplane in accordance with the style of the time, which performed some good service at the Front and later was used as a school machine until mid 1917. Early in 1916 Breguet brought out a tri-motor bomber (three 250 hp Renault engines) of considerable size, which was able to fly at 6500 meters for three hours while carrying a load of 1200 kilos. Converted to feet and pounds this doesn't seem like much in terms of performance today, but the ship had the French Air Ministry quite excited.

While his tri-motor was pleasing the military authorities, Breguet put the finishing touches on model 14, one of the sweetest ships ever to take to the air. The surest method of identifying a 14B.2 or 14A.2 was to read the designation painted on the rudder. By way of review, the letter A indicated "Corps d'Armee" (army cooperation) while B indicated "Bombardment". The figure "2" indicated number of men in the crew. Besides the rudder designation, these

Besides the rudder designation, these general characteristics often permitted proper identification: 14B.2-window below the gunner's cockpit in each side of the fuselage; airfoil-like extension of the lower wing leading edge between fuselage and inboard interplane struts; automatic full span flap on the lower wing. The 14A.2 generally had none of these identifying characteristics but carried the word "Photo" at the pilot's cockpit on either side.

Because parts of these two designations were interchangeable, some B types had no flaps, some A types did; some A's were converted B's and possessed fuselage windows, and so forth. Balanced and nonbalanced ailerons also were variously fitted to both types. And type A, in accordance with requirements for all other single engined planes in this class, carried fittings for attachment of bomb racks with a capacity of four small bombs.

Construction

Briefly, the Breguet 14 was of mixed wood and metal construction. each material being used where its designer thought it (1) would give the best service, and (2) would be most adaptable to high production methods.

The fuselage was framed principally of aluminum with wood or steel reinforcements as required. Longerons were tubular aluminum. Uprights and crossbraces of the same material were attached by means of welded steel tube sleeves riveted to the components. Steel wire was used to brace the structure. Engine bearers were made of U channeled aluminum supported by aluminum and steel struts. The nose radiator, pierced for the propeller shaft, was attached to the bearers and to special extensions of the lower longerons.

The husky landing gear consisted of three pairs of struts of aluminum tubing drawn to streamline shape, each internally reinforced by a full length of channeled steel riveted in place. Upper end of each strut was attached to the longerons on each side by means of steel stampings. Strut lower ends fastened to right and left horizontal steel members which carried the axle. The landing gear assembly was wire-braced and equipped with rubber cord shock absorbers.

Breguet tailskids were made of ash, covered with aluminum sheet, and sprung from rubber shock cord. Additional shock absorbing was provided by steel icaf springs on the skid tip and a vertical coil spring of the "oleo" type set inside the tubular fuselage sternpost.

The fuselage was covered in front with well louvered removable side and bottom panels. The upper cowl, also removable, covered the top of the engine and was provided with an opening for installation of an overhead exhaust collector. Sheet aluminum served as the top fuselage fairing to the rear of the gunner's cockpit. From there to the tail—both top and bottom—a built up wood and metal fairing, covered with fabric, was provided. The fuselage otherwise was fabric covered.

Engines fitted in the Breguet model 14 varied with the type and are specified in the comparison table accompanying this article.

Two gravity fuel tanks of 130 litres each, located behind the motor, and an 18 litre oil tank mounted on the right side fed the engine. Exact placement of these reservoirs varied slightly in some instances, but the allowable fuel load for any type in the 14 series was 475 lbs. This was sufficient for about 2½ hours full throttle operation at sea level. Each fuel tank was fitted with an individual, electrically operated float type indicator which was actuated by pressing a button on the instrument panel. Electricity for the fuel gages was supplied by a small dry cell battery.

The instrument panel, protected on all new models by a large sheet of framed Triplex safety glass (some pilots removed this glass to save the weight) contained a tachometer, watch, altimeter, compass and water temperature indicator. On the pilot's right were the radiator shutter control lever, starting magneto, engine priming pump, oil and fuel petcocks and cockpit lighting and radio fittings. On his left were the throttle and spark levers, air pump regulator, magneto switch and fuel shut-off valve control.

10

The observer was provided with a seat so hinged that he could sit either high in the fuselage (flying to an objective) or low on the bottom (for bomb aiming in model 12B.2, camera sighting in model 14A.2). The windows in the fuselage sides gave the bomber-observer a view of what was going on outside when he was busy with the mounted bombsight. Bomb release levers were located on the observer's right; to his left were a throttle control and magneto switch. Dual flying controls were fitted, those in the observer's cockpit being removable.

Many Breguet model 14s, both A and B, were equipped for night flying and had position lights fitted to their outer inter-

plane struts. These were controllable from the observer's cockpit along with the radio installation, if any. Power for radio and position lights was supplied by a wind driven dynamo mounted below the fuselage.

Armament on all models included one fixed, synchronized machine gun mounted on the left side of the fuselage and operated by the pilot. The observer's armament was either one or two machine guns-usually the latter-mounted on a tourelle surrounding his cockpit.

Further description of the Breguet model 14 and an analysis of flight surfaces, performance figures and flight characteristics will be presented next month.

| | | _ | | | | | | |
|-------|----------------|-----|---------------|------------------|-----------------|---------------------------|----------------------------|--|
| TYPE | Engine | HP | Span, feet | Area, Sq. ft. | Length, feet | Weight emply pounds | Weight loaded pounds | |
| 14A.2 | Renault 12 FCX | 300 | 47.12 | 560 | 29.58 | 2222 | 3380 | |
| 144.2 | Renault 12 FCY | 310 | 46.00 | 528 | 29.22 | 2222 | 3380 | |
| 14A.2 | FIAT A12. | 285 | 46.00 | 528 | 29.31 | 2288 | 3447 | |
| 14A.2 | FIAT A12 | 275 | 46.00 | 528 | 29.2 | 2200 | 3396 | |
| 14A.2 | Lorraine 12D. | 370 | 47.12 | 560 | 29.58 | 2310 | 3144 | |
| 14A.2 | Renault 12K. | 400 | 46.00 | 528 | 29.2 | 2640 | 4090 | |
| 14B.2 | Renault 12 FCX | 300 | 46.00 | 560 | 29.2 | 2280 | 3880 | |

The Ancient Glow-Plug

(Continued from page 19) of the glo-plug in model airplane engine design is an ingenious application of an old proven device, and where results count it behooves the user to consider the factors which, theoretically at least, should produce the best results.

In its connection with model airplane history the glo-plug has a little to offer, too. 'Way back in 1908 Ray Arden, de-signer of the present type of Arden gloplug, developed and used a glo-plug in a model engine. It seems a long time from 1908 to 1948 but recently the story came out.

A year or two ago Ed Chamberlain came up with a novel approach to the same problem. He developed a fuel called Liquid Dynamite. which in effect turns the sparkplug into a glo-plug. This special fuel is used in the conventional manner, aided by the regular ignition system for starting purposes; but after the en-gine reaches a good heat the sparkplug points come to a glow, and the ignition system may be disconnected. Moving the timer arm then has no affect on engine operation,

For two years, Art Hasselbach has been experimenting with sparkplugs (Fig. 1) converted to glo-plugs for use with this Liquid Dynamite. The H & H enginewhich was developed just before the war and has been on sale for the past 18 months—is the first commercially-produced engine designed for use with the glo-plug.

The model airplanc engine in its two cycle form is accepted as the best for its purpose because of its simplicity and lightness. Few moving parts give it both of these desirable qualities. Because of the rapid firing action of the two cycle engine, any slight disarrangement of the ignition system causes it to fail. But failure will also result from any other dislocation. Therefore, by merely inserting a glo-plug one may or may not get good results. The supporting factors such as: type of fuel, fuel-air mixture, correct compression ratio, proper port timing, and precise mechanical fits, are vital to good operation. Removal of waste products, or



The National Stunt Champion

All Atwood Engines are Fully Tested and Fully Guaranteed ATWOOD MANUFACTURING CO., 147 Pasadena Ave., So. Pasadena, Calif.



exhaust, must also be taken into account. Since the manufacturers provide the features for proper operation of their engines, and recommend fuels, mixtures and handling procedures, the engine user himself must check the unknown factors when attempting glo-plug adaptation. The manufacturers who sell engines equipped with a glo-plug can do so because they have found the best combination of fuel, compression ratio, and construction for their particular products. However, all engines may be adapted for glo-plug use.

Fuel is a delicate matter and it is usually found that where a certain fuel is prescribed that fuel will give good results. When a strange fuel is used the results may very well be poor running or com-plete failure. This may not be the fault of the fuel itself. No two fuel-air mixtures have the same combustion point. The combustion point is that degree of temperature at which the mixture will ignite. In an engine utilizing the glo-plug, this combustion point may be regulated somewhat. The range of regulation possible depends on the allowances left in the engine to change the compression ratio, since the latter (explained below) is the factor which determines the heat of the mixture as it goes into its preparatory stages before ignition and combustion.

In a diesel where there is no ignition aid such as a glo-plug, all the heat necessary for ignition and combustion is generated by compression alone. Forcing a quantity of fuel and air into a greatly decreased area will cause the compressed vapor to generate heat. This system of utilizing only the heat of high compression for ignition gives rise to the term compression ignition engine. In a spark ignition engine, where a timed electrical spark sets off the fuel charge, high compression ratios are not of primary importance because the spark does this job.

The glo-plug, since it does not give a timed spark, makes use of the compression ratio as a primary heat source obvious. As stated above, no two fuel-air mixtures have the same combustion point, and neither is it certain that two engines with the same compression ratio will be alike. The heat generated depends on heat losses through the walls of the engine and possible leakage through ports or poor fitting of parts.

A spark ignition engine operates in the range of compression ratios between 7 and 10 to 1, while the compression ignition engine utilizes ratios of between 12 and 22 to 1. By addition of a glo-plug we find that the compression ratios need be less than those last mentioned. To emphasize, those engines which are manufactured for use with a glo-plug take all these points into consideration; the proper compression ratios are built in and usually a special fuel mixture is recommended. The reasoning is obvious. Best results are obtained because the fuel, the ratio, and the glo-plug all combine to assure complete combustion.

Difficulties are apt to arise when new fuels are tried because the new fuel-air mixture may not have the same combus-tion point. To attain proper results, the compression ratio would have to be changed. Before attempting such alterations. the original compression ratio should be known; we will show how to determine this. But first, to accentuate the importance of these ratios study the table below. It demonstrates the critical compression ratios of selected fuels. (Critical compression ratio means that ratio from which maximum power delivery in compression ignition engines may be attained.)

A NEW LINE OF SOLID MODELS!



| %" Scale for greater detail and ease in carv | ing |
|--|--------|
| Jimmie Doslittle "Gae Bee" | \$0.75 |
| Art Chester "Jeep" Racer. | |
| Frank Hawks Mystery Ship Texaco "13" | |
| Weddell Williams' Racer-Roscoe Turner's "57" | |
| Pesco Special Racer | .60 |
| Heward "Pete" Racer | |

Scale Plastic decals for a better finish. Detailed plans—full instructions. All balsa cut to outline shape. AT YOUR DEALERS.

TUTTLE BROS. MFG. CO.

330 N. E. 16th Ave., Phone Vermont 5273, Portland 14, Oregon



| FUEL | RATIO |
|------------------------|----------|
| Nitro-Methane5 o | r 6 to 1 |
| Kerosene | to 1 |
| Light Diesel Fuel8 to | o 1 |
| Heavy Diesel Fuel10.6 | to 1 |
| 60 Octane Gasoline11.1 | to 1 |
| 80 Octane Gasoline14.2 | 2 to 1 |

The range of ratios is wide, and when using a glo-plug where the owner desires to try various fuels, consideration must be given to the fuel and its close relative, the compression ratio. Keep in mind that the glo-plug equipped unit is not a spark ignition engine, and cannot be treated as such.

Nitro-methane, a commercial solvent used extensively for film processing, is the most common accelerator used to date. Proportions of a successful fuel are: 1 part nitro-methane, 2 parts methol alcohol, 2 parts bakers AAA castor oil.

Two dimensions are usually stated when describing an engine: bore and stroke. Bore is the diameter of the cylinder into which the piston fits. Stroke is the distance the piston travels from the lowest point in the cylinder to the highest point. The dimensions used here are purely hypothetical and have no relation to any engine which may have these dimensions. Let's take an engine with bore .500 and stroke .750. (For those not familiar with these measurements, they represent 500 thousandths of an inch and 750 thousandts of an inch respectively.) The figures we need next are the volume of the cylinder and the volume of that space which is between the underside of the cylinder head and the piston top when the piston is at its highest point in the cylinder.

To determine the volume of a cylinder the mathematical formula is: 3.1416 x diameter (bore) squared, divided by 4. This figure is then multiplied by the stroke and the result is the volume of space with the piston at its downmost position. To simplify we can divide 3.1416 by 4 and use this formula: .7854 x .500 x .500 x .750. This gives us .1472625 from which we may drop the last four figures as they are insignificant. We have now the volume of the space swept by the piston: .147 cubic inch. Next we determine the volume of the space between the piston at top position and the underside of the cylinder head. The diameter (bore) is the same for this determination. Assume that the height of this space is .050 or fifty thousandths of an inch. The same formula is used thus: .7854 x .500 x .500 x .050 and the answer is .0098175 which we will call .010 for simplicity.

Adding these two volume figures we have: .147 cu. in. (volume of piston displacement) plus .010 cu. in. (volume of clearance space) equals .157 cu. in., total volume of the entire cylinder. The compression ratio is the relationship between this total volume and the volume of the clearance space when the piston is at its topmost position. Dividing the volume of the clearance space into the total volume, the answer is of course 15.7. Hence the compression ratio of our hypothetical engine is 15.7 to 1. Knowing the two dimensions, bore and stroke, application of the above formula will give the compression ratio of any engine.

In the above case the charge of fuel and air is compressed into a space which is about 1/16 the original space occupied, and great pressure is reached, which heats the charge. The glo-plug here performs its function by igniting the highly compressed charge as the charge is brought up to its point of ignition. Com-



Designed by Dick McCoy

Want a winner? Here's your engine ... brand new and raring to go... the hottest Red Head in a complete line of McCoy contest engines. The new *improved* McCoy "60" follows precision standards of other famous Red Heads (49, 29 and original 60). It is built to *win*... to set records... to show its heels to the competition in all events. It is built to make *you* kingpin of *your* contest.

Here it is - more engine at this price than has ever been offered before.

FEATURES

 2 MRC precision ground ball bearings
 2 Perfect Circle piston rings
 Tungsten automotive type points
 Displacement, .60 cu. in. Max. RPM, 20,000 plus Machined surfaces, metal to metal fit, no gaskets VR2 Champion racing plug Weight, 12 oz. Over 1 HP at 15,000 RPM

Buy it at your hobby dealer





With the caming new A.M.A. rules look to the G-P Mighty Midget for the undisputed champion class "C" free-flight engine.

- class "C" free-flight engine.
 Light weight. 7 or. bare.
 More power. Rated .6 H.P. at 12,400 R.P.M.
 10,000 R.P.M. with 12' propeller.
 Only class "C" engine especially designed for free-flight using piston rings.
 Steel piston and cylinder. Glo-plug or hot fuel operation will not pound out steel piston with piston rings. The Mighty Midget can really take it!

- it! Larger crankpin bearing for G-P operation. Bunting bronze main bearing. Flight-tested. Not critical with *any* alcohol base fuel on the market.



bustion starts and the engine operates. The gases released by combustion expand and the piston on its way down opens the exhaust ports, the burnt gases are expelled, a new fresh charge is brought in and the process repeats itself. The gloplug, by retaining some of the heat generated by the explosion remains incandescent and aids the next cycle of operation.

In order to adjust the compression ratio of an engine so that a glo-plug can be used to best advantage, the ratio between clearance space and total volume of the cylinder must be varied. To raise the ratio, the cylinder head must be lowered. This is accomplished by removing metal from the head flange or from the top of the cylinder barrel to diminish the total distance. In fact, any operation that low-ers the cylinder head in relation to the piston top will do the job. In any case no more than .010" thickness should be removed. Taking more than this may seriously affect the port timing of your en-gine. Take care when lowering the head, to allow enough clearange for the gloplug; the piston at its highest point must have no obstruction.

To lower the compression ratio the head must be raised. The effect will be to increase the volume of the clearance space, and this is accomplished by placing gaskets between the head and the cylinder barrel. By knowing the thickness of the gaskets, the new ratio can be computed.

The engine owner must realize that an engine can be changed only insofar as the construction of his particular engine will permit. Some engines with thick cylinder heads may permit the removal of sufficient material to accommodate any baf-fle on the piston itself. In all such conversion work, however, the parts must remain true fitting to prevent pressure losses. Any leakage due to a bad fit, or for any other reason, will reduce the actual compression ratio; while the mathematical ratio in such case might be correct, it is the actual pressure achieved that is important. Mathematical formulas can only determine the ratio, never porduce it.

Use of the glo-plug opens a wide field of heretofore unexplored territory. The possibilities for exceeding present day performance may well come from the combination of fuels, compression ratios, and mechanical perfection which, with the use of the glo-plug, will utilize the greatest percentage of power given up by combustion. The trend of new developments in engines toward greater lightness and speed can be traced from the spark ignition to the diesel, and now to the gloplug. All of these and their many variations promise more for the future development of the ultimate in model airplane engine design. No development is insignificant, and who knows by what happy coordination of features some modeller may come upon the most progressive power unit the model airplane engine field has ever seen.

The writer would appreciate any comment on tests made utilizing the glo-plug, no matter if the engine is one converted for its use or one manufactured with the glo-plug as an integral part. It is suggested that all data be put in writing so comparisons may be made. Fuel and mixture, compression ratio, starting characteristics, port timing, etc.; all of these, as well as visual manifestations, should be noted and by comparing results more accurate information will be obtained. Address all correspondence care of MODEL AIRPLANE NEWS.



Plane on the Cover

(Continued from page 15)

the reciprocating engine ship. Yet it is at low speeds that an airplane needs the greatest power for acceleration in getting the ship in motion quickly.

When a turbojet engine is "run up" on the ground, its big compressor creates a powerful "suction" through the air intake that cannot be accommodated by the surrounding air. Therefore, this creates such a tremendous vacuum in the intake that it has been known to crush the internal ducts. The basic jet fighter problem, as these Grumman engineers saw it, was to provide some means for admitting extra air into the engine while the airplane was moving at a very slow speed. And the answer was "blowing doors", small panels along the upper rear portion of the fuselage near the engine compressor which (1) reduce the vacuum inside the engine chamber thereby relieving the strain on the duct walls, and (2) provide plenty of air for the engine to "breathe" at low speeds. By this comparatively simple device, Grumman appears to have solved the heretofore tough problem of operating a jet fighter aboard a carrier.

A set righter aboat a carrier. As a result, the XF9F-2 Panther needs only 450-650 ft. (depending on the speed of the carrier) to get off the deck and into the air, while the Lockheed P-80 Shooting Star requires about 4000 ft. of runway to get airborne! In addition, when the Panther makes its final approach to the carrier deck and receives a "waveoff" from the Landing Signal Officer, the pilot can "pour the coal" to the engine without hesitation and the resulting surge of power will carry him up and around promptly and safely without the laborious (and dangerous) delay of many other jet types.

With this problem solved, the Grum-man design team set to work on the routine problem of designing a fast, maneuverable fighter of simple, easily-produced for the pilot. But this "routine" job was not executed in a routine manner. For the team next took up the question of landing a very "hot" fighter slowly and This is simply a question of lift safely. coefficient, a product of wing shape, airplane attitude, and speed. Since it re-quires a low lift coefficient to go fast and a high lift coefficient to go slowly, engineers have compromised in the past with both extremes, the resulting product go-ing neither as fast nor as slowly as possible.

Grumman engineers solved this problem by producing a changeable wing profile, one that was straight and smooth for high speed and curved for low speed. This was accomplished by fitting "nose flaps" to the NACA high-speed wing. These nose flaps move forward and down while the trailing edge flaps are moving back and down: producing a high-cambered airfoil with an extremely high lift coefficient in the extended position. As a result, the Panther can slow to 50 mph when "coming aboard" a carrier steaming into the wind, resulting in short landing run and reduced loads on the structure when the deck arrester gear engages.

Another problem, which was not so easily solved, was tailpipe length. The length of the jet tailpipe behind a turbojet engine is of critical importance. It must be long enough to permit the exhaust gases to recover their pressure lost through acceleration yet short enough to minimize the effect of energy losses in the duct. Grumman engineers decided





Here's another addition to your JET POWER FUN by the creators of the original jet racer. Get this new kit from your favorite store today. Fully shaped body with axle holes, metal axles and bushings, rubber wheels, plastic steering wheel and windshield, wire for bumper guards, decals. A truly complete kit! If no dealer near you include 15c extra for shipment

> MONO-JET Ask your dealer to show you the new Mono-Jet too, Monogram's sensational Indianapolis-Type Jet Racer. Kit R-3 . . . 85c.

FIVE

Extra time required for

Fully Shaped Body

Monoarill

Kit R-4

85c

Front

painting and details, of course. Completely shaped balsa body with Mon-ogrill front end, axle holes, and bored for let cartridge, makes assembly easy.

MONOGRAM MODELS, INC., 2329 S. Michigan Ave., Chicago



that the latter problem was of greater importance than the former and fixed the optimum tailpipe length far short of the tail of the airplane, giving the *Panther* its peculiar "soup ladle" appearance at the tail.

One other design problem was adequate power. The engineers were aware that high speed is basically a question of power and no U.S. turbojet engine offered the power required for the new design. So Grumman went abroad for the potent Rolls-Royce Nene turbojet engine that is rated at 5000 lbs. of thrust (dry) and nearly 6000 lbs. of thrust using water injection. Two engines were imported for experimental use in 2 of the 3 prototype Panther fighters. In the meantime, the Navy Department made arrangements for establishing an American producer of this powerful engine and signed a con-tract with Pratt & Whitney Division, United Aircraft Corp. to produce th *Nene* in quantity. As a further safegua-to insure power for the *Panther*, the save to insure power for the Panther, the contracted with Allison Division, C General Motors Corp., for recently-improved Model 400 engines, which are eventually slated to attain the output of the British model. The third prototype KF9F-2 will be powered by this new Allison engine. Production quantities will alternate between the two engines, creating the first U.S. jet airplane capable of using either of two engines.

Proof that Grumman engineers have produced another winning design is the award of a contract for constructing 100 Panther fighters before Corwin "Corky" Meyers had even put the new craft through its initial paces. (The first flight, incidentally, ended on the runway at still-uncompleted Idlewild Airport, where Corky knew there was adequate runway length. Following the landing he took the Panther aloft from Idlewild, thereby "breaking in" the magnificent new project as a secret test base before it assumes its more prosaic duties as an airline base next July.)

Performance figures on the new Panther are not available simply because neither Grumman nor the Navy know them: The plane is still so new that it hasn't been flown over carefully calibrated courses, nor its instruments checked for accuracy. But you can bet it will crowd the 650 mph mark when it does race over the Naval Air Station course at *Patuxent* shortly. And it will top the 45,000 ft. altitude mark by a considerable margin.

Grumman is already forming an F9F production line and building the special dies, fixtures and jigs for its production. During this year the Navy expects to get only one dozen F9F's, and a total of 89 next year, but that 100-order is only the beginning of the Navy's plans for the speedster. They've already prepared schedules for eventual quantities of 200-300-500 Panther fighters, the exact number of which will depend on Congress and how well the Navy can convince them that in the new Grumman F9F Panther fighter this nation has the world's best carrier jet fighter. Personally, we're already convinced!

New WYLAM Series!

A new series of Bill Wylam's superb Masterplans on the PFALZ D12, German W.W.I pursuit ship will begin in

May MODEL AIRPLANE NEWS

This series will include detailed drawings of the Mercedes engine, used in the Pfalz and also in many other German service planes.

Scrap Box

(Continued from page 8)

other ingredients. Is that better, Phil? And how about you other fellows, should we give details of record models?

give details of record models? Here is one that should knock over in-the-rut speed demons. On last Novem-ber 10, Richard Grandel, age 14, set a mark of 120.85 mph in Class VI Junior, with a *Dooling* 61 in a *Duraplane* kit model, the aggregate weighing 44 oz. How's them for apples! And here is another. Last Dec. 1, Manuel D. Andrade, Oakland, Calif., heaved a 5/8 oz. Class B Open indoor glider to a mark of 1:08. It had a 14-5 8 in. poly-hedral wing, with 45.3 sq. in. of area. This talk of AMA official records re-

This talk of AMA official records re-minds us that last month we invited the This taik of AWA official records re-minds us that last month we invited the AMA to reply to those Indiana beefs about a more democratic way of making the rules. You will recall that the Indiana Gas Model Ass'n thought enough leaders, clubs, etc., would be interested to help pay the ex-penses of an individual poll. If this sounds like a swell suggestion it is also an old one, for all of us, officials included, always wished it was possible. Russ Nichols, exec-utive director of AMA, offers something to chew on but also first points out a few difficulties, such as hard to evaluate factors that spring into being with a large ballot mailing. For example, there is the ad-dressing and mailing of some 30,000 pieces of mail, and the help needed to tabulate all these returns, to say nothing of printing and preparing the mailing. and preparing the mailing.

and preparing the mailing. "In thinking this over," says Russ, "it seems to me that perhaps we should go at the problem from the other end, namely that of devising a different procedure for the process of changing rules and then pro-posing the necessary amendments to the by-laws to accomplish this. For example, if the clubs in the various districts were willing to raise funds for this purpose, it would seem to me that the logical next step would be to pay the way of their contest board members to an actual meeting of the body to be held in some centrally located city. Of course." Russ goes on, "this should be done with plenty of advance notice so that each member could come to the meet-ing with a thorough understanding of what the model builders in his district want."

Russ makes the point that there is no other organization of comparable size that does not carry on its voting and policy pro-cedure by actually holding a national meet-ing or convention. Since it is obvious that we can't pay our way as individuals to such we can't pay our way as individuals to such a convention or meeting it might not be too great a strain on various clubs to get to-gether and raise railroad fares for their two contest board members once a year. But where do we go from here? You Hoosiers started this. How about picking up the ball and running for another down. Maybe we'll be able to push the ball over the line. if we all put our heads together. (We hope to publish replies, if any, two or three issues from now—this being written in mid-Janu-ary.) ary.)

We apparently underestimated the light-We apparently underestimated the light-ness of ships with glo-plug engines, for Dick Korda tells us about a new 4-1/2 oz. 10 in. Arden .099 speedster. The "butchered" Arden is on its side with a cylinder pointing to the left or outside wing. A butterfly tail with elevator on the outside half, and an odd "flat" look distinguish this unusual design. Dick is going to have a hard time keeping design secrets in the future from at least one other Cleveland expert George

keeping design secrets in the future from at least one other Cleveland expert. George Reich has it figured out. He got himself engaged to Dick's sister. Model trends around Little Rock are largely what oldtimer John Sadler likes to build. If John goes free flight, so do the boys. Currently it is U-control, so you can guess what happened to free flight. The Little Rock boys are going faster and faster and Arkansas is becoming one of the hot spots. Sadler cross-countried all the way to Charlotte, N.C., last fall and came home bugeyed over a second place won at 111 mph with a biplane with a fixed gear. Also present was a father and son team with three PDQ kits and six engines—one for each class. The kid chewed bubble gum

MODEL AIRPLANE NEWS . April, 1948



anteed satisfaction, you'll like doing business with us. Dependable California merchandise a specialty! We also recommend the following items: *Means California Merchandise

Accessories

9.50

Wright Test Block

Engines

| *Daaling 61 | \$35.0 |
|-----------------------|--------|
| *McCoy 49 | 25.0 |
| *McCoy 29 | 19.5 |
| "Ohisson 60 | 11.9 |
| Ohlsson 23 | 9.9 |
| 'Ohisson 19 | 9.9 |
| *Anderson Spitfire 60 | 24.9 |
| *Fox 59 | 29.9 |
| *Atwood Champion | 17.5 |
| *Madewell 49 | 12,5 |
| *Contestor | 18.5 |
| *Cyclone 60 | 22.0 |
| *K&B Torpedo 29 | 18.5 |
| *K&B Torpedo 24 | 16.5 |
| "Dennymite | 6.9 |
| Arden 099 PB | 12.5 |
| Arden 099 BB | 15.5 |
| *Sportsman Jr. Hot Pt | 14.93 |
| *Sportsman Sr. Hot Pt | 16.9 |
| *Mighty Midget G.P. | 14.9 |
| *Vivell Diesel | 11.9 |

Control Line Kits

10.00 5.95

14.75 4.95

10.95

8.50

9.95

6.95 3.95

6.95 7.95

4.95 3.95

3.95

3.95

3.95 3.95

3.95 4.25

4.95

4.95

3.95

5.45

2.50

3.50

2.95 2.95

2.95

5.50

5.95

6.00 6.95

4.95 3.95

4 95 3.95

3.00

3 50

4.95

4.95 3.65

1.95

1.50

1.50

*Madman (C) *Box Car Chief (C) *Box Car (C) *Casalaire (C)

*Casalaire (C) Suger-Zilch (C) *Snatu Ercoupe (B-C) *Snatu Typhoon (B-C) *Snatu Typhoon (B-C) *Snatu Tero (B-C) *Skychief (B-C) Orbit (B-C) A. J. Fireball (B-C) Skybox Trainer (B-C) Skybox Stunt (B-C) Skybox Stunt (B-C) Ryan Fireball (A-B-C)

Trainee (B) "Fairchild PT-IS (A-B).... Hawker Super Fury (A).... *Fokker "Tripe" (A)..... Whirlwind Jr. (A).... Hall Racer (A)... Skystreak (A)....

Free Flight

 Silvaire (B)

 Wanderer (B)

 Aoronca Champ (B)

 Honey "B" (B)

 Zipper (B-C)

 "Miss Tiny (A-B)

 "Spoak "48" (A-B)

 "Plxle (A)

 American Acc "36" (A)

CRESCENT

CO2 Powerhause

Mercury (C) .

| U-Reely Control | 7.50 |
|-------------------------|-------|
| U-Realy Remoto | 12.50 |
| *Flightline Reel-Metal | 1.25 |
| "Wood Reel 6" Dia. | .50 |
| *Wood Reel 8" Dia | .75 |
| *Flightline Hndl.—Metal | 1.25 |
| *Wood Handle | .75 |
| *2-50' Stranded Wire | 2.60 |
| *2-70' Stranded Wire | 3.25 |
| *2-30" Lead Outs | .40 |
| Spark Plugs (All sizes) | .50 |
| Arden Glow Plug | .85 |
| *McCoy Hot Point Plug | .85 |
| *Firecracker Coil | 2.75 |
| Aero Quality Coil | 3.00 |
| Aero Ft. Wt. | 2.50 |
| *Competitor Coll | 1.95 |
| Aero Racer Condenser | .60 |
| Aero Condenser | .35 |
| Metal Condenser | .30 |
| Slide Switch | .25 |
| Toggle Switch | .50 |
| *Hillcrest Timer | 1.25 |
| *Austin Timer | 1.50 |
| Arden Timer | 1.85 |
| Arden Booster Jack | 1.25 |
| *Univ. Needle Valve | 1.00 |
| *Battery Box | .40 |
| *Veco Bell Crank | .25 |
| *Maeco Stunt Tank | 1.25 |
| *Baker Wedge Tank | 1.25 |
| (Lg. Med, Small) | |
| "Ohlsson "60" Tank | 1.75 |
| *Ohlsson "23" Tank | 1.50 |
| "4-Way Plug Wrench | .50 |
| *Austin Glue Gun | 75 |

Tools

| Dremel Moto Tool | 23.50 |
|------------------------|-------|
| Dremel Moto Saw | 5.85 |
| DeLuxe Vibro Tool | 16.50 |
| Hobby Chest #86 | 10.00 |
| Hobby Chest #87 | 15.00 |
| Xacto Hand Drill | 2.75 |
| Xacto "C" Clamps (4) | 1.50 |
| *Ungar Soldering Kit | 2.00 |
| *Ungar Woodburning Kit | 2.00 |
| | |

Gas-Powered Boat Kits

| 0-Gee (B-C) | 5.95 |
|---------------------|-------|
| O-Gee Hardware Kit. | 1.95 |
| Harco Gruiser | 4.50 |
| Chris Craft | 4.50 |
| Owens Flagship | 4.50 |
| "Sea Myth" Luxury | |
| Cabin Cruiser | 13.95 |

Deserve

| | | CT.3 | |
|----------|-------|----------|------|
| *Thimble | Drome | "Champ" | 3.95 |
| *Thimble | Drome | Wind-Up. | 2.95 |
| *Thimble | Drome | w/tether | 2.25 |

Misc. Kits

| 32 Pd. Carronnade | 4.50 |
|---------------------|------|
| Sea Mortar | 4.00 |
| One Pounder | 4.00 |
| Field Artillery | 5.00 |
| *S.F. Cable Car | 2,95 |
| *Horseless Carriage | 1.50 |
| *Covered Wagon | 3.95 |
| *Stage Coach | 3.95 |
| "Sportsman Conv. | 1.00 |
| *AV8 Hot Rod | 1.00 |
| *Midget Racer | 1.50 |
| *Metal Quonset Hut | 1.95 |
| | |

5620 West Pico Blvd.

L

Ohlsson & Rice No. I Pint 75c \$1.40 Quart Ohlsson & Ric FOR GLOW PLUG Ohlsson & Rice No. 2 Pint 75c Quart. \$1.40 NEW O & R GLOW PLUG An improved tested glow-plug for dependable performance. Each 85r 23.____ 9.95 19 9.95 Rotary Valve 60 Special 6.00 Rotary Valve 19 & 23..... 5.00 Tank Mount..... 1.75 AUSTIN-CRAFT **GLUE GUN** Puts cement on edges and in tight corners. Very handy, 75c **AUSTIN-CRAFT PLUG WRENCH** C C, 4 Sockets to fit all plugs, Pro-tects head fins and plug porce-lain. 50c POSTAGE FREE IN U.S.A. Our policy: Minimum order \$1.00. Send remittance in full. \$1.00 with C.O.D. orders. (Calif. residents please add $2\frac{1}{2}\%$ sales tax.) **MODEL SHOP:** PLANES, BOATS, TRAINS Los Angeles 35, Calif.

NEW O & R

FUELS

Sensational "hot" fuels just

announced by Ohlsson & Rice.

Increased R.P.M.! Improved

FOR

STANDARD IGNITION

lubrication!

59



and the old man switched engines all day. They took every junior event. Personally, we think the father-son deal in U-control is a fine thing for the hobby. Before control line came along such teams were a phenomenon.

trol line came along such teams were a phenomenon. Texarkans (or is it Texarkanians?) figure they have a pretty hot stunt man in a chap named Corley who believes in taking things easy. He lies flat on his back and does eighths in series. Corley favors a big fast ship capable of 92 mph on the "straightaway." Span is 54 in., power *Hornet*, prop 11-8.

Stunting is fun, no doubt, but it is also funny. So many fellows take to it like ducks to water. And some of us really have our headaches. Paralysis of the brain, or dolor de la cabezza as they say in high school Spanish (did we get that right?), or sorrow of the head. Once the ship is on its back, thinking processes freeze. No wonder you see crates with wheels on both top and bottom! Previous modeling experience doesn't seem to help, and experience with real aircraft seems to be a handicap. Jack Reeves, an ex-Army pilot from Texarkana and a good control line man, has his troubles with inverted flying. "I flew it inverted twice—the first time about half a lap and the second time over two laps." explains Reeves. "Both flights ended in inverted rather shallow dives into the ground. In other words. I gave it a slight amount of up to get back to level flight which, of course, increased the dive—then I lost all power of normal thought process and just did nothing 'til bang! I can talk myself through a whole flight inverted—on the sidelines, but boy, when I get that handle it's different. I just can't push when it seems I ought to be pulling." Like we said, this sort of thing happens to a lot of us. Do any of you not rock stunters have a few helpful tips, or do you have to be born that way?

that way? Speaking of stunting, we hear our figures on Jim Walker's *Glo-Plug Fireball* were almost double what the ship really weighs. Now we hear that it is 10½ oz. People who have seen it flown say it is like a whirling dervish. responds fast and has a skidless, mushless grip on the air like roller skates in a sand pit. You can make a mistake, pull out of it, make another, get out of that ... what suspense! "The Texans are Glo-Plug happy in Dal-

pull out of it. make another, get out of that ... what suspense! "The Texans are Glo-Plug happy in Dallas." says Jim Tucker, another ex-fly boy of Monticello. Ark. "I imagine you have heard of Sam Beasley, their local hot shot; I was reliably informed that he hit 148 mph with a McCoy 49, glo-plugged and pressure cowled. They have done 138 mph with a Hornet. They are all using the new semitoothpick (9-13) Rev-Up prop which is made in Dallas." Though we haven't seen one of these props yet, we hear they are beautifully machine cut. Tucker, incidentally, swears by benzol for fuel. He gets it from a drug company at \$1.75 a gallon and warns about being sold white gas as benzol. "This stuff is hot." says Tucker. "when mixed right, with the right ingredients, and used while still fresh. The Dooling will burst your ear drums if you stand on the exhaust side while running that mixture in it."

it." We don't know where the idea came from, but for the benefit of an occasional U-controller who asks us not to go rough on said sport, we wish to go on record by saying that we don't dislike what some of the rabid free flighters call yo-yo. We probably will never fly speed, but we feel that the speed model comes closer than free flight to the engineering type of design problems of real aircraft. The good speed builder gets into problems of cooling. venting, efficiency, loadings, that free flighters hardly care about. The hot speed job is more than an engine. we'll be the first to admit. And stunting really interests us. So does scale. As a matter of fact. the only way we could get interested in speed would be in a flying scale event. Through the years there has appeared a wondrous line-up of speed jobs, the Chester and Howard racers, the Caudrons, etc. Picking the right job for your motor and getting the motor into it without parting too much from scale would be a real test of skill. Such an event would



introduce a new element, besides flying skill, the hot engine. fuels, props. etc. They'll be important, but the advantages or disadvantages of the real ships selected would be a major factor. Factory plans, or at least bona fide three views like magazine plans, should be required. Points should be awarded on some simplified basis for appearance, scale, etc.; something like the flying scale event only simpler and more practical. What would happen if these ships had to be built to uniform scale? Two models in one circle would be a thrill. Hold your hats!

hats! So the secret police won't pick us up as a free flight deserter we want to pass on a thought on those new designs. One factor we intend emphasizing in our own stuff, if we ever get chance to open that glue can, is the relationship between lifting area and the thermal. Anybody knows that a C job is more apt to make like a sailplane than an A job (that's force of habit; we don't get it through our noggin that there are also Class D and E these days!); so with no wing loading to contend with why not use all the area that you can get away with, efficiently. of course. Use a really thin airfoil, even if it means a lower L/D. You'll stay within the limits of the motor to drag the ship upstairs in a hurry. It'll float. too. Clean up the design and cowl in the engine to eliminate that flat-plate firewall drag. Charles H. Muth. secretary for Minneapolis Model Aero Club, with the sad case in mind of untrained volunteer timers who work with much enthusiasm but little skill, suggests a national pool of timers who have

Charles H. Muth. secretary for Minneapolis Model Aero Club, with the sad case in mind of untrained volunteer timers who work with much enthusiasm but little skill, suggests a national pool of timers who have proved themselves competent in reasonably large meets, and who would be willing to assist in meets in nearby areas—both as timers and instructors for new timers. Well, it seems to us that in small areas and the average contest the meet management, or at least their adviser, if he has anything between the ears, would know of available timers. But in larger meets there never seems to be adequate timers. One possibility would be to have the contest director supply the list of names and addresses of timers used to the Academy. or at least to the district vice president who then could supply information when somebody runs short of people who make with the watches. Hobby shops could keep a file of timers in their areas, if sold the idea. Another aspect of this problem is that the less flights allowed for all types of models the further the timers will stretch at any given meet. We wondered about this while watching control line speed flights tie up three timers simultaneously for as long as 15 minutes.

We wondered about this while watching control line speed flights tie up three timers simultaneously for as long as 15 minutes. Of interest to clubs who would interest beginners. Muth relates that the Minneapolis Aero Club challenged the St. Paul Modelers to a contest with 12" models--tissue covered--which were flown at the Minneapolis Club meeting place. Ceiling is about 10 ft., with chandeliers furnishing erratic thermals and obstructions. High time, nevertheless, was 3:55, and both clubs were so enthused that a return bout was scheduled in Feb. The meeting place? The mayor's reception room at the Minneapolis court house!

mayor's reception room at the Minneapolis court house! A letter from Eddie Cosh, received just as this material was ready for the printer, confirms some vague rumors we have heard that 1948 will see a resumption of Wakefield competition. Though final plans have not been made, it seems there will be an F.A.I. meeting held at Cleveland during the air races and it is proposed to hold the Wakefields at this time. Eddie is unable to say whether a team will come over from England or whether they will have to send their models over to be flown by proxy. At any rate, the English flyers are planning to run a scries of elimination trials all over the country before the finals are held, and we are assured that the very best possible team will be chosen.

team will be chosen. Rules will be the same as they were prewar; we urge interested modelers to study them carefully and start their building program for the Wakefields at once.

> National Boys' Club Week April 5th to 11th

MODEL AIRPLANE NEWS . April. 1948



COMPLETE WITH price! Send for LEAD! "The Sparky Coil" and take advantage of this special offer! It's a value at \$2.50! It's a sensation at this new low price! model builder wants it! Here is a honey of a knife that you can carry with you wherever you go—for repairs on the field—building at home —a 1000 uses! It's as sharp as a razor because it is a real razor blade! Always with you because it comes complete with a strong chain! The blade is replaceable! The knife is collapsible! Get your Razor Knife now!

| BOTH FOR \$1.25 SEND FOR YOUR PL | INCLUDING POSTAGE! RIZE PACKAGE TODAY! |
|-------------------------------------|---|
| SPARKY SPECIALTIES, INC., 17 | 3 West Madison St., Chicago 2, III. |
| Dear Sparky: | |
| Please send me | Prize Packages. I'm attaching \$1.25 |
| for each package! Send Today — | - to: |
| Name | |
| Address | ZoneState |



can you top this?

THE FOLLOWING ITEMS FREE WITH EACH MOTOR

1. Quality Coil 2. Metal Condenser 3. High Tension Lead 4. 100' Control Line Wire 5. Slide Switch

C R N O

INSURANCE

FREE

OSTAGE

۵.

- 6. Alligator Clips 7. One Foot Fuel Line 8. 6' Ign. Hook-up Wire
- 9. Two Pen Cells 10. Mounting Bolts

GAS ENGINES

| | | - 4 |
|-----------------------|-----------------------------|-----|
| McCoy 29 | Sportsman, Jr | 0 |
| McCoy 49 25.00 | Sportsman, Sr 16.95 | |
| McCoy 60 35.00 | K and B Torpedo 29\$18.50 | |
| O. K. 29 | Hornet 35.00 | |
| O. K. Super 60 18.00 | Super Cyclone GR 22.00 | 9 |
| O. K. Twin 55.00 | Super Champion JH 23.50 | |
| Arden .199 B. B 18.50 | Pacemaker 24.95 | c |
| Drone Diesel 21.50 | *O. K. Co ₂ 4.95 | 5 |
| * NO FRE | E ITEMS | - |

ALSO COMPLETE LINE OF KITS AND ACCESSORIES

mple mailing instructions: Print name and address clearly, list items, enclose check or ¢ money order, Free packing, handling and postage. No minimum order. No C.O.D.

THE EASTERN SUPPLY CO. New Britain, Conn. Box 615 Operated by Active Model Builders



Flash News

(Continued from page 2) (Continued from page 2) SECOND NORTHROP YB-49 eight-jet Flying Wing bomber flew away from its Hawthorne, Calif. birthplace to Muroc Base for extended tests. Reports from the first YB-49 reveal high speed of better than 500 mph and a phenomenal rate-of-climb. BEECH AIRCRAFT has designed an am-bulance version of the "butterfly tail" Bonanza for charter service. The modifica-tion consists of removing the right front seat and the entire rear seat and installing a small left rear seat and a metal-framed

seat and the entire rear seat and installing a small left rear seat and a metal-framed stretcher easily clamped in place. This pro-vides room for pilot, attendant and patient. SUCCESSFUL TEST flights have been made on the Aquafight. Inc., amphibian, Aqua I. A six-place design, the craft is pow-ered by two Lycoming 125 hp engines. It is a high wing monoplane with sponsons pro-jecting from either side of the fuselage at the waterline. Of composite construction, the amphibian has a wooden hull and metal

INSU

Jecting from either side of the fuselage at the waterline. Of composite construction, the amphibian has a wooden hull and metal wing structure. Cruising speed is 125 mphover 750 mile range, 1400 lbs. useful load. THE HUSKY is looking for a new owner and several offers have been received for the purchase of this Canadian-built single-engine "bush freighter." Fairchild Aircraft Ltd., one of the oldest aviation companies in Canada, announced its dissolution and the placing for sale of all rights, technical data. tooling and parts including one complete airplane, of the Fairchild Husky.
THE NOISELESS AIRPLANE, developed by NACA last year, is going to be even more "noiseless". Latest development in the project is the transfer of the airplane (a special Air Force Stinson L-5 Sentinel) to the Aeronautical Research Foundation, a group of researchers from Mass. Institute of Technology. Multiple propeller blades (up to 8) are now being tried, together with various types of Maxim silencers to reduce noise to the lowest practical limit. After this is achieved, the noise will be progressively increased until the threshold of "nuisance" is approached. The design will then be offered to manufacturers free for incorporation into production designs. BIGGEST YEAR in history of the lightlane has been rung up with final 1947 reports showing total production of 16,023 personal aircraft valued at \$\$3,206,000. This is about 150% better than 1941 best prewar year. Oddly enough, the record shows that three and four-place types outnumbered the popular two-place type. This year the value of production is predicted at about the same (about \$50 million), but the numbers are expected to drop 50%, the difference being in the increasing sales of 3-4 place type. Signat Monsanto solid fuel rocket motors developing 10,000 bs. of thrust each, the equivalent of 150,000 hpt? Purpose of the high-speed device is to mount model airfoils for testing at supersonic speed, the sled attain-

testing at supersonic speed, the sled attain-

Attention! METROPOLITAN **N.Y. CITY DEALERS!**

YOU are invited and urged to attend the meetings of the reorganized "Metropolitan Hobby Guild" which has begun to ACCOMPLISH BENEFITS FOR YOU!

We are getting flying locations for model builders in this area, and are working on obtaining race car tracks and boat builders locations.

Our meetings have interesting and worthwhile features including: movies, guest speaker, display of new items by monufocturers, etc.

The bigger we become, the more we can accomplish—FOR YOU!

See your jobber for more details— or contact Tex Foster, 105-14 Ja-maica Ave., Richmond Hill 18, N.Y.C.

ing speeds as high as 1000 mph. What would ing speeds as high as 1000 mph. What would make it interesting to watch is the fact that it leaves the end of the tracks going at a speed of 1000 mph and leaps and bounds across the flat dry lake bed at Muroc Air Base, Calif. quickly flying to pieces. North-rop engineers, however, believe that a 10,000 ft. track would permit slowing the sled to a halt with the aid of reverse-firing rockets and a water trough into which a scoop dips near the end of the run.

scoop dips near the end of the run. WHAT MAY PROVE TO BE the first "average man pocketbook" helicopter has completed initial test flights satisfactorily. Known as the JOV-3, the two-place craft utilizes dual rotors mounted fore and aft (as the Piasecki) and is powered by a Ly-coming 100 hp aircooled engine. Designed by D. K. Jovanovich, president of Heli-copter Engineering Research Corp. of Philadelphia, the tiny craft cruises at 73 mph and has top speed of 100 mph. It will sell for about \$8.500 with a \$6.000 price tag ex-pected when production gets underway. THE HOPPI-COPTER continues to grow.

THE HOPPI-COPIER continues to grow. Here's another progress report on what started out to be a good idea and, like so many other good ideas, got completely out of hand. It started out as a simple little back-pack which enabled the wearer to soar into the air via whirling helicopter soar into the air via whirling helicopter blades. But it has grown and grown. It now has a 40 hp engine, rotors 17 ft. in diameter and 900.000 shares of stock in the corpora-tion. It has grown a large framework, seat, additional controls, wheels and a special enclosure fabric covered. Why not just start all over again, Horace? AS THIS IS BEING WRITTEN, the sup-posedly 5-man Civil Aeronautics Board con-sists of 2 men: Oswald Ryan and Josh Lee, and cases continue to pile up on the stack awaiting decision. A replacement for Clar-ence Young hasn't been found since his resignation last fall; Pres. Truman refused to reappoint Chairman James Landis, and

to reappoint Chairman James Landis, and member Harlee Branch recently resigned. This is certainly a scandalous way to oper-ate the highest judicial body in aviation in the U.S. in a period when air transport in the U.S. in a period when air transport is staggering under heavy losses, air-freight is completely stymied, and contracts for the Martin 2-0-2 and Convair Liner—the two postwar airliners dreamed of for long months during the war—are being cancelled again and again. And T. P. Wright, Admin-istrator of Civil Aeronautics, has resigned, locating the again of the airway with leaving private flying and the airways with-out direction. If ever there was a monu-mental opportunity for dynamic leadership to come forward, now is the time. Let's hope it won't take too long!

A Class C Towliner

(Continued from page 25)

The stabilizer is cemented firmly to rear of the fuselage, and wing hooks-made of straight pin wire-are cemented in place to hold the rubberband which secures the wing. Balance should be at the wing spar, midway out on the wing panels.

Check the model carefully for warps, sighting from front and rear while holding the model at arm's length and removing any noticeable misalignments by steaming. The first test glides are made from kneeling position, into the wind, as a check on trim and balance. Adjust the fins for a gentle turn in either direction. Rules specify a 100' towline with a streamer attached within a foot of the model so that the timer may be certain when the model is free and the official timing begins. Ordinary kite string will do, with a small wire loop at the end to engage the tow hooks on the model. In gentle winds a rear hook will be found best, and in higher winds those toward the nose are recommended. Launch the model by having an assistant release it as you walk or run into the wind, veering to the side opposite that to which the model tends to turn. When maximum altitude has been reached. slacken the line, permitting it to drop free.

 BASS OR PINE COST TWICE BALSA BALSA SMEETS—2x18

 2 x 36 or 3 x 16 cost 3 times 3 x 36 or 4 x 18 cost 5 times 2 x 60 or 4 x 18 cost 5 times 3 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 60 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 x 60 x 6 times 1 do costs 8 times 4 times 4 x 6 times 1 do costs 8 times 4 x 6 times 1 do costs 8 times 4 x 6 times 1 do costs 8 times 4 x 6 times 1 do costs 8 times 4 times 4 x 6 times 1 do costs 8 times 4 times 4 times 1 do costs 8 times 4 times 4 times 1 do costs 8 times 4 times 4 times 1 do costs 8 times 4 times 4 times 1 do costs 8 times 4 times 4 times 1 do costs 8 times 4 times 4 times 1 do costs 8 times 4 times 4 times 1 do costs 8 times 4 times 4 times 4 times 4 times 4 times 4 times 1 do costs 8 times 4 times 4 times 4 times 4 times 3/10x124*...4, Sc I s_x1* ... Dc ea. 18" BALSA PLANKS 36" Costs Double, 60", Four Times 34x34...10 1x3...55 2x6...100 1x1...10 2x2...40 3x3...80 1x2 34...10 3x4...125 1x4....25 2x4...100 3x6...225 1x4....25 2x4...100 3x6...225 1x4....25 2x4...100 3x6...25 1x4....25 2x4....100 3x6...25 1x4...25 2x4...100 3x6...25 1x4...25 2x4...10 PROPBLOCKS
 NOSE
 BLOCKS
 PROPBLOGKS
 Mustang P51

 1x2x1
 12x2x81
 1061/2x2x83
 26
 PACKET NO. 11

 3207
 524x84
 1561/2x32x83
 26
 PACKET NO. 11

 1x2x1
 12x2x61
 1061/2x32x83
 26
 PACKET NO. 11

 1x2x6
 561/2x32x81
 106
 26
 Atracobra

 1x2x6
 561/2x32x81
 107
 Atracobra

 1x3x6
 76.4x61x4
 106
 1x11/2x12
 C

 1x3x6
 76.4x61x4
 106
 1x11/2x12
 C

 1x3x6
 76.4x61x4
 107
 11/2x12
 C

 1x3x6
 76.4x61x4
 1x11/2x12
 C
 PACKET NO. 12

 2x3x3
 76.4x62x4
 1x11/2x12
 C
 PACKET NO. 12

 2x3x3
 76.4x62x6
 14/2x218
 126
 PACKET NO. 12

 2x3x3
 76.4x62x6
 14/2x218
 126
 PACKET NO. 12

 2x3x3
 76.4x62x6
 14/2x218
 126
 PACKET NO. 12

 1x10x60001
 14/2x218
 126 NOSE BLOCKS
 IS*
 OGC 90C

 PLASTIC
 20c

 2 Biads bid abi
 20c

 1½2
 2c 10c 10C

 2 Lastic
 30c 8 asstd. cols.

 1½2
 2c 10c 10C

 2 Side 3bi
 4bi

 1½2
 2c 10c 10C

 2 Side 3bi
 4bi

 1½2
 3c 15c 20c

 3¼2
 10c 20c X

 4''
 10c 20c 3C

 5''
 20c 30c 30c

 5''
 20c 30c 30c

 1 Sto 20c 30c
 Xa

 Yapt 55c; pt\$1.00
 Col-PRE-WAR SILK TRIPLE A grade 4mm \$1.98 sq.yd. Luxe, 2 jars \$1.98 **KIT MANUFACTURERS** Skyway's new, streamlined price and service set-up gives you special cut balsa, metal parts, access., etc. Send requirements and we will quote. SKYWAY BARGAINS 42"-34 Scale FLYERS, Cadet Thun-derbolt-Hellcat-Mustang, Were \$1, NOW ALL 3-\$1.95. MASTER MODELCRAFT \$3-4 Solids Mustang, Martin B-26, Corsair, Doug-las, Mosquito, Thunderbolt, Can be converted into Control Liners, ONLY \$1.95 each 6 CADET 26c SOLIDS only 98c CAUE: Ca SULISS ONLY 38C
 Thunderboit, Helicat, Focke-Wulf, Ty-phoon, Spitfre, Mustang
 RAY SI SOLIDS 59c each
 Helicat, War Hawk, Mustang, Spit-fre, Typhon, Shooting Star
 RAY ROCKET ONLY 59c
 \$1.25 RAY ROCKET GUN Only 59c
 \$1.25 RAY ROCKET GUN Only 59c

All parts moulded of precision plas-tic.

Over 130 die eut parts of wood, metal and plastic.

Was \$7.95. \$5.00

SUPER PLANS \$1.00 Packets Fictus VA" = 1' PACKET NO. French Spad Fokker DV11 Sopwill Camel Nieuport 17C1 Fokker DV111 British SE5a Albatross Scale Three V PACKET NO. 1 Typhoon Vought Corsair Spithre IX Focke-Wulf 190 Lightning P38 P-40F Mosquito MOSQUIO PACKET NO. 2 Helleat Zero Stormovik Thunderbolt Mustang P51 Airacobra Avenger PACKET NO. 5 Flying Fort Marauder Mitchell B25 Liberator Lancaster Arracembra Avenger PACKET NO. 3 Hawker Hawker Marace Marace Hurricane Kingcobra Nazi NE 109 Dauntiess CONTROL LINE CONTROL LINE CONTROL LINE Factor Wolf 190 Musting P51 PACKET NO. 11 PACKET NO. 6 Culver-V Scabce Piper Super Aeronca Voyager Globe Swift Voyager Globe Swift Erroupe Erecket roc. 13 Spad Fighter Fokker DV11 Supwith Camel Nieuport 17C1 PACKET NO. 14 Piper Skycycle Globe Swift Erroupe Johnson Rocket Johnson Rocket Fokker Racer Fokker Racer Wendell Williaman Howard IV Facket No. 13 Gee Hee Racer Fokker Racer Stable Construction Culver Catel Floya Stable Compethed 10 AIRFOIL SECTIONS \$ 1 3" to 12" 444 SIZES ---- \$ universal N'die Valve 50c; Flex. T5c WalkER "U' REELY CONTACT. 7.50 WalkER "REMOTO." Launch with motor idling. Fly solo. taxi, etc With ensure led control wire \$12.50. JEM CONTACL HADLE. Only one that always redums to neutral. Was \$3.0.7. www.science.
 JEM CONTROL HANDLE. UNLY MEE

 Discours
 Control Handberger
 Unly Meeters

 Stable
 Now \$2.49.
 Press

 Discours
 Song Stable
 Press
 Press

 Discours
 Song Stable
 Press
 Press

 Discours
 Song Stable
 Song Stable
 Press
 Press

 Discours
 Song Stable
 Song Stable
 Song Stable
 Song Stable
 Song Stable

 Discours
 Song Stable
 Song Stable
 Song Stable
 Stable
 Song Stable

 Discours
 Song Stable
 Song Stable
 Stable
 Stable
 Stable

 Discours
 Song Stable
 Stable
 Stable
 Stable
 Stable

 Discours
 Song Stable
 Stable
 Stable
 Stable
 Stable

 Discours
 Stable
 Stable
 Stable
 Stable
 Stable

 Discours
 Stable
 Stable
 Stable
 Stable
 Stable

 Output
 Stable
 Stable
 Stable
 Stable
 Stable

 0434 or 1.00* 56
 043 or 1.00* 56
 110* 56

 0434 or 1.00* 56
 126
 126

 043 or 1.00* 56
 126
 126

 043 or 1.00* 56
 126
 126

 044 or 1.00* 56
 126
 126

 045 or 1.00* 56
 126
 126

 046 or 1.00* 56
 126
 126

 047 or 1.00* 56
 126
 126

 048 or 1.00* 56
 126
 126

 126
 126
 126

 126
 126
 126

 126
 126
 126

 126
 126
 126

 127
 126
 126

 126
 126
 126

 127
 126
 126

 128
 126
 126

 128
 126
 126

 128
 126
 126

 128</ Rogers LCI merly \$2.95 tic. Farmerly \$2.95 Now \$1.00 Varney PT BOAT Varney PI BUAI Dover 120 die eut. 2012" scale. 2012" scale. 2012" scale. 2012" scale. 2012" scale. 2012" scale. 2016" scal Skyway Modelcraft 426-6"AVE.

SEE YOUR Skin 24 HOUR SERVICE GUARANTEED IN U.S.A. WE STOCK ALL WORTH WHILE ADVERTISED KITS and SUPPLIES
 WE SIGCA ALL WORTH WHILE
 Gas ENGINES 4%/16 Coll & C'denser

 Atom A .099.
 55.50

 Sarden .049 B.12.50, B.D......
 15.50

 Genie S.60 55. Thor.
 9.95

 Madewell C ...was \$18,, \$12.50

 Contextor C, Rotary Valve......
 T56 CONTEST RUBBER THRUST BEARINGS Small 4 for 5c Medium 3 for 5c Large 2 for 5c 24-5 C OLOR PLANE PHOTOS 25c Val. only 15c Clean, shiny, for covering luc sq.ft. 1/2×1/2×12"25c
 MAIR BRUSHES
 DOWELS

 Small 0c; Medium
 1/16x12⁻⁻-6.5c

 12c; Large.....15c
 1, Xx14⁻⁻.3.5c

 Gas Model.....25c
 1/4x18⁻⁻

 WET CELLS

 Penlices 2 for 15c

 Intermod 10c ca.

 Flashlight 10c ca.

 AV Boosters

 AC Charge 4.43

 Boosters

 U4" Scale
 13c
 10c; 112"-150.

 No. 85 X-ACTO Tool Chest \$12.50
 3 knives, full askid. blades, etc.

 No. 1, with 1 blade
 50.50

 With 0 Baserted blades
 50.50

 With 0 Baserted blades
 100

 No. 1, with 1 blades
 100

 No. 2, with 1 blades
 100

 No. 62, 2 handles, 12 blades
 50

 No. 82, 3 handles, 12 blades
 50

 No. 82, 4 handles, 12 blades
 50

 No. 82, 5 handles, 12 blades
 50

 No. 82, 5 handles, 12 blades
 50

 No. 82, 5 handles, 12 blades
 50

 No. 84, 5 handles, 12 blades
 50

 Sander 50015
 4.95
 305

 Yoot, 57,50; DE Luxe
 10.30

 Yoot, 57,50; DE Luxe
 5.00

 NiNG KUT HEGAL TREASURE
 5.00

 NiNG KUT HEGAL TREASURE
 10.00

SHIP MODELS ILLUSTRATED

FREE FLIGHT KITS

FREE FLIGHT KITS Status Construction Status Construction Status Construction Berkeley Buccancer Bases Status Construction Status Construction

CONTROLINE KITS

MODEL AIRPLANE NEWS . April, 1948

63



Checking Horsepower

(Continued from page 12) ing top speed obtained) you can see how your engine's output hp varies with engine speed. All runs must be made at top engine speed with each prop used. The results of these runs can be plotted in a smooth curve such as Fig. 1. If a few points seem scattered, recheck those runs since the correct curve will be smooth.

Just a note on ignition point flutter; if your points begin to flutter the hp will fall off rapidly, so set them closer together before continuing. When you have made a series of runs on your engine and found its power peak, try different fuels to see which give the most power.

When you mount another engine on the stand, check the calibration again because the difference in engine weight may require some change in the amount of lead shot needed for correct readings. If any questions arise during construction or operation of this test instrument, write us care of this magazine and we'll be glad to answer them.

Meet the Rudevator

(Continued from page 29)

the arm (#3) on the rotary tab shaft (#2) and stops the tab in that position. When the armature relaxes, the tab shaft resumes rotation. Almost no power is required of the rubber motor since it only drives the escapement shaft. The rubber motor never drives the rotary tab or viceversa. The rubber is good to the last twist, and since it will hold so many turns we find that winding once a day is sufficient. Actually the control could be designed without a rubber motor; the rotary tab could be used to operate the escapement, but a time lag would be involved and the overall response to signals would not be as fast.

There are four neutral positions on this type of escapement. This is more than we need; so we use one of them for stopping the airplane motor. The small switch (#8, 9) is normally closed and we wire it in series with the plus side of the ignition batteries. In one neutral position when the electro-magnet is relaxed a small drop of glue (#11) on the escapement shaft hits and opens this switch. We make this occur on the neutral position after down. One must remember not to dwell on this neutral position but to use any one of the other three unless he is ready to stop the engine. For this reason it is best to leave this switch disconnected and rely on an engine timer for the first few flights. The escapement opens this switch every time around, but it goes by so fast that the engine merely burps.

Now for the control head. This is nothing but a simple four point selector switch. We use a typical 12 point rotary selector switch with 4 of the detents flattened out. This leaves 8 detents, 4 of which are sloppy loose and 4 are normal tight and alternated with the sloppy loose ones. We use the loose ones for neutral so there is an extra feel for neutral without having to look at the position of the crank. The 4 tight detent positions are connected into the transmitter B battery. With the control in the left hand and the crank side of the box facing the operator, up is up, down is down, left is left and (you guessed it) right is right. Neutral is when the crank points to any corner of the box.

Synchronization with the rudevator is simple. With the transmitter and receiver on, your assistant starts the engine. The slipstream starts the rudevator rotating. Put the crank in any signal on position. The rudevator will stop in some position, say up. Turn the control box in your hand so the crank is pointing up. You are in sync. If you make a mistake and get out of sync in flight, do the same thing. Our rudevator escapement goes up, right, down, left or clockwise as viewed from the rear. So remember to turn the crank clockwise to stay in sync. We prefer it this way, but if you must operate like a pilot, turn the control box flat with the crank on top. Then forward is down and back is up and rudder remains the same. But you must crank counter-clockwise to stav in svnc.

There is one case where you can move the crank back and forth in both direc-tions and still remain in sync. This is when you are using rapid alternate left and right rudder alone to jockey the ship in for a spot landing, or when using ele-vator alone to do loops. Actually, the escapement goes through down while the rank goes through up, but who cares if you are only interested in the one control at the time. The crank can be turned as fast or slow as desired. As a check, we twirl the crank and listen to the rudevator escapement rattle in response.

Our ship was designed and built by Dick Schumacher of Burbank at a time Dick Schumacher of Burbank at a time when we expected to have to carry about 3 lbs. of radio apparatus. The present rudevator installation weighs 1 lb. com-plete and gross weight is 5 lbs. 10 oz. The 7 ft. wing gives it a glide almost like a sailplane. We fly it trimmed straightaway, of county and plantu of downthwart is of course, and plenty of downthrust is used to hold the nose down under power. Turns of 360° can be made under power before the nose drops dangerously. Power off turns are gentle and can be held to the landing Elevator down will not cause an outside loop but merely an increase in speed until the large stabilizer balances out. At this point up elevator produces a loop. Simple maneuvers like this are enough to keep one busy at first. The simple formula for our next job will be less airplane and more rudevator.

RUDEVATOR PARTS LIST

- No. Rear steady bearing-.032" Alum.--Washers soldered to shaft prevent fore aft motion.
- Rotary tab shaft—1/16" brass rod. Rotary tab shaft crank—.020" 3. brass sheet.
- Rotary tab shaft stop-.032" music wire 4. -one spoke of four-spoke escapement wheel is bent to form this stop. Escapement wheel-.032" music wire-
- 5. Escapement wheel—.032" music wire— has three plain straight spokes and one stop spoke (4). All spokes are soldered into drilled holes in a #0-80 brass nut —then unit is soldered to shaft. Escapement shaft—1'16" brass rod. Ignition switch platform—part of (27). Ignition switch movable contact—insu-bated=0.006" brass shoal contact
- 6.
- 8. lated-0.006" brass sheet-contacts, coin silver
- Ignition switch stationary contact-.006" 9. hrass
- 10.
- brass. Armature—1/16" iron. (Hole for shaft oversize to prevent binding—#0-80 nuts soldered to shaft.) Ignition switch cam—model airplane cement built up to required height on escapement shaft. Switch shown open (it is nearently ideated) 11.
- (it is normally closed). Escapement shaft crank—.020" music 12.
- 13. Rubber motor crank bearing-1/16" brass tube.
- Rubber motor hook—.020" music wire. Rubber motor—2 strands 1/32" or 1/16" 15.
- square—any practical length. Forward Bearing Bracket--.020" brass 16. sheet.
- 17
- Armature stop—part of (16). Armature return spring support—part 19.
- of (16).



Beautiful Biplane Control Model "PRECISION PREFINISHED" NO-CARVING KIT

Metal Parts.

CARL GOLDBERG'S

★ Formed Landing and Tail Gears.

★ All Necessary Formed Wire and

★ Wingspan 23½", Length 20".

Designed for .19 to .49 Engines.

Die-Cut Plywood Cabane Struts.

IFTY

★ Prefinished, Carved and Hollowed **Fuselage!**

★ BOTH Sets of Wings Precision Airfoiled

★ Stabilizer, Elevators, and Rudder Precision Shaped.

★ Finest Quality "Job-Selected" Materials: Balsa for Lightness, Hardwood for Stress.



MODEL AIRPLANE NEWS 😱 April, 1948



FRANK CUMMINGS OF LOS ANGELES NATIONAL A.M.A. CHAMPION SELECTS FOX .59 FOR CONTEST WINNING PERFORMANCE

FOR YOUR FREE FLIGHT, CONTROL LINE SCALE, STUNT, SPEED, OR RADIO CON-TROL JOB, INSIST ON A FOX HI-TORQUE OR HI-SPEED MOTOR. NO OTHER ENGINE POSSESSES SUCH DESIRABLE FEATURES AS THE FOX:

THE HI-SPEED MOTOR WEIGHS ONLY 91/4 OZ., DEVELOPS 11/8 H.P. AT 16000 R.P.M., IS EASY TO START EVEN WITH SMALL PROPS, COMPARES IN SIZE TO MOST .49 ENGINES. HAS A LONG EXTENDED SHAFT, IS IDEAL FOR STREAMLINE COWLING, WILL RUN IN ANY POSITION AS TRACTOR OR PUSHER, OPERATES AT PEAK PERFORM-ANCE WITH EITHER STANDARD IGNITION OR GLOW PLUG, THE ONLY MOTOR WITH A HORSE POWER TO WEIGHT RATIO OF 2 H.P. PER POUND.

BUILD AROUND, FLY AROUND A FOX, AND OUTFLY THE REST.

REMEMBER, "THE WORLD'S MOST VER-SATILE MOTOR."



1948 SOUTH GRAND AVENUE LOS ANGELES 7, CALIFORNIA

20. Armature return spring — ½" dia. solder to armature.

- 21. Armature bearing-.032" music wire
- soldered to bottom of armature. Coil-2 required-4 to 6 ohms total when connected in series; these were 22 from a code practice buzzer. Magnet back plate—1/16" iron. Escapement wheel 2d stop—.032" music
- 23. 24.
- wire. This is a labyrinth stop-rotation of escapement wheel is clockwise as viewed from rear-(up, right, down, 25
- Viewed from rear—(up, right, down, left)—as each spoke leaves first stop (25), it is caught by 2d stop. Escapement wheel first stop—.032" music wire. Must clear spokes of wheel. Both stops are soldered to (27). Base plate— λ_8 " hard balsa. Rear bearing bracket—.020" brass sheet. Both housing bracket—.020" brass sheet. 26.
- 27. #2-56 machine screws which bolt thru base plate & airplane structure. Assembly is checked for alignment after installation.

Skipper

(Continued from page 17)

scape, be sure that the entire ship is doped sufficiently to be really oil-proof. That means at least four coats of dope. We trust that somewhere along the line a friend has come to visit you and that you've been able to inveigle him into covering the wing. If not, call up somebody good at covering jobs (and tell him to bring the Silkspan). Or else do it yourself, the hard way. Ready to fly Skipper? With the model

balancing halfway between the leading and trailing edges, glide-testing should be attempted from shoulder height. If the model follows a relatively straight path, try higher launchings from overhead. Point it down at the ground about 30 ft. ahead of you, so that you won't stall it purposely. Since a small amount of incidence is built into the wing you should have no troubles so far. If the model dives or stalls, make adjustments on the wing incidence. To correct the diving tendency, add sheet balsa under the leading edge. For a stall cure, add sheet balsa under the trailing edge. The rudder tab should be offset to get a slight circle to the right.

Now for some power flights. For some undetermined reason the author's engine runs for only 30 sec. on a full tank, adjusted for a rich feed. By holding the model and monkeying with the fuel adjustment for 10 sec., an engine run of 20 sec. is had. (I don't ask questions-I just have fun). In any event, don't risk losing the model by using too long an engine run. If necessary, use a timer to cut off fuel or to close the air intake completely.

Well, to get back to flight-testing. Make power flight adjustments with thrust offset. Once your wing and tail surfaces have been adjusted in glide-testing, leave them be! For flights with the model circling to the right under power and in the glide, about 3° downthrust is needed. Adjust for a tighter circle with the rudder tab, if you want to, but use a little left thrust to compensate; the model should not be made to circle tightly under power, as the net result is a waste of power. A tight circle in the glide won't hurt, since the model will remain in small thermals. For those interested in contest work.

the weight of *Skipper* should be at least 10 oz. to conform with the 100 oz. per cubic inch rule. If it is necessary to add weight to bring the model up to specs, put the weight in the approximate center of the pod, as too high or low a center of gravity will make the model harder to adjust for power flight.

Don't be lackadaisical about putting your name and address on the modelthese things do get lost you know.



Design Forum

(Continued from page 24)

the pull of its mass. This creates an opposite force, Ps, due to the air pressure against the outward side of the fuselage, wings, and other parts of the airplane. The center of reaction of this air pressure is directed against the side of the plane at some particular point CLA. Theoretically this point would be the center of the side projected area of the airplane, and was named the "center of lateral area."

As a matter of fact this side pressure in various types may react at other points which, however, are not far from the CLA. In some planes it may be forward; in others it may be to the rear—above it or below it, but practical tests have shown that this CLA point may be used as the theoretical center of side pressure with very accurate results.

In Mr. Brown's airplane this side force acting at CLA when turning at high speed reacts above the CG. The CG pulling outward and the side force pushing inward creates a rolling couple which banks the plane inward. The further the CLA is above CG the greater this couple will be and the more it will bank the airplane against any resisting recovery forces that might develop. Many modelers say that the CLA has no effect, and they proceed to accept this steep banking of planes and apply corrective measures in the form of resisting forces. Briefly, they deny or overlook the disturbing forces and try to correct the trouble by applying recovery forces. By the latter we mean forces which roll the airplane back into normal position after it has been displaced. This produces constant rolling back and forth.

Anyone who has been at contests cannot deny that most of the airplanes flown bank critically. Some use large dihedral to produce restoring force and in so doing often make matters worse. Others reduce size of the fin; this is logical because if the fin is small and there is considerable area forward beneath the wing the nose will not drop as quickly as when the fin is large. Furthermore, there is more time to restore the airplane to its normal flight position laterally before the nose drops into a dive. In this way the fin is a deterrent to spiral instability but not a corrective. It only reduces the degree of spiral instability.

Some have conceived the bright idea of placing the fin low. Fig. 3, not to cure spiral instability but to create a nosed up position when the plane banks sideways under the effect of the high CLA. This does not cure the spiraling tendency but keeps the nose of the plane pointed upward so that it *spiral climbs* instead of spiral dives. Typical examples of this condition are pylon models. Take for instance the Zipper, which, it is claimed, is spirally stable. This is refuted by the fact that some flyers boast how well the model spiral climbs. By applying small fins and placing them in a low position, the designer has not eliminated the spiral tendencies but has merely directed them into a constructive maneuver instead of a destructive one.

Perhaps now you can see what is wrong with Mr. Brown's airplane. The CLA is considerably above the CG, Fig. 1. This in itself creates a spiralling tendency. Second, the fin or sideways tail area, is high. This causes the axis DD' which passes through the centers of gravity and lateral area to be slanted downward at the nose. The airplane rolls first about this axis DD' when banking due to external forces, and about axis

not already ordered, write National Ioday. THIMBLE DROME \$3.95 MINI-Power . . Action . . MOUNT Speed . . Plus Beauty Complete and Authentic Scale \$9.45 The Mini-Mount Transmission Unit, die-cast frame slips easily into the Thimble Drome chassis as shown in photo. Universal type Bange or radial mounts for all Class A and most Class B engines. Drilled and tapped, ready for installation. Unit, less gears... Unit, with ring and pinion 9.45 Some of the features include: Ball Bearing Axle Hangers—½ Inch Steel Axle, threaded and fitted with four speed-lock nuts—Adjust-able Allen Screw Lock Collar—Fly Wheel—L-147 Beveled, Hard-ened Steel Ring and Pinion Gears, and Y-2% Brass Bushings— Housing for Optional Addition of Ball Bearings for Bantam Engine headletics Housing for Installation.

Now that the demand for a good power transmission unit has been answered, the popularity of the Thimble Drome Racer will be greater than ever. Your National Dealer has or can get both the car

and transmission unit for you. Car is die cast aluminum with aluminum rubber-tired wheels, chrome exhaust stacks, wobble pump, simulated leather seat and back, instrument panel and numbers.

The Mini-Mount Handles all Class A -Most Class B Engines

Now! Power Transmission Unit for Thimble Drome Racer

Dealers!

Here is the double-barrelled sensation for 1948. If you have



"O.K." HIGH-VOLTAGE COILS



FASTER STARTS LONGER BATTERY LIFE

"O. K." High-Voltage Coils bring proven better performance to any miniature ignition type engine. Flight check starts and laboratory tests reveal they contribute positively to easier, faster starting and longer battery life. Pack a load of reserve power that pays off on the flight line. Made only of the finest materials, they have a clean, perfect finish with lifetime sealed end coverings. Every coil is tested and guaranteed. Sold complete with necessary high tension leads.

| Coil . | Α | for | Α | and | В | class | s i | engin | es | | \$2.5 | 0 |
|--------|-----|------|----|------|----|-------|-----|--------|------|-------|-----------|---|
| Supe | r-1 | Coil | С | for | B | and | С | class | engi | ines. | \$2.5 | 0 |
| Twin | C | lio | fo | r tw | 0~ | cylin | de | er eng | ines | | \$5.0 | 0 |

MATCHED CONDENSERS

| Strength and freshness assured as | they are her- |
|--------------------------------------|-----------------|
| metically sealed in moisture-proof E | Bakelite cases. |
| 200V for single cylinder engines | |
| 400V for two-cylinder engines | |

SOLD BY LEADING DEALERS





Be the first in your city to own and fly the Seabee. You can quickly assemble. No experience required. Just follow the 33 simple, step-by-step Production illustrations. Complete hardware furnished. Note corrugated wing and tail surfaces. Plexiglas windows, detachable motor hood, retractable landing gear Only kit with all exterior parts of pre-formed Phenopregsturdy, fough, durable and water-tight. U-Control, Jim Walker's U.S. Pat No. 2,292,416. DEALERS WRITE.

If your dealer can't supply, send coupon today Satisfaction guaranteed if not pleased, return kit in 10 days and money will be returned promptly



MONEY BACK OFFER

 THOMAS ASSOCIATES
 207 W. Palm. Burbank, Cabil.

 □ Enclosed find \$1 00—1 will pay Postman

 \$13 50 plus parcel post charges

 □ Enclosed find \$14 50 (check or money order)

 Please ship kit with parcel post prepaid

 □ Send descriptive folder free

 Name

 Address

 City
 Zone

RR' when banking under the influence of the pressure at the high center of lateral area. The combination of these rolling motions causes the plane to nose down.

You can readily determine this by holding an airplane at a low point at the nose and a high point at the rear, then rolling it sideways with your fingers without moving the position of your hands. You will note that the nose points downward. This is exactly what happens to Mr. Brown's airplane when it is in flight. It banks sharply due to the high CLA, noses down due to the high fin and downward slant of DD', and then proceeds on its merry way into a sudden left spiral. Because it noses down the speed increases. This causes a tighter spiral, and the tighter the spiral the greater the speed. Consequently, each effect builds up on the other until a crash results.

Mr. Brown can cure his troubles by doing one of two things. He can slant the thrust line down (relative to fuselage axis) and change the angle of wing and stabilizer, as shown in Fig. 3. In doing so he must be sure to raise the movable weights, such as batteries, coil, timer, etc., upward, so the CG will be raised and located on a horizontal line passing through the CLA or near it, as in Fig. 3. This line is parallel to the thrust line. This is not the best arrangement, how-Much better results will be obever. tained if the thrust line is raised to the position shown in Fig. 4, which is the most stable setup, because all points are on the thrust line. This raises the CG to the level of the CLA without the necessity of changing the angles of wing and stabilizer. It also brings the thrust line on a line with the CG or above it. The latter condition creates a tendency against looping at steep climbing angles, by producing a counter-clockwise corrective moment in combination with the downward pull of the CG.

Our readers will be greatly interested, I am sure, if Mr. Brown carries through these changes and writes to tell us of the results.

It is strange but true that the significance of lateral area effects has not even been realized by large airplane designers. Possibly this is due to the fact that pilots in large craft correct any deviation from normal flight with the controls before their planes reach critical positions that might demonstrate the significance of the lateral area factor. It was not until the Army attempted the design of pilotless aircraft that they encountered difficulties with spiral instability. To the consternation of those opposed to this theory, its application in the case of the Army corrected their troubles and pioneer research men are beginning to realize more and more the value of placing vertical areas or surfaces forward and below the CG in order to locate the CLA, on a line with the CG. Placing more area forward also makes it possible to use larger fins and thereby gain greater directional stability, because there is a definite proportion between the size of the fin and side area forward at the CG. The more area forward relative to the fin size the less the nose will drop be-fore recovery forces react to restore lateral equilibrium and in this way reduce spiral diving tendencies. With the CLA in the right position, banking will be very small and therefore the nose will have little tendency to drop regardless of fin size. However, a small fin allows restoring forces plenty of time to do their work properly before the nose drops dangerously.



We are not overlooking our U control modelers this month. Val Rich of Montpelier, Idaho sends us a very interesting suggestion. He believes in progress and not in merely swinging an airplane around at the end of a string for the sake of hearing the engine turn over. He suggests, and very wisely, that U control fliers use their hobby for experimenting. Perhaps some have realized that within their grasp they have an excellent instrument to test different wing forms, body shapes and aerodynamic combinations. For instance, a series of tests could be run to determine the most advantageous form of wing for any par-ticular type of flight. Some wings will be faster; others will give greater lift. Mr. Rich suggests that you construct

a special fuselage with engine and landing gear to mount detachable wings for test-Then make a set of wings with a ing. known and definite airfoil section and ith considerable area. Test runs should be ade to determine the plane's takeoff run and high speed. If your craft shows plenty of zip and climbing ability during tests, cut down the wingspan and area little by little, testing the plane after each time you trim the wing, until finally you have just enough area to lift the airplane from the ground without excessive climb. On each test, the takeoff run should be measured and the high speed clocked. For your first wing section we suggest Fig. 5-A. This will be very fast. By running the tests as described, you can determine the minimum area that will fly your plane; also by weighing your airplane you can find out exactly what this wing will lift per sq. ft.

Tiger deale

opero the bitte netroubl

Super

Super

If you keep accurate records of your test data you will find them invaluable in working out designs of future air-planes, both U control and free flight.

The second series of tests might be made with a wing having a crossection similar to Fig. 5-B. This wing should have the same span, area and outline as the original wing with crossection A. Place wing B on your fuselage and run through the same tests as you did with A. Measure the takeoff run and determine the high speed, endeavoring in each case to fly the plane under the same condi-tions and in the same way as in tests with wing A. In this way you can de-termine the relative speeds and lifting effect of the two wings. These tests will also tell you which wing is better for your speed models. It is possible that wing B will lift more than A, and because of this less area can be used, with the final result that the airplane with wing B will have less drag than with A.

Fig. 5-C indicates another interesting crossection for testing. This has an un-dercamber as well as an upper, with the undersurface bellied down slightly and then upward as it sweeps rearward from the leading edge. This downward bulge is called a "Philips Entry" and reduces drag often caused by undercamber. In fact, the wing crossection given in C, is highly efficient, and when the wing shaped in this manner from balsa it will give even better results in free flight than built-up wings. They are especially adaptable to planes with CO₂ engines. Planes having balsa wings with this crossection were flown out of sight as long ago as 1919

You will probably find that this undercambered wing is not suitable for high speed control line jobs but may prove quite satisfactory for control line stunt planes. Without question its lift coefficient is higher than either A or B, and the plane therefore will take off sooner

| | - | | | | | | | | | | |
|---|--|---|---|--|--|---|---|--|---|--|---|
| N | () | | ' (| DA | 77,5 | 5 | 9.9 |)5 | (REI FRO | DUCIEE M \$15. |) |
| | | | | | | Complete | with coil | CHER | SE E | XTR structions, ition wire | AS spark coil |
| | | | | | | Here is model | resto start Practice I 5 your c of the | ter and c Book. pportur famous | nity to b G. H. | uy the l Q. Gos | 948 948 |
| | 8 | | | P | | COIL & assemb uncond | ABSOL 5 CONI led by a itionally | DENSER experts, guara | fully be | Every en Every en ench run | gine and |
| | | | | Þ | | 4 | AN E | NGII Iriu | NEER MPH | ING | |
| | | Barrie | C | | | Neve | r Befo | re at a | So Lou | va Pri | ice! |
| are pr one. J | tising | , recommend ost hair-rais | ling, at | nd endo till you' | rsing this sci- ve ever exper | Indeed a standing structed i exhaustive —geared more that sponse. T entific achiev ienced will i woken record | n enginee G. H. Q. d nto the G. e scientific to the hig n that, the 'housands rement. It he yours w is for amagi | ring triu lesigners a . H. Q. ma e acrodyna hest possif e acid tes of users seems as i dth the G. zing perfor | nph-accom nd engineer otor everyth unic researd de degree o t an in all part f everyone i . H. Q. mo mance | iplished by rs, who har, ing that ye ch could pi of perfection overwhelmin s of the co in America tor—actuali and just in | out- e con- ars of roduce h. But hy re- buntry wants ly one hagine |
| -flies | mode | el planes from IONARY U | m 4 10 SE. Ea | 10 foot sy 10 st | wingspread. art and simp | AND JUST le to run, | AS EFFIC | CIÊNT FO | R BOATS, | MIDGET | CARS |
| | | KIT PAI | RTS. (| | SCREWDR | | | Sa.35 | SI EXT | RA | log of |
| 0 | ER | 100,000 | | USE | TODAY!! | | | bun boat | dreds of mo | del engine, d hobby | plane, items. |
| 4 Port 5/16" | 2 Si Diam | troke Cycle. . Rotation, | ⊰≨″St Either | trake. I Directio | 5/16" Bore. an. Invertibl | 300-7,000 R e. 1/5" H.F | .P.M. Bea . Class C | aring Surf under NA | ace 11/4" L A Rules. | ong, Crank | shaft, |
| S | E | N D | 0 |) N | LY ship pres | \$1 | . 0 0 |) | Shipped . O. D. | l Collect Some D | av |
| L | | | | 0110 1 | e sinp prep | | | | | | - 1 1 |
| G. H | I. O | . MOT(| ORS, | DEI | PT. M-48 | B, P.O. | BOX 1 | 93, ST/ | A. O, N. | Y. 11, I | Ν.Υ. |
| G. H | ak way of r the ; or t new uels, oday | es An Perfo Dut in front new Tiger he old stand r needle val | DRS, JCC IN A In mod Glo-fri Joy, Tor Vers for Vers for Vers for Vers for | DEI JC Add Bet el engi uels-A ger reg reger reger uel Pum | PT. M-48 | ne Ask your ignitionless slend. See. patrol with s, time and | BOX 19 | 93, ST/ Tiq F U E UM 69 | L PS | Y. 11, P | 4. Y. |
| G. H M Sler for brand brand brand brand brand brand er Glo er Glo | ak way (r the i or l new uels, oday —A. | es An Perfo out in front new Tiger he old stand r needle val and get a 1 Supe Petroleum Methanol | DRS, JORS, JOR JOR JOR JOR JOR JOR JOR JOR JOR JOR | DEI DEI Aode Bet el engi uels-A iger reg r precisi uel Pum lo Fue | PT. M-48 P el Engi ter! ne operation and B for to a start to n engine co p to save ga els c il fortified. F | Ask your ignitionless ontrol with s, time and Pints \$1,00 | BOX 19 | FUE UM 69 | L PS | Y. 11, P | -, , , , , , , , , , , , , , , , , , , |
| G. H ser is solar for aration brand | ak way (c ; or I new uels, oday | es An Perfo out in front new Tiger he nedd stand and get a Supe Petroleum Methanol | DRS, JOC | DEI JC Add Bet el engi uel Pum inst, 75 castor o | PT. M-48 | Ask your ignitionless ontrol with s, time and Pints \$1.00 | BOX 19 | | L PS | Y. 11, P | OBBY RAFI |
| er is sler fo sration new i ible— ier Gla wer Gla Wr Too | ak way of ; or I new uels, oday — A. — B. | A. MOTO es An perfo out in front new Tiger he old stance in reading and and get a l Supo Petroleum Methanol | DRS, JOC In mad Gla-Fri Isger Ft er-Gil base, c | DEI JC Add Bet el engi uel Pum to Fut castor o | PT. M-48 P el Engi ter! ne operation ward B for ward B for ward B for ward B for ward B for bios are ga els c d for light tion For light | Ask your ignitionless blend. See. ontrol with s, time and pints \$1.00 Ger - FU and B ionless C | BOX 19 | FUE FUE 69 | L PS C | Y. 11, P | OBBY RAFI PLIEJ |
| G. H M er is v sler for er dio new i ble er Glo wr Too | ak ak r the is or li r the uels, oday | es An Perfo out in front new Tiger he need stand and get a Supo Petroleum Methanol | DRS, JORS, J | DEI JC Adde Bet el angi uel Pum inst, 75 castor o C | PT. M-48 PT. M- | ne Ask your ignitionless ontrol with s, time and Pints \$1,00 | BOX 19 Fits Standa Pint Can ELS Opera- Hugs 00 | FUE FUE 69 | A. O, N. | Y. 11, P | OBBY RAFI PLIES |
| G. H Participation of the second sec | ak vay of r the inew, ioday | A MOTO | DRS, JOC In mod Glo-fri isger ft base, p base, c | DEI JC Adde Bet UPum UPum UPum Co Fuc Sastor o | PT. M-48 P el Engi ter! ne operation ular 3 to 1 to and B for ular 3 to 1 to to save ga els c dil fortified. F GLO A For Igniti tion wi 75c co NEE | Ask your ignitionless plend. See ontrol with s, time and and st. and B ionless C ith Glo-P and \$1. BETTE DLE VA | BOX 19 Fits Standa Pint Can ELS Pera- lugs 00 R LVES | FUE FUE 69 | A. O, N. | Y. 11, I Y. | OBBY RAFT PLIES |

TIGER PRODUCTS CO., 13014 Baltimore Ave., Chicago



parts and materials required to build this engine . . . a discarded CO₂ cylinder for a compression tank plus a few odd pieces of metal found in most scrap boxes. Entire jet engine can be built quickly and easily with ordinary hand tools. Small amount of welding is necessary.

The M.E.W. 601 engine runs from three to five minutes. Uses gasoline for fuel. Is easy to start . . . requires no ignition or external starting apparatus. Copyrighted plans for the M.E.W. 601 are fully illustrated and easy to follow. Complete plans only \$1.00 postpaid. No CODs please.



work.

Pointed tips only absorb power without delivering proportional thrust.

We hope that other readers will send in new designs for criticism and any questions which may be puzzling them.

The answers to many questions sent us in the past are given in MODEL AIRPLANE DESIGN AND THEORY OF FLIGHT by Charles Hampson Grant, a 528 page book published by Air Age Inc. (551 Fifth Ave., New York 17). We suggest that those who

are seriously interested in the science of model aeronautics obtain a copy of this



used with a .6 engine. The only other highly critical factor in a control line plane is the propeller. Mr. Stripko has chosen well in this case. An 8" diameter and 12" pitch should give very high speed. The blades on such a propeller should be approximately 3/4" to 1" wide maximum with rounded tips. Pointed tips only absorb power without delivering proportional thrust.

We hope that other readers will send in new designs for criticism and any questions which may be puzzling them.

The answers to many questions sent us in the past are given in MODEL AIRPLANE DESIGN AND THEORY OF FLIGHT by Charles Hampson Grant, a 528 page book published by Air Age Inc. (551 Fifth Ave., New York 17). We suggest that those who are seriously interested in the science of model aeronautics obtain a copy of this work.

The new M.E.W. 601 engine costs you practically nothing to build. In fact, most modelers will already have all the necessary parts and materials required to build this engine . . . a discarded CO₂ cylinder for a compression tank plus a few add pieces of metal found in most scrap boxes. Entire jet engine can be built quickly and easily with ordinary hand tools. Small amount of welding is necessary.

AFFORD TO OWN

The M.E.W. 601 engine suns from three to five minutes. Uses gasoline for fuel. Is easy to start...requires no Ignition or external starting apparatus. Copyrighted plans for the M.E.W. 601 are fully illustrated and easy to follow. Complete plans only \$1.00 postpaid. No CODs please.



MODEL AIRPLANE NEWS . April, 1948
AT LAST! WHAT MODELERS HAVE LONG NEEDED! An Up-to-Date Manual & Reference

Book on Model Motors!

THERE has been a growing need for a complete, up-todate manual and reference book on model motors to aid model builders in the intelligent use of their powerplants. MODEL MOTOR MANUAL was long and carefully planned to fill this need!

The publishers commissioned LOUIS GARAMI, widely recognized as the top expert in the field of miniature recognized as the top expert in the field of miniature received as the top expert in the field of miniature reconstruction with HOWARD McENTEE (Editor of Model Airplane News magazine), to amass all the essential material for such a comprehensive volume. Alan Orthof, one of America's outstanding aeronautic draftsmen, was also engaged to illustrate this book with his exceptionally fine drawings.

The combined efforts of these technicians have produced one of the most authoritative and useful books in the history of model activity!

The reader is first given a thorough explanation, by text and illustration, of the function of the model motor and the ignition system. Then he is made acquainted with the actual mechanical design features now used in commercial engines, and with the manufacturing processes that produce these units—such as grinding, milling and lapping.

The authors departed from the traditional method of classifying motors by number of ports employed—they found it more logical to identify them by the means used to bring fuel into the cylinder. The practicability of this new method is proved by the fact that although many new motors have reached the market all fit readily into the categories described in Chapter 5.

Besides a comprehensive coverage of every phase of model motor operation, this new book presents helpful tables, charts and data, and a large photograph section of: American gas, jet and diesel engines, as well as Foreign diesels.

Technical terms are avoided whenever possible, for this book is intended for the beginner as well as the expert, both of whom will find it an invaluable aid in the intelligent use of their powerplants!







CONTENTS

Basic Principles of the Model Motor Operation of the Model Motor The Ignition System Fuel, Lubricant and Carburetion Types of Model Motors Engine—Upper Half Ignition Timers The Sparkplug Coil and Current Wires and Connactions Starting the Engine Trouble Shooting Compression Advancing and Retarding the Spark Trouble Shooting After Installation

Care of the Motor The Flight Timer The Propeller Engine Operation (Oil and Gas) A Simple Engine Test Mount Home and Factory Repair Making Accessories Testing for Performance Testing Plane Performance Four-Cycle Motors Diesel Motors Multi-Cylinder Motors Model Motors of the Future Choice of Motor Appendix Index

MODEL MOTOR MANUAL is no small booklet—it is beautifully bound in cloth and gold stamped . . . contains 228 pages, 6 x 9 inches . . . 112 highly skilled detailed drawings and photographs. Get your copy of this limited first edition from your favorite model shop—if he cannot supply you, order direct from publisher.

-----Mail This Coupon Today!------

AIR AGE INC. 551 Fifth Ave., New York 17, N.Y.

Please send me postpaid a first edition copy of your new book MODEL MOTOR MANUAL, for which I enclose herewith \$3.00 (Outside U.S.A. \$3.25.)

| Name | | |
|---------|--------------------|--|
| Address | | |
| City | Dist. No. State | |





Ohlsson & Rice Are Producing Two New Model Engine Fuels

Why? All the years that we have been manufacturing model engines, Ohlsson & Rice have never recommended any engine fuel other than 3 parts gasoline and 1 part SAE 70 lubricating oil.

We were, of course, aware that many gas modelers were using the so-called "hot" prepared fuels. Gas models are flown for fun, and the more power the more fun, thrills, and performance.

However, it is common knowledge among engine manufacturers that these "hot" fuels as a class have been the major cause of all model engine troubles.

The reason is simple: Operating engines at high R.P.M. day in and day out requires high quality expensive labricants which were simply not included in the average prepared fuel.

In a nutshell, the situation was this: Ohlsson & Rice engines, and other good engines, were capable of giving gas modelers consistent high speed performance. But the engine manufacturers' efforts were constantly being defeated, and the engines gummed up and otherwise damaged by inferior fuels. Producing in small quantities, the makers of these fuels were unable to use high grade materials and sell their fuels at a price which the average modeler could afford to pay.

WITH THE APPEARANCE OF THE GLOW-PLUG several months ago, it seemed for a time that perhaps the answer to dependable high speeds had been found: that the problem was not fuel, but ignition. However, whatever additional work may remain to be done on the glow-plug, it soon became apparent that here too *fuels* were falling down that the glow-plug alone was not the answer.

For these obvious reasons-in order to protect our engines and give gas modelers the performance they were entitled to, this company—as the world's largest model engine manufacturer—has for some time been studying high performance fuels and in particular high performance lubricants for two-cycle engines.

In carrying out the research, one of our first steps was to hire a competent chemical engineer to investigate all possible materials and develop fuels that would embody the latest findings of science.

NOW AFTER MONTHS OF WORK and the construction of a complete fuel processing plant, Ohlsson & Rice Fuel Laboratories is prepared to supply modelers not just one but two superior gas engine fuels—"supreme fuels for model engines." As a result of tests with every type of engine, both standard ignition and glow-plug, contest and pleasure, we are in a position to change our long-standing recommendation and invite gas modelers to try really "hot" model fuels.

In every way, Ohlsson & Rice fuel No. 1 and No. 2 are hot, hotter than any formula ever before offered to model builders! Together with superior combustion and powerproducing characteristics, they also contain the most expensive lubricants ever used in such fuels.

So complete is the combustion and so clean-burning are these two fuels that they not only do not form carbon, sludge, and engine varnish, as do other fuels, but they actually remove and expel carbon, sludge and varnish that previously had been deposited.

LAST AND NOT LEAST, in spite of our sizable investment and the exceptionally high cost of the materials used, these fuels are offered at *competitive* prices, in line with Ohlsson & Rice's long-established policy of setting the "standard of the model world." Both fuels are available at your dealer's for immediate delivery



A new formula Cantaining special high performance lubricants and high quality fuel ingredients designed for use in any standard ignition engine. An ideal cool running fuel for sport Rying Tray starting, clean running, and cool operating. Supplies smooth power. Due to high grade ingredients used, it is recommended as break in fuel for new engines.

Ohlsson & Rice No. 2 For Glow Plug

Methanol base in a new to. mula combining latest scientific fuel ingredients with special high performance lubricants. Easy starting, clean running, and cool operating, supplies steady smooth power. This fuel is recommended as a high speed racing fuel and can be used in engines having standard ignition if a fuel cut-off system is installed.

OHLSSON & RICE, INC., Emery at Grande Vista, Los Angeles 23 •

PINTS

75c

QUARTS

51.40

htson & Riv

Standard of the Model World

PINTS

75c

QUARTS

\$1.40

